

(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Criterion 3: Research, Innovations and Extension

Key indicator 3.3: Research Publications and Awards

3.3.1: Number of research papers published per teacher in the Journals notified on UGC care list during the last five years

Index

S.No	Description	Website link
3.3.1.1	Number of research papers published per teacher in the Journals notified on UGC care list during the last five years	Click to View



Dr.R.PANNEERDHASS,ME,Fh D.
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

3.3.1.1: Number of research papers published per teacher in the Journals notified on UGC care list during the last five years

#### **CONTENTS**

S.No	Description	Page No
1.	AUTHENTICATION CERTIFICATE	1
2.	Presence of the paper In the UGC care List /SCOPUS/ Web of Science / other	2-84
3.	Proof of Publication	85-159

VILLUPURAM 605 601

Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

#### AUTHENTICATION CERTIFICATE

3.3.1.1: Number of research papers published per teacher in the Journals notified on UGC care list during the last five years

Details		Λ	cademic Ye	ar	
Details	2022-2023	2021-2022	2020-2021	2019-2020	2018-2019
Number of Papers published	26	70	49	63	35
Total no of Papers Published			243		

Lower

Dr.R.PANNEERDHASS, ME, Ph.D...
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



A. R. ENGINEERING COLLEGE
(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

				Link to the rec	ognition in L	the recognition in UGC enlistment of the journal / Digital object	e journal / [	Digital object
TITLE OF PAPER	NAME OF THE AUTHORS	DEPT OF THE AUTHOR	Name of Journal	Year of Publication	ISSN number	Link to website of the journal	Is it listed in UGC Care list	Link to article/ paper/ abstract of the article
1							/Scopus/ Web of Science /other,	
Reduction of Voltage Stress in			Internationa l Journal of				No	
a Medium Frequency Transformer using IFBTL DC/DC Converter for PMSG Based Wind Turbine	A. sugunya	ECE	Electrical and Computer Engineering	2021-2022	1118	21/4/3.pdf		2021/4/3.pdf
Life prediction and statistical			Internationa l Journal of		2454-	http://ijrmmae.i	No	http://ijrmma e.in/Volume7
aloevera in composite specimen	A.Arulkumar	Mech	Mechanics and Mining Sciences		1435	4/paper2.pdf		2.pdf



Dr.R.PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
PRINCIPAL
POST,
A.R. ENGINEERING COLLEGE
A.R. ENGINEERING LAYAM,
A.R. ENGINEERING COLLEGE
POST,
A.R. ENGINEERING COLLEGE
Ph.D.,
A.R. ENGINEERING PALAYAM,
A.R. ENGINEERING



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

R. 605 601 CT	Varying Progrance	Grid Connected Multilevel Inverter Topology Suitable for	With 45 iiii ciilos cemiology	Implementation of low power 17-transist or true single-phase clocking flip –flop designs		smart utilization of power using new bidirectional intelligent solid state transformer		Development of Smart Control System for Improved Energy Management in Building	Power and Area Optimization	An effective GDI (Gate Diffusion Input) Based 16- bit Shift Register Design for
		A.Sugunaya		A.Madhavan		A.Chandrasekaran		A.Chandrasekaran	The state of the s	A.Chandrasekaran
		EEE		CSE/ECE		EEE		EEE		EEE
	Computer	International of Journal of Electrical and	Engineering	International I Journal of Electrical and Computer	Eugmeering	Internationa I Journal of Electrical and Computer	Engineering	Internationa I Journal of Electrical and Computer	Computer Engineering	Internationa I Journal of Electrical and
A.R.F	TANK!	2020-2021		2020-2021		2020-2021		2019-2020		2019-2020
ADAKUCH PPIYAMPI PPIYAMPI	PRINCE	2456- 172X NEEROP		2456- 172X		2250- 1118		2456- 172X		2250- 1118
KAPPIYAMPULIYUR FOT.	BALAYAM,	2456- /Volumeatsave4/ 172X ASS Baper7.pdf PANNEEROHAS Baper7.pdf	1/:-:	http://iriges.com /Volume5Issue4/ paper4.pdf		http://ijice.in/20 20/5/5.pdf		http://iriges.com /Volume4Issue3/ paper21.pdf		http://ijice.in/20 19/4/4.pdf
			No	,	No	Č	2	70	7	S <sub>o</sub>
		om/Volume4l ssue4/paper7	l in distance of	om/Volume5l ssue4/paper4 .pdf	http://irigas.c	http://jiice.in/ 2020/5/5.pdf		http://iriges.c om/Volume41 ssue3/paper2 1.pdf		http://ijice.in/ 2019/4/4.pdf

1



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

E/VIIIII O	Smart Drainage Management to Mitigate Summer Drought Damage in Nordie Agriculture within the Circular Hohomy Framework	Experimental behavior of fiber reinforced concrete using recycled aggregate with agrowaste replacement	Design and analysis of single layer quantum dot-cellular automata based 1- bit comparators	kinetic study on the effect of water hyacinths in foodwaste biogas production	
	B.Anandhakumar	B.Anandhakumar	Amutha.S	A.Vinoth	
	Civil	Civil	CSE	Civil	
	Internationa I Journal of Rock Mechanics and Mining	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Engineering
Co	2022-2023	2019-2020	2020-2021	2021-2022	
N 1 C N	2454- 1435 Dr.R.PAN	2347- 6729	2454- 1435	2454- 1435	
GINEEKING AYA	1435 Dr.R.PANNEERABLE COLLEGE Dr.R.PANNEERABLE COLLEGE	http://jrrset.com /2023/March/pa per5.pdf	http://ijrmmae.i n/Volume6Issue 2/paper4.pdf	http://ijrmmae.i n/Volume7Issue 3/paper7.pdf	
P. Control of the Con	No No	No.	No	No	
	http://ijrmma e.in/Volume( lssue1/pape	http://irrset.c om/2023/Ma rch/paper5.p	http://iirmma e.in/Volume6 lssue2/paper 4.pdf	http://ijrmma e.in/Volume7 Issue3/paper 7.pdf	<u>.pdf</u>

A.R.ENGINEER.... A.R.ENGINEER... A.R.ENGINEER.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

EERING	Fabrication of mems pressure sensor on thin film membrane	Investigation of Properties and Dynamics Mechanical Analysis of Glass fiber / Human hair / Coir fiber reinforced epoxy polymer Hybrid Composites	Effect of Mechanical, Thermal Properties and Drilling Parameters on Groundnut Shell-Broom Fibre-Reinforced Epoxy Composite	
	Anbazhagan R	Anbazhagan R	Anbazhagan R	
	Mech	MECH	Mech	
	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal for Research in Applied Science and Engineering Technology	Sciences
Dr.R.PAN	2	2021-2022	2021-2022	
NEERDH!	2348-	2347- 6729	2347- 6729	
Dr.R.PANNEERDHASS, M.C.	http://irrset.com /2021/Oct/paper 2.pdf	http://www.ijrm mae.in/Volume7 lssue2/paper3.p	http://jrrset.com /2022/Novembe r/paper4.pdf	
	Z	Z	N <sub>o</sub>	
	http://irrset.c om/2021/Oct /paper2.pdf	http://www.ii rmmae.in/Vol ume7Issue2/ paper3.pdf	http://irrset.c om/2022/Nov ember/paper 4.pdf	3.pdf



Dr.R.PANNEERUCIPAL

PRINCIPAL

A.R.ENGINEERING COLLEGE

VADAKUCHIPALAYAM,

VADAKUCHIPALAYAM,

VAPPIYAMPULIYUR POST,

KAPPIYAMPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

EN COLUMN TO COL	Grid Connected Multilevel Inverter Topology Suitable for Solar PV Applications with Varying Irradiance	smart utilization of power using new bidirectional intelligent solid state transformer	Hybrid Composite Materials: Machinability of Luffa with Groundnut shell Fiber Reinforced Epoxy Polymer	preparation, properties and machinability study of luffa fiber - groundnut shell reinforced epoxy composite
	B. Keerthana	B.Keerthana	Anbazhagan R	Anbazhagan R
	EEE	EEE	Mech	Mech
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal for Research in Applied Science and Engineering Technology
Dr.R.PANNEERUKASS,	2020-2021	2020-2021	2021-2022	2021-2022
PRINCIPAL PRINCIPAL PRINCIPAL COLLECT LENGINEERING COLLECT PRINCIPAL PURAM-605 601. VILLUPURAM-605 601.	2456- 172X	2250- 1118	23454- 1435	2347- 6729
LEGE POST,	http://irjges.com /Volume4Issue4/ paper7.pdf	http://ijice.in/20 20/5/5.pdf	http://www.ijrm mae.in/Volume7 lssue1/paper4.p df	http://jrrset.com /2022/Septembe r/paper5.pdf
	Z	Z. No	Zo	N <sub>o</sub>
	http://irjges.c om/Volume41 ssue4/paper7 .pdf	http://ijice.in/ 2020/5/5.pdf	http://www.ii rmmae.in/Vol ume7Issue1/ paper4.pdf	http://jrrset.c om/2022/Sep tember/paper 5.pdf

VILL



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

EN VILLUPURAM F	Growth, structural, optical, spectral and mechanical studies of adp single crystal	soil area network for landslide predict and avoidance system based on arm cortex m3, mems and gsm	SBFET -Based Full Adder with Ultra-Low Leakage and High Speed	Power Flow of MTDC Using Droop Control & Impact of DC Voltage Drops	Error control system incellular network
	Bharathiraja.R	Bharath	B.Lakshmi	B.Keerthana	B.Keerthana
	S&H PHYSICS	ECE	ECE	ECE	EEE
	Internationa I Journal of Electrical and Computer	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPURAM-605 601.	2019-2020	2019-2020	2021-2022	2021-2022	2021-2022
ENGINEERING COLLE VADAKUCHIPALAYAM, VADAKUCHIPUR POS APPIYAMPULIYUR 601.	2250- 1118 JEERDHASS,M	2454- 1435	2231- 2099	2456172 X	2456- 172X
λΜ, 50ST, 301.	2019-2020  2250-  1118 1118 119/4/5.pdf  PANNEERDHASS, M.E., Ph. 9/4/5.pdf	http://ijrmmae.i n/Volume5- lssue- 1/paper8.pdf	http://njice.in/2 021/1/3.pdf	http://irjges.com /Volume7Issue2/ paper1.pdf	http://iriges.com /Volume6Issue2/ paper7.pdf
	No	No	N <sub>o</sub>	No	S.
	http://ijice.in/ 2019/4/5.pdf	http://ijrmma e.in/Volume5 -Issue- 1/paper8.pdf	http://njice.in /2021/1/3.pd f	http://iriges.c om/Volume71 ssue2/paper1	http://iriges.c om/Volume61 ssue2/paper7

AJR.ENGINEERING COLCE KAPPIYAMPULIYUR POST, VILI UPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

An: in e	Inv ma gro reir hyb	De joi	COI	» -
Analysis of surface preparation in en8 steel materials by using coating methods.	Investigation of properties and machinability of luffa with groundnut shell fiber reinforced epoxy polymer hybrid composites	Design and analysis of knuckle joint using fea software	connectivity in a fuzzy graph	
D.Manikandan	D.Manikandan	D.Manikandan	Chandrapraba.R	
Mech	Mech	Mech	S&H MATHS	
Internationa I Journal of Electrical and Computer	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Engineering
2019-2020	2018-2019	2018-2019	2022-2023	,
2456- 172X 0HASS,ME	2454- 1435	2454- 1435	2454- 1435	
2019-2020 2456- /Volume4lssue2/ paper18.pdf	http://iirmmae.i n/Volume4- lssue- 4/paper5.pdf	http://ijrmmae.i n/Volume4- Issue- 3/paper11.pdf	http://iirmmae.i n/Volume7Issue 4/paper3.pdf	
	Z o	No.	No	
om/Volume4 ssue2/paper: 8.pdf	http://iirmma e.in/Volume4 -lssue- 4/paper5.pdf	e.in/Volume4 e.issue- 1ssue- 3/paper11.pd f	http://ijrmma e.in/Volume7 Issue4/paper 3.pdf	

DI.R.PARRIVEIPAL

PRINCIPAL

COLLEGE

PRINCIPAL AYAM,

A.R.ENGINEERING COLLEGE

VADAKUCHIPALAYAM,

VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST,

KAPPIYAMPULIYUR 601.

FOS 601 CO



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

* CO 300 7710 C	Life prediction and statistical analysis of e-glass faber with aloevera in composite specimen	Assessment of open central hole on the stress concentration factor of glass fibre-coconut coir-human hair hybrid composite	Experimental investigation and buckling analysis of woven glass epoxy laminated composite plate	
	D.Manikandan	D.Manikandan	D.Manikandan	
	Mech	Mech	Mech	
	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal for Research in Applied Science and Engineering Technology	Engineering
DIR. PANNE A.R. ENG! VADA KAPPIY VILL	2022-2023	2021-2022	2019-2020	
PANNEERUITAL PRINCIPAL PRINCIPAL COLLEGE PRINCIPAL AYAM. R.ENGINEERING COLLEGE VADAKUCHIPALAYAM. KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	2454-	2348- 3105	2347- 6729	
A.R.ENGINEERING COLLEGE A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	http://ijrmmae.i n/Volume7Issue 4/paper2.pdf	http://jrrset.com /2021/Nov/pape r2.pdf	http://jrrset.com /2019/December /paper9.pdf	
	No	No	No	
	http://ijrmma e.in/Volume7 lssue4/paper 2.pdf	http://jrrset.c om/2021/Nov /paper2.pdf	http://irrset.c om/2019/Dec ember/paper 9.pdf	



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

R.EN					
VILLUPURAM TO SOO	Growth, structural, optical, spectral and mechanical studies of adp single crystal	Grid Connected Multilevel Inverter Topology Suitable for Solar PV Applications with Varying Irradiance	smart utilization of power using new bidirectional intelligent solid state transformer	English language teaching and conversational	Non-verbal communication: focus on recruitment interview for freshers
	Devika.D	D.Sureshkumar	D.Sureshkumar	D.Sampathkumar	D.Sampathkumar
	S&H PHYSICS	EEE	EEE	English	English
	Internationa I Journal of Electrical and Computer	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
A.R.ENGIY A.R.ENGIY VADAI KAPPIY	20	2020-2021	2020-2021	2019-2020	2019-2020
A.R.ENGINEERING COLLEGE A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPUR POST, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR 605 601.	2250- 1448 ERDHA\$\$	2456- 172X	2250- 1118	2456- 172X	2456- 172X
YAM, R POST,	http://ijice.in/20 19/4/5.pdf ,M.E.,Ph D.,	http://irjges.com /Volume4lssue4/ paper7.pdf	http://ijice.in/20 20/5/5.pdf	http://irjges.com /Volume4Issue4/ paper6.pdf	http://irjges.com /Volume4Issue2/ paper17.pdf
	No	No	No	No	No
	http://ijice.in/ 2019/4/5.pdf	http://irjges.c om/Volume4! ssue4/paper7	http://ijice.in/ 2020/5/5.pdf	http://iriges.c om/volume4I ssue4/paper6	http://irjges.c om/Volume4! ssue2/paper1 7.pdf



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	_																								
	A STATE OF THE STA			product of fuzzy matrices	Bounded sum and bounded		一日 明月十二日 人工人工 中国国际的			(90,000)	with 45 nm cmos technology	clocking flip -flop designs	17-transist or true single-phase	Implementation of low power	U	basedoptimization	weightteaching-learning-	usingadaptiveinertia	in smart grid	economic energy equilibrium	opullar load control for	ontimal load and 16			
				Dr. I. Silambarasan								Dhanalakshmi v					,	Dhanalakshmi V							
				S&H								CSE/ECE						CSE							_
UT.10.	3	Surgmeeting	Computer	and	Flactrical	Internationa			Engineering	Computer	and	Electrical	I Journal of	Internationa	Sciences	and Mining	iviectianics	Machania	Pools	1 Ioumal of	Internationa		Į.	Engineering	- !
I.K. Spied Think Cip	NAMESCROHASS, M.E., PHO.,	ς		2018-2019								2020-2021						1202-0202							•
7	SS,M.E.,Pr			406-414							X7/T	1770	2456-				(	1435	2454-						
í	0.,	uzzy Matrices	ed Product of F	1843 Bounded	ublication/33088	earchgate.net/p	https://www.res	4			paper4.ndf	/Volume5Issue4/	http://irjges.com				2/paper5.pdf	n/Volume6Issue	nttp://ijrmmae.i	7,					
								No						No						Zo	:				
	rices	of Fuzzy Mat	m and Boun	Bounded Su	n/330881843	net/publicatio	researchgate.	https://www.		.pdf	ssue4/paper4	om/Volume5I	nttp://irjges.c			5.pdf	issue2/paper	c.iii/ volulileo	e in Moliman	http://iirmma				_	



A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

* 605 601 C	NG.	Algebraic Operations on Pythagorean Fuzzy Matrices		Hamacher sum and Hamacher product of fuzzy matrices
		Dr. I. Silambarasan		Dr. I. Silambarasan
	15	S&H		S&H
A.R.ENC VADD KAPP	Dr. Ravani	Internationa I Journal of Electrical and Computer Engineering		Internationa I Journal of Electrical and Computer Engineering
A.R.ENGINEERING CYAM. A.R.ENGINEERING CYAM. VADAKUCHIPALAYAM. VADAKUCHIPALAYAM. VADAKUCHIPALAYAM. VILLUPURAM-605 601. VILLUPURAM-605 601.	RAPARWEERDHASS, M.E., Ph.D.,	2018-2019		2018-2019
POST,	E.Ph D.,	81-90		116-131
	FUZZY- MATRICES.pdf	OPERATIONS O  N PYTHAGOREA  N FUZZY MATRI  CES/links/5e2ed  59c458515e2e87  55b2e/ALGEBRAI  C-OPERATIONS-  ON-  DYTHAGOREAN	https://www.res earchgate.net/pr ofile/l- Silambarasan/pu blication/338833	https://pdfs.sem anticscholar.org/ 35cc/bbe9310e4 0b8384afb96191 62138771737e2. pdf
			No	No
	OPERATIONS- ON- PYTHAGOREA	LGEBRAIC OP ERATIONS O N PYTHAGOR EAN FUZZY MATRICES/lin ks/5e2ed59c4 58515e2e875 5b2e/ALGEBR AIC-	https://www. researchgate. net/profile/I- Silambarasan /publication/	https://pdfs.s emanticschol ar.org/35cc/b be9310e40b8 384afb96191 62138771737 e2.pdf



A. R. ENGINEERING COLLEGE (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post, Villupuram-605601,Tamilnadu.

100			
Implication Operator On RING Pythagorean Fuzzy Set	Commutative monoid of Pythagorean fuzzy matrices	Hamacher Operations of Intuitionistic Fuzzy Matrices	
Dr. I.Silambarasan	Dr. I. Silambarasan	Dr. I. Silambarasan	
S&H	S&H	S&H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2019-2020	2019-2020	2018-2019	
69-78 VEERDHA	191-198	81-91	
http://www.ijstr.  org/final-  org/final-  print/aug2019/l  mplication- print/signerator-On-	https://www.ijcs eonline.org/pub _paper/107- IJCSE-06602.pdf	https://www.res earchgate.net/p ublication/32338 5451_Hamacher _Operations_of_ Intuitionistic_Fuz zy_Matrices	
No	No	N <sub>o</sub>	
http://www.ij str.org/final- print/aug201 9/Implication- Operator-On- Pythagorean-	https://www. ijcseonline.or g/pub_paper/ 107-IJCSE- 06602.pdf	https://www.researchgate.net/publication/323385451_Hamacher_Operations_of_Intuitionistic_Fuzzy_Matrices	N-FUZZY- MATRICES.pd

A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

				4 \$	A Section 1			
The second second	An Interval-Valued Intuitionistic Fuzzy Matrices Based on Hamacher Operations		An Interval-Valued	New operations for Pyhagorean Fuzzy Matrices	Hamacher operations on Pythagorean fuzzy matrices			
		Dr. I. Silambarasan		Dr. I. Silambarasan	Dr. I. Silambarasan			
		S&H		S&H	S&H			
	and Computer	Electrical	Internationa	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering			
T A CONTRACT	ANNERDH THE ROLL	2020-2021		2019-2020	2019-2020			
2	ASS ME.P	637-643		Ľ	1505- 1509			
	WEERDHASS, M.E., P. D. Volume%201-	er.org/wp- content/uploads	https://www.jsc	https://indist.org /articles/new- operations-for- pythagorean- fuzzy-matrices	https://pdfs.sem anticscholar.org/ 35cc/bbe9310e4 0b8384afb96191 62138771737e2. pdf	<u>Fuzzy-Set.pdf</u>		
			No	No	No			
	<u>ads/2020-</u> <u>Volume%201-</u>	iscer.org/wp- content/uplo	https://www.	https://indjst. org/articles/n ew- operations- for- pythagorean- fuzzy- matrices	https://pdfs.s emanticschol ar.org/35cc/b be9310e40b8 384afb96191 62138771737 e2.pdf	<u>Fuzzy-Set.pdf</u>		

A.R.ENGINEERING COLLEGE A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR FOST,



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Some Operations over Pythagorean Fuzzy Matrices Based on Hamacher Operations	Fermatean Fuzzy Matrices	
Dr. I. Silambarasan	Dr. I. Silambarasan	
S&H	S&H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Engineering
2020-2021	2020-2021	
541-552	541-551	
https://pdfs.sem anticscholar.org/ 35cc/bbe9310e4 0b8384afb96191 62138771737e2. pdf	https://jaem.isik un.edu.tr/web/i ndex.php/archiv e/116- vol12no3/887- fermatean-fuzzy- matrices	<u>Issue%205/JSCER</u> <u>03122020.pdf</u>
Š	No	
emanticschol ar.org/35cc/b be9310e40b8 384afb96191 62138771737 e2.pdf	https://jaem.i sikun.edu.tr/ web/index.ph p/archive/116 - vol12no3/887 -fermatean- fuzzy- matrices	<u>Issue%205/JS</u> <u>CER03122020</u> <u>.pdf</u>

); o. /a ;; l



Dr.R.PANNEERDHASS, M.E. Ph D.,
PRINCIPAL
PRINCIPAL
A.R. ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Some new operations and their properties on q-rung orthopair fuzzy matrices	New Operations Defined Over The Q-Rung Orthopair Fuzzy Sets	New operators for Fermatean fuzzy sets
Dr. I. Silambarasan	Dr. I. Silambarasan	Dr. I. Silambarasan
S&H	S&H	S&H
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
2021-2022	2021-2022	2020-2021
44-64 DHASS,W	429-443	429-442
https://www.res earchgate.net/p ublication/35126 8862 Some ne 2021-2022 44-64 w operations a nd their proper ties on q- rung orthopair f	http://www.imvi bl.org/journal/10 20 2/journal i mvi 10 2020 2 341 359.pdf	https://www.res earchgate.net/p ublication/34421 8108 New oper ators for Ferma tean fuzzy sets
Z	Z	No
net/publicatio n/351268862 Some new operations a nd their pro perties on q- rung orthopa ir fuzzy matr	nttp://www.i mvibl.org/jou rnal/10 20 2 /journal imvi 10 2020 2 341 359.pdf	https://www. researchgate. net/publicatio n/344218108 New operat ors for Ferm atean fuzzy s

A.R.ENGINEERING COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

	Generalized orthopair fuzzy sets based on Hamacher T-norm and T-conorm	Generalized orthopair fuzzy matrices	
	Dr. I. Silambarasan	Dr. I. Silambarasan	
	H&S	H%S	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
1	2021-2022	2021-2022	
AND THE SERVE	148-161	513-523	
हैं। हैं।	https://pisrt.org/ psrpress/j/oms/ 2021/1/generaliz ed-orthopair- fuzzy-sets-based- on-hamacher-t- norm-and-t- conorm.pdf	https://pisrt.org/ psrpress/i/oms/ 2021/1/generaliz ed-orthopair- fuzzy- matrices.pdf	
	No	No	
conorm.pdI	https://pisrt.o rg/psrpress/i/ oms/2021/1/ generalized- orthopair- fuzzy-sets- based-on- hamacher-t- norm-and-t-	https://pisrt.o rg/psrpress/j/ oms/2021/1/ generalized- orthopair- fuzzy- matrices.pdf	ices



A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Some Operations Over Intuitionistic Fuzzy Matrices Based On Hamacher T-Norm And T-Conorm	Fermatean Fuzzy Subgroups	Some algebraic properties of Picture fuzzy sets
Dr. I. Silambarasan	Dr. I. Silambarasan	Dr. I. Silambarasan
S&H	S&H	S&H
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
2021-2022	2021-2022	2021-2022
119-133	288 – 299	30-41
Internationa I Journal of Electrical and Computer Engineering process and Engineering process are all the state of the sta	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=JJt5lhQA AAAJ&citation_f or_view=JJt5lhQ AAAAJ:8k81kl- MbHgC	http://www.imvibl.org/buletin/bulletin_imvi_11_3_2021/bulletin_imvi_11_3_2021_429_442.pdf
No.	No.	
https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=JJt5lh QAAAAJ&cita tion_for_view =JJt5lhQAAAA J:8k81kl- MbHgC	http://www.i mvibl.org/bul etin/bulletin_ imvi_11_3_20 21/bulletin_i mvi_11_3_20 21_429_442. pdf

A.R.ENGINEERING COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE; New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Parameter optimization of friction stir welding of cryorolled AA2219 alloy using artificial neural network modeling with genetic algorithm	Some Algebraic structures of Neutrosophic fuzzy sets	
Dr. K KAMAL BABU AP/MECH	Dr. I. Silambarasan	
AP/MECH	S&H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2018-2019	2022-2023	
417-429	341-359	
https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=A6j7O3g AAAAJ&citation_ for_view=A6j7O		AAAJ&citation_f or_view=JJt5lhQ AAAAJ:W70EmF My1HYC
Z	No No	
nttps://scrioid r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=A6j70 3gAAAAJ&cita	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=JJt5lh QAAAAJ&cita tion_for_view =JJt5lhQAAAA J:M3ejUd6NZ C8C	&user=JJt5lh QAAAAJ&cita tion_for_view =JJt5lhQAAAA J:W70EmFMy 1HYC

Dr.R.PANNEERDHASS,M.E.,Ph.D., PRINCIPAL

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Microstructure Evaluation on Friction Stir Welding of Cryorolled 2219 Aluminum Alloy	Influences of metastable 0 ", 0' and stable 0 intermetallics formed during cryorolling and friction stir welding process on AA2219	
Dr. K KAMAL BABU AP/MECH	Dr. K KAMAL BABU AP/MECH	
AP/MECH	АР/МЕСН	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
https://schologle.co.in/cons?view_op w_citation&l n&user=A6j7 AAAAJ&citat for_view=A6 3gAAAAJ:Y0 Dr.R.PANNEERDHASS,ME.,Ph &q_DkC	2018-2019	
RDHASS,	2149 – 2165	
https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=A6j7O3g AAAAJ&citation_ for_view=A6j7O 3gAAAAJ:YOpCki 1E.,Ph	https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=A6j7O3g AAAAJ&citation_ for_view=A6j7O 3gAAAAJ:IjCSPb- OGe4C	3gAAAAJ:UeHW p8X0CEIC
No	No	
https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=A6j7O 3gAAAAJ&cita tion_for_view =A6j7O3gAAA	https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=A6j7O 3gAAAAJ&cita tion_for_view =A6j7O3gAAA AJ:IjCSPb- OGe4C	tion_for_view =A6j7O3gAAA AJ:UeHWp8X OCEIC

A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

			-
RE VINGEERING	Synthesis, spectroscopic characterisation and Molecular dyanamics simulations and molecular docking study of 3-(4-bromophenyl)-1-(thiophen-2-yl) prop-2- en-1 one	Synthesis, spectroscopic, computational and molecular docking studies of 1-(pyridin-2-yl amino) methyl napthalene-2-ol	
	Dr. P.RAJAMANI	Dr. P.RAJAMANI	
	S&H	S&H	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
DE R. PANNEE	2019-2020	2019-2020	
VEHRDHASS,	67-75		
OLECULAR_DOC KING INVESTIGA KING INVESTIGA KING INVESTIGA KING INVESTIGA KING INVESTIGA	https://www.res earchgate.net/p ublication/33773 8455_SYNTHESIS _DFT_SPECTROS COPIC_CHARACT ERISATION_FT- IR_FT- RAMAN_NMR_A ND_UV-	https://www.sci encedirect.com/ science/article/a bs/pii/S0022286 019308804	
	No	No	
_AND_UV- VISIBLE_AND _MOLECULAR _DOCKING_IN	https://www.researchgate.net/publication/337738455_SYNTHESIS_DFT_SPECTROSCOPIC_CHARACTERISATION_FT-IR_FT-RAMAN_NMR	https://www. sciencedirect. com/science/ article/abs/pii /S002228601 9308804	AJ:YOpCki6q_ DkC

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 661.



### (Approved by AICTE, New Delhi & Affiliated to Anna university, Chemnai)

Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Preparation and optical characterization of EnO thin film for optoelectronic applications	FT-IR, FT-Raman, UV-Visible, NMR, DFT and molecular docking investigation of 1-(phenyl (piperidin-1- yl) methyl) naphthalene-2-ol	Synthesis, Characterization, Spectroscopic, DFT and Molecular Docking Studies of 3-(3, 4-Dihydroxyphenyl)- 1- Phenyl-3-(Phenylamino) Propan-1-One	
Dr. R. ELILARASSI	Dr. P.RAJAMANI	Dr. P.RAJAMANI	
S&H	S&H	S&H	
Internationa I Journal of Electrical and Computer	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2018-2019	2021-2022	2020-2021	
https://ieee-2019 497–499 e.ieee.org/ ment/544:	65-71	103-108	
explor docu 1056	https://www.sci encedirect.com/ science/article/p ii/S22117156210 00011	https://www.sci encedirect.com/ org/science/artic le/abs/pii/S1040 663822005802	_BROMOPHENYL -1-THIOPHEN-2- YL_PROP-2-EN- 1_ONE
No	No	No	
https://ieeex plore.ieee.org /document/5 441056	https://www. sciencedirect. com/science/ article/pii/S22 11715621000	https://www.sciencedirect.com/org/science/article/abs/pii/S1040663822005802	VESTIGATION _OF_3-4BROMOPHE NYL-1- THIOPHEN-2- YL_PROP-2- EN-1_ONE
	The second secon		

A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

* 35077	-	GINEERIA			Properties of ZINC OXIDE IIIMS	sudclural and optical	Effect of annealing on	1						reaction method	synthesized using solid state	Cu-doped ZnO nanoparticles	magnetic characterization of	Structural, optical and			
						Dr. R. ELILARASSI	٠									Dr. R. ELILAR ASSI				-	
				20 -		S&H									υαΠ	C & 11					
A.K.ENON VADAI KAPPIY	Dr.R.PANRO	A CONTRACTOR		Engineering	and	Electrical	l Journal of	Internationa					Engineering	Computer	and	Electrical	l Journal of	Intomotion		96	Engineering
VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KILLUPURAM-605 601.	Dr.R. PANNEERING COLLEGE	EDDHASS ME	,			2018-2019									5102-0103	2018_2010					_
M, OST,	196	Ph D.,				378-384									1173	1168-					
	%3A1716616959	, e	1&sxsrf=ADLYWI K2uT2VC9I9CCP <sub>E</sub>	5323e&sca_upv=	%0D%0A&sca_es	zinc+oxide+films	l+properties+of+	tural+and+optica	nealing+on+struc	?q=Effect+of+an	ogle.com/search	https://www.go		009-0041-у	10.1007/s10854-	ger.com/article/	https://link.sprin				-
												No					No				
	ADLYWIK2uT 2VC9I9CCPge-	upv=1&sxsrf=	=b310902482	de+films%0D %0A&sca_esv	s+of+zinc+oxi	cal+propertie	ural+and+opti	ng+on+struct	ct+of+anneali	earch?q=Effe	google.com/s	https://www.	0041-у	/s10854-009-	ticle/10.1007	ringer.com/ar	https://link.sp				



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

* 300	R 603 603 77 100	) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	DE RIA																						
															,									*	_
A.R. ENGRADON PALAYABITA VADAKUCHIPALAYABITA POSTI KAPPIYAMPULIYUR POSTI KAPPIYAM.605 601.	PRINCIPAL COLLEGE	十一 Commonway であっている。	1 1 2 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5																						_
				XMKMgcOlygnG XMKMgcOlygnG	G9mlHppbmMg	m9wZXJ0aWVzI	3B0aWNhbCBwc	dXJhbCBhbmQgb	gb24gc3RydWN0	hbm5lYWxpbmc	VmZmVjdCBvZiB	d2l6LXNlcnAiTU	gs_lp=Egxnd3Mt	+films%0D%0A&	es+of+zinc+oxide	optical+properti	+structural+and+	of+annealing+on	ct=5&oq=Effect+	EQ4dUDCBE&ua	QbWwGHa_NDa	wjq6d3AkKiGAxV	Ao&ved=OahUKE	ul9DaseMPr5u3i	595&ei=_35RZqr
	WNhbCBwcm	hhmOgh3B0a	WNOdXIPPCB	bm5lYWxpbm	mVjdCBvZiBh	NlcnAiTUVmZ	nd3Mtd2l6LX	A&gs_lp=Egx	+films%0D%0	of+zinc+oxide	l+properties+	al+and+optica	g+on+structur	t+of+annealin	t=5&oq=Effec	dUDCBE&uac	GHa_NDaEQ4	KiGAxVQbWw	UKEwjq6d3Ak	Ao&ved=0ah	DaseMPr5u3i	i=_35RZqrul9	616959595&e	wcQ%3A1716	qgmw37wr2



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

* 608 609 TT	E VIII O	G	A LE PORTO														F									
VADAKUCHIPATA POST, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	R ENGINEERING COULEGE	DETTANNETEN	A SAMETERDINASS, M.E. Phili	< \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \																						_
		_	gDGLQCGOUCG	8B2AEBMhYQAB	UCGOoCGIwDGI	YQABgDGLQCGO	wDGI8B2AEBMh	QCGOUCGOoCGI	EBMhYQABgDGL	OoCGIwDGI8B2A	gDGLQCGOUCG	8B2AEBMhYQAB	UCGOoCGIwDGI	QABgDGLQCGO	DGI8B2AEBMhY	GOUCGOoCGIw	MhYQABgDGLQC	CGIwDGI8B2AEB	GLQCGOUCGO0	OoCMhYQABgD	OoCMgcQlxgnG	OoCMgcQlxgnG	OoCMgcQlxgnG	OoCMgcQlxgnG	OoCMgcQlxgnG	OoCMgcQlxgnG
	8B2AEBMhYQ	GOoCGIwDGI	DGLQCGOUC	AEBMhYQABg	oCGIwDGI8B2	госеонсео	MhYQABgDG	wDGI8B2AEB	GOUCGOoCGI	YQABgDGLQC	lxgnGOoCMh	gnGOoCMgcQ	GO <sub>0</sub> CMgcQlx	oCMgcQlxgn	MgcQlxgnG0	cQlxgnGOoC	lxgnGOoCMg	gnGOoCMgcQ	G0oCMgcQlx	oCMgcQlxgn	MgcQlxgnG0	cQlxgnGOoC	ZmlsbXMKMg	Mgb3hpZGUg	G9mlHppbm	9wZXJ0aWVzI



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

* 000	R. Supplier	NG	THE STATE OF THE S		5											でをとせい パーパール									)
						4																			
KAPPIYAM KAPPIYAM	PRINCE	TO BANNEER	4	<u> </u>																					
ADAKUCHIPALA POST, PPIYAMPULIYUR POST, VILLUPURAM-605 601.	PRINCIPE COLLEGE	TEERDHASS M. T. T. C. C.								<	≻ ≻	EYC5I	JgDEI	ApgC	BA8g	gBAK	ougo	EBSN	0°CG	gDGL	8B2AF	ucec	YQLh <sub>ε</sub>	wDGI	acco
										wiz-serp	&sclient=gws-	EYC5IHATGgBwA		ApgCAaACEKgCF	BA8gBAPgBAfgB	gBAKABAKoBALg /	OUQcAF4AJABAJ c	EBSNYYUOUQW	OoCGIwDGI8B2A	gDGLQCGOUCG .	8B2AEBMhYQAB	UCGOoCGIWDGI \	YQLhgDGLQCGO (	wDGI8B2AEBMh   L	QCGOUCGO0CGI / A
ž	BAKoBALgBA	QWOUQcAF4	AEBSNYYUOU	oCGIwDGI8B2	rdceonceo	MhYQABgDG	wDGI8B2AEB	GOUCGO <sub>0</sub> CGI	YQLhgDGLQC	GI8B2AEBMh	UCGOoCGIwD	ABgDGLQCGO	8B2AEBMhYQ	GOoCGIwDGI	Deloceonc	AEBMhYQABg	oCGIwDGI8B2	LQCGOUCGO	MhYQABgDG	wDGI8B2AEB	GOUCGO <sub>O</sub> CGI	YQABgDGLQC	GI8B2AEBMh	UCGOoCGIwD	ABgDGLQCGO



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Carl true	G.	The Party of the P			reaction route		<u>ğ</u> .	characterization of CdS	Structural and ontical				optoelectronic applications		d zinc	Synthesis and optical		XIII						
							Dr. R. ELILARASSI	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7						Dr. R. ELILAKASSI										_
							S&H							S&H	1									
Section 2	1	D'R PANN		Succing	Engineering	and	Electrical	l Journal of	Internationa				Computer Engineering	and	Flectrical	Internationa								_
PERMIND BUT	PRINCIPAL		かり ことのの ま				2018-2019							6102-0103	2018-2019				i					_
2000	U	33	50				309-312							5/0-505	370 305									•
		n_route	chemical_reactio	using_a_simple_	les_synthesized_	_CdS_nanopartic	aracterization_of	_and_optical_ch	5456_Structural	ublication/26836	earchgate.net/p	https://www.res	010-9236-у	10.1007/s11801-	ger.com/article/	https://link.sprin								•
												No				No								•
	chemical_rea	ng_a_simple_	nthesized_usi	oparticles_sy	_of_CdS_nan	aracterization	nd_optical_ch	_Structural_a	n/268365456	net/publicatio	researchgate.	https://www.	9236-у	/s11801-010-	ringer.com/ar	https://link.sp	serp	ent=gws-wiz-	TGgBwA&scli	gBEAEYC5IHA	CFJgDELoGBg	ApgCAaACEKg	8gBAPgBAfgB	



A.R.ENGINEERING CHAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR 605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

EA VILLURIE C	GRERIUS	Diluted magnetic semiconductor properties in Zn1-xCuxO nanoparticles synthesized by sol gel route		Structural, optical and magnetic properties of nanoparticles of ZnO:Ni -DMS prepared by sol-gel method	
		Dr. R. ELILARASSI		Dr. R. ELILARASSI	
		S&H	,	S&H	
VAD	OCR.PA	Internationa I Journal of Electrical and Computer Engineering		Internationa I Journal of Electrical and Computer Engineering	
VADAKUCHIPALAYAM,	PRINCIPAL PRINCIPAL CINEERING COLLEGE	2018-2019		2018-2019	
YAM, POST,	M.E.,PhO., OLLEGE	101-108	2	450-455	
	_route	6070_Diluted_m agnetic_semicon ductor_propertie s_in_Zn_1- x_Cu_x_O_nano particles_synthe sized_by_sol_gel	https://www.res earchgate.net/p ublication/25119	https://pubs.acs. org/doi/10.1021 /acsomega.3c01 727	
			No	N <sub>o</sub>	
	y_sol_gel_rou te	_Diluted_mag netic_semico nductor_prop erties_in_Zn_ 1- x_Cu_x_O_na noparticles_s	https://www.researchgate.net/publication/251196070	https://pubs. acs.org/doi/1 0.1021/acso mega.3c0172	ction_route

VADAKOCHI ATA



A. R. ENGINEERING COLLEGE
(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

* 100 500	E PILLUPIUS ( ) (C)			177								solution growth method	fabricated using a simple	of Co-doped ZnO films	photoluminescence properties	Microstructural and			Control of the contro	· 一 · · · · · · · · · · · · · · · · · ·	明日有四次日本是門外親 化外口					
										♥ 17 × 1 車 4 0 × 1 1 1 1				Dr. R. ELILARASSI												
										-				S&H												
Ŧ	-	Dr.K	of the same	P							- Linguisci III B	Engineering	and	Electrical	l Journal of	Internationa		4								
VADAKUCHIPARA POST, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	S ENGINEERING COLLEGE	PAINTE PRINCI	TARRETTE OF		\									2018-2019												
17UR POS M-605 601.	G COLLEY		S. M. C. P.											179-183												
<u>_</u>	F	Ti.	NUMEROHASS, WENT Prome&ie=UTF-8	_0j15&sourceid=c	me69i57.3347j	ethod&aqs=chro	ution+growth+m	ng+a+simple+sol	s+fabricated+usi	doped+ZnO+film	+Co-	e+properties+of	hotoluminescenc	structural+and+p	ethod&oq=Micro	ution+growth+m	ng+a+simple+sol	s+fabricated+usi	doped+ZnO+film	perties+of+Co-	minescence+pro	ral+and+photolu	?q=Microstructu	ogle.com/search	https://www.go	
																										No
	rome69i57.3	thod&aqs=ch	n+growth+me	mple+solutio	d+using+a+si	ilms+fabricate	doped+ZnO+f	+Co-	properties+of	minescence+	and+photolu	rostructural+	thod&oq=Mic	n+growth+me	mple+solutio	d+using+a+si	ilms+fabricate	doped+ZnO+f	•	perties+of+Co	nescence+pro	nd+photolumi	ostructural+a	earch?q=Micr	google.com/s	https://www.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

		,	1	INTABILETIC SCHILLCOHOUCHOL	Maratia Samianduater	Magnetic Characterization of	Synthesis, Structural and						Synthesis, structural and optical characterization of Nidoped ZnO nanoparticles
٠						Dr. R. ELILARASSI							Dr. R. ELILARASSI
						S&H			*				S&H
AT.	<b>×</b>		Engliceting	Engineering	and	Electrical	l Journal of	Internationa					Internationa I Journal of Electrical and Computer Engineering
W ADILACI	/				3	2018-2019							2018-2019
and the pho.						46-50							751-756
	ples.	n%20the%20sam	20occurred%20i	%2Ddoped,has%	crystalline%20Ni	ary%2C%20nano	ext=ln%20summ	201.09.html#:~:t	.materials.20120	ub.org/10.5923.j	http://article.sap		https://link.sprin ger.com/article/ 10.1007/s10854- 010-0206-8
												No	No
amples.	n%20the%20s	occurred%20i	oped,has%20	e%20Ni%2Dd	nanocrystallin	mary%2C%20	xt=In%20sum	09.html#:~:te	als.20120201.	5923.j.materi	sapub.org/10.	http://article.	347j0j15&sou rceid=chrome &ie=UTF-8 https://link.sp ringer.com/ar ticle/10.1007 /s10854-010- 0206-8



Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
PRINCIPAL
A.R.ENGINEERING COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

			method	using a novel autocombustion	studies on Cu-doped	Paramagnetic resonance	Optical and Electron					method	using a novel auto-combustion	nanoparticles synthesized	emission properties of ZnO:Co	Optical absorption and		semiconductor	diluted magnetic	of ball milled Fe-doned 7nO	Synthesis and about
			7		Dr. R. ELILARASSI									Dr. R. ELILARASSI	10 M 10 1 M 10 M				Dr. R. ELILARASSI		
		9			S&H									S&H					S&H		
	Dr.R.PAI	*	Engineering	Computer	Electrical	l Journal of	Internationa	2,10			9	Engineering	and	Electrical	l Journal of	Internationa	Engineering	Computer	Electrical	l Journal of	Internationa
	PANNEERDHAS			Q.,	2018-2019									2018-2019					2018-2019		
	ASS,M.E.,Ph				196-201									96–105					109-112		
•	NNEERDHASS,M.E.,Ph.D., stion method	vel auto combu	<u>articles synthesi</u>	ped ZnO nanop	udies on Cu do	tron paramagne	optical and elec	5112/Structural	demia.edu/3505	https://www.aca		ļ	727	/acsomega 3c01	org/doi/10 1021	https://pubs.acs		012-1157-5	10.1007/s11801-		
		C#									No					No					No
	novel auto c ombustion m	cles synthesi zed using a	nO nanoparti	e studies on Cu doped Z	etic resonanc	on paramagn	al and electr	ructural optic	/35055112/St	academia.edu	https://www.	7	mega.3c0172	0.1021/acso	acs.org/doi/1	https://pubs.	1157-5	/s11801-012-	ticle/10.1007	ringer.com/ar	https://link.sn



PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR 605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

E VILLUPURAM E 605 601	Layer in Cu/V2O5/n-Si Structured Schottky Barrier Diodes	Impact of Annealing Temperature on Spin Coated V205 Thin Films as Interfacial	the structural, optical and magnetic properties of TiO2 diluted magnetic semiconductor nanoparticles prepared by high energy ball-milling technique	Optical, electrical and ferromagnetic studies of ZnO:Fe diluted magnetic semiconductor nanoparticles for spintronic applications  Influence of nickel doping on	
	Dr. S. Rajesh		Dr. R. ELILARASSI	Dr. R. ELILARASSI	
	S &H PHY		S&H	S&H	
	and Computer Engineering	Internationa I Journal of	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
A.R.ENGII VADA KAPPIY VILLI	DI TOTO-ZOZO		2018-2019	2018-2019	
ENGINEERING AYAM, VADAKUCHIPALAYAM, POS APPIYAMPULIYUR POS 601 VILLUPURAM-605 601	RINGIPAL	,	14536- 14542	120-131	
A.R. ENGINEERING LAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR 601. VILLUPURAM-605 601.	20the%20absorb 20the%20absorb ançe%2C%20it% 20is,when%20co PRINCIPAL AmpaGE%20to%20	https://link.sprin ger.com/article/ 10.1007/s10904- 019-01117-	https://link.sprin ger.com/article/ 10.1007/s10854- 017-7317-4	https://pubmed. ncbi.nlm.nih.gov /28641142/	
		No	Ö	Z No	
	01117- z#:~:text=Fro m%20the%20 absorbance% 2C%20it%20is	https://link.sp ringer.com/ar ticle/10.1007 /s10904-019-	https://link.sp ringer.com/ar ticle/10.1007 /s10854-017- 7317-4	https://pubm ed.ncbi.nlm.n ih.gov/28641 142/	<u>ethod</u>



A. R. ENGINEERING COLLEGE (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

,					
pathogenesis and possible cure—A review		hexagonal boron nitride (hBN) decorated Fe2O3 photocatalyst for the degradation of methylene blue	Highly crystalline V2O5 and V6O13 thin films by PLD and a study on morphology transition of V2O5 by post annealing		
Dr. S. Rajesh		Dr. S. Rajesh	Dr. S. Rajesh		
S &H PHY		S &Н РНҮ	S &Н РНҮ		
Electrical and Computer Engineering	Internationa	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering		
2022-2023		2021-2022	2021-2022		
	v		2250- 1118		
https://pubmed. ncbi.nlm.nih.gov /34919978/		https://link.sprin ger.com/article/ 10.1007/s10854- 020-05215-4	https://www.sci encedirect.com/ science/article/p ii/S0042207X210 00531	omer%zonims.	0+60-8/2021
	Z	No	N <sub>o</sub>		
https://pubm ed.ncbi.nlm.n ih.gov/34919 978/		https://link.sp ringer.com/ar ticle/10.1007 /s10854-020- 05215-4	https://www.sciencedirect.com/science/article/pii/S0042207x21000531	<u>mpare%20to</u> <u>mpare%20to</u> <u>%20other%20</u> <u>films.</u>	



Dr.R.PANNEERDHASS,M.E.PKD.

PRINCIPAL

A.R.ENGINEERING COLLEGE

VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST,

KAPPIYAMPULIYUR 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

R. (VILLUPURAM ) TO 605 601 150	Design of Double Inspection Quick Switching System [DIQSS (0,1)]	Selection and Development of Double Inspection Single Sampling Plan	Repetitive Deferred Variable Sampling plan Involving Minimum Sum of Risks	A Survey of Student preception and feedback during the COVID -19 lockdown
	Dr. SENTHILKUMAR D	Dr. SENTHILKUMAR D	Dr. SENTHILKUMAR D	Dr. SENTHILKUMAR D
	S&H maths	S&H maths	S&H maths	S&H
P	Internationa I Journal of Electrical 202 and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	2022-2023	2021-2022	2021-2022	2020-2021
N-605 601.	ASS <sub>IME.P</sub>			
਼ੁਜ	https://scholar.g  2022-2023  r 2022-2023  r pRINCIPAL pRINCIPAL principal principal principal principal principal	https://scholar.g oogle.co.in/citati ons?user=f1e5Uz IAAAAJ&hl=en	https://scholar.g oogle.co.in/citati ons?user=f1e5Uz IAAAAJ&hl=en	https://journals.lww.com/jmsc/fulltext/2021/2302 0/perception of faculty and students about.11.
	N <sub>o</sub>	No	No	Z <sub>o</sub>
	https://schola r.google.co.in /citations?use r=f1e5UzIAAA AJ&hl=en	https://schola r.google.co.in /citations?use r=f1e5UzIAAA AJ&hl=en	https://schola r.google.co.in /citations?use r=f1e5UzIAAA AJ&hl=en	https://journ als.lww.com/j msc/fulltext/ 2021/23020/ perception of faculty and students abo ut.11.aspx

MINE WILLIAM STATES



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

		Bio	Rei	Pro	$\top$	_	_		_	_ h	- 7	m	_						_				
10110		nposites		Properties of I wiffs Fiber					I.	hybrid composites	reinforced epoxy polymer	groundnut shell fiber	machinability of luffa with	Investigation of properties and						Bivariate Poisson Distribution	Sampling Plan for an Independent Process Using	Double Inspection Single	Construction and Selection of
		Di.iv. I amiceiumass										Dr.R. Panneerdhass									SENTHILKUMAR	Dr.	
		rincipal	Dinainal								•	Principal									S&H maths		
Engineering	Computer	and	Electrical	Internationa   I Journal of					Sciences	and Mining	Mechanics	Rock	l Journal of	Internationa					Engineering	Computer	Electrical	l Journal of	Internationa
BEK. PHINE	A	1010	2019-2020		1							2019-2020									2022-2023		
Value	EFROHAS	`									1435	-+0+2	275										_
_oi_tuiia_riber_	9175 Properties	ublication/33684	earchgate.net/p	https://www.res		ext composite	in Neillorced Eb	Il Poinforced F-	Groundhut Cho	Fiber -	Study of Luffa	d Machinability	n Properties an	0158 Preparatio	ublication/30800	earchgate.net/p	https://www.res			IAAAAJ&hl=en	ons?user=f1e5Uz	https://scholar.g	_
				No														No				70	Z
_Properties_o	n/336849175	net/publicatio	researchgate.	https://www.	<u>omposite</u>	ced Epoxy C	Shell Reinfor	Groundnut		Luffa Fiber	ility Study of	nd Machinab	Properties a	Preparation	n/308000158	net/publicatio	researchgate.	https://www.	AJ&hl=en	r=f1e5UzIAAA	/citations?use	r.google.co.in	https://scholal



A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

4 5			
Compressive and impact properties of luffa fiber reinforced composite materials	Study of mechanical behavior f luffa / coir fiber reinforced composite using experimental and fem techniques	Optimization approach for design of spur gear based genetic algorithm"	
Dr.R. Panneerdhass	Dr.R. Panneerdhass	Dr.R. Panneerdhass	
Principal	Principal	Principal	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2019-2020 Dr.R.Ph	2019-2020	2019-2020	
NEERDH			
https://www.sci encedirect.com/ science/article/p ii/S18777058140 Dr.R. PANNEERDHASS, M.E., Fri D.,	https://www.ijrt e.org/wp- content/uploads /papers/v10i1/A 59340510121.pd	https://journals.i nnovareacademi cs.in/index.php/i jet/article/view/ 15076/19633	Reinforced_PHB V_Biodegradable _Composites
No	No	No	
https://www. sciencedirect. com/science/ article/pii/S18 77705814035	https://www. ijrte.org/wp- content/uplo ads/papers/v 10i1/A593405	https://journ als.innovarea cademics.in/i ndex.php/ijet /article/view/ 15076/19633	f_Luffa_Fiber _Reinforced_ PHBV_Biodeg radable_Com posites



PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR 605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Analysis of surface preparation in en8 steel materials by using coating methods		Effect of mechanical, thermal properties and drilling parameters on groundnut shell-broom fibre-reinforced epoxy composite"	preparation, properties and machinability study of groundnut shell-broom fibrereinforced epoxy composite
	R.Panneerdhaas	Dr.R. Panneerdhass	Dr.R. Panneerdhass
	Mech	Principal	Principal
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal for Research in Applied Science and Engineering Technology
The state of the s	2019-2020	2019-2020	2019-2020
10.11	2456- 172X	2347- 6729	2347-6729
	2019-2020 2456- <u>earchgate.net/p</u> 172X <u>ublication/33428</u> 2740 Analysis a	https://www.rip ublication.com/V olume/ijaerv10n 2spl.htm	https://www.res earchgate.net/p ublication/34415 9525 Preparatio n Properties an d Machinability Study of Grou ndnut Shell- Broom Fibre- Reinforced Epox y Composite
	No	No	S.
Andrysis an	https://www. researchgate. net/publicatio n/334282740	https://www.ripublication.com/Volume/ijaerv10n2spl.htm	https://www.researchgate.net/publication/344159525 PreparationProperties and Machinability Study of GroundnutShell-Broom Fibre-Reinforced Epoxy Compos



A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR 605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

1. 60% 50%	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Analysis of woven glass epoxy laminated with composite plate
	Dr.R. Panneerdhass	Dr.R. Panneerdhass
	Principal	Principal
	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences
PRIN		2020-2021
CIPAL	2454- 1435 0HASS,M	2454- 1435
	https://www.res 2020-2021 2454- 2020-2021 1435 2852 An Impact of Methyl Este phayMEERDHASS,M.E., rs of Algae bio	Investigation o f Surface Modifi cation in EN8 S teel by Using T hermal Spray T echnique  https://www.res earchgate.net/p ublication/37394 586 Buckling An alysis of Woven Glass Epoxy La minated Compo site Plate
	N <sub>o</sub>	No.
3	https://www.researchgate.net/publication/367002852 An Impact of Methyl Fs	d Experiment al Investigati on of Surfac e Modificatio n in EN8 Ste el by Using Thermal Spra y Technique https://www. researchgate. net/publicatio n/37394586 Buckling Anal ysis of Wove n Glass Epox y Laminated Composite Pl ate

A.A.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

E VILLER O	15:/			coir-human hair hybrid composite	factor of glass fibre-coconut	Assessment of open central					Coco Shells and Palm Shells	Particles of the Same Size:	Characterization of a Hybrid Composite Material with Two	Elaboration and		上の日本での大年に			
			17 132		Dr.R. Panneerdhass					10000000000000000000000000000000000000		Di.N. ranneerdnass	Dr B Bonne	41		n Diesel Engi	The factor of		
					Mech					. 17		Principal							
A.R.	Dr.R.I	5	Technology	Science and	Research in	l Journal for				0	Computer Engineering	and	l Journal of	Internationa					
A.R.ENGINEERING COLL	Dr.R. PANNEERDHASS, M.E., Ph. L. PRINCIPAL	*			2021-2022							1707-0707							
				3105	2348-														
	IO	Epoxy Composit	rties of Luffa fi	entration on M echanical Prope	ole Stress Conc	9850 Effect of	ublication/27463	https://www.res			paperid=102056	perinformation?	https://www.scir				ngine	Fuel in Diesel E	diesel Used as
									No				ā	S					
	ed Epoxy Co mposite	es of Luffa f iber Reinforc	nical Properti	Concentratio	pen Central Hole Stress	Effect of O	net/publicatio n/274639850	researchgate.	https://www.		rmation?pape rid=102056	nal/paperinfo	scirp.org/jour	h++p://	læ	n Diesel Engi	ed as Fuel i	biodiesel Us	ters of Alpae

VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

10	Conductivity studies on PEO:NaClO3 electrolyte system with different plasticizers	Ionic conductivity and battery characteristic studies on PEO+NaClO3 polymer electrolyte	Mechanical and Water Absorption Characterization of Mango Seed Shell/Epoxy Composite for Low Load Carrying Structures
	Dr.R.Vasanthi	Dr.R.Vasanthi	Dr.R. Panneerdhass
	S&H	S&H	Principal
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
- PNI	2018-2019	2018-2019	2022-2023
PKINCIPAL	DHASS,		
7	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpFTk AAAAAJ:qjMakF	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2ipFTk AAAAJ&citation for view=m2ipF TkAAAAJ:u- x608ySGOsC	https://www.hin dawi.com/journa ls/iips/2023/997
	No	No	Z <sub>o</sub>
1	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion for view	https://schola r.google.com/ citations?vie w op=view c itation&hl=en &user=m2jpF TkAAAAJ&cita tion for view =m2jpFTkAAA AJ:u- x6o8ySGOsC	https://www. hindawi.com/ iournals/iips/ 2023/997640

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

E VILLUPIDAN T	Olivine-type nanoparticle for hybrid supercapacitors	Heterojunction solar cell with 2% efficiency based on a Cu20 substrate	
	Dr.R.Vasanthi	Dr.R.Vasanthi	
	S&H	H&S	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
A.R.E.	2018-2019	2018-2019	
GINEER	NNEERD		
AS COMPERSE	https://scholar.g  oogle.com/citati  ons?view op=vie  w citation&hl=e  n&user=m2ipFTk  AAAAJ&citation  for view=m2ipF  for view=m2ipF  TkAAAAThaaics  PRINCIPAL ZDif8C  PRINCIPAL ZDif8C	https://scholar.g oogle.com/citati ons?view op=vie w citation&hl=e n&user=m2jpFTk AAAAJ&citation for view=m2jpF TkAAAAJ:ufrVoP GSRksC	нру7ѕс
	N <sub>o</sub>	No.	
	https://schola r.google.com/ citations?vie w op=view c itation&hl=en &user=m2jpF TkAAAAJ&cita tion for view =m2jpFTkAAA	https://schola r.google.com/ citations?vie w op=view c itation&hl=en &user=m2jpf TkAAAAJ&cita tion for view =m2jpFTkAAA AJ:ufrVoPGSR	=m2jpFTkAAA AJ:qjMakFHD y7sC

A.R.ENGINELINIALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

AND WHEED THE



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Photophysical and Electrochemical studies of 4-dicyanomethylene 2, 6-dimethyl-4H-pyran (DDP) dye with amides in water	Photophysical studies of a food hydrocolloid, Gum Arabic with resorcinol based acridinedione dyes in water	
Dr.R. Vasanthi	Dr.R.Vasanthi	
S&H	S&H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2018-2019	2018-2019	
na ogle.com/citati ons?view op=vie of 2018-2019 w citation&hl=e n&user=m2ipFTk AAAAJ&citation for view=m2ipF TkAAAAJ:UebtZR TkAAAAJ:UebtZR TkAAAAJ:UebtZR	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpF TkAAAAJ:LkGwn XOMwfcC	
No	Z	
https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2ipf TkAAAAJ&cita tion for view =m2ipFTkAAA	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion_for_view =m2jpFTkAAA AJ:LkGwnXO MwfcC	AJ:hgOjcs7Dif <u>8C</u>

A.R.ENGINEERING GOLLEGE VABANUCHIFALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

R.



A. R. ENGINEERING COLLEGE
(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

R.E. VILLUPURAM TO	Spectroelectrochemical Investigation of 4-Dicyanomethylene 2, 6-Dimethyl-4H-Pyran (DDP) Dye with Guanidine Hydrochloride (GuHCl) in Water	Electrostatic Investigation of 4-Dicyanomethylene-2,6- dimethyl-4H-pyran (DDP) Dye with amide Derivatives in Water	
	Dr.R.Vasanthi	Dr.R. Vasanthi	
	S&H	S&H	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
KAPPI KAPPI	2019-2020	2019-2020	
VADAKUCHIPALAYAM APPIYAMPULIYUR POS VILLUPURAM-605 601.	EERDHA	*	
VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpFTk AAAAJ&citation_ For_view=m2jpFTk AAAAJ&citation_ COLLEGE BEHALLEEPING COLLEGE OOGLEGE OOGLE	https://scholar.g oogle.com/citati ons?view op=vie w citation&hl=e n&user=m2jpFTk AAAAJ&citation for view=m2jpF TkAAAAJ:Se3iqn houfwC	
	No	N <sub>o</sub>	
	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion_for_view =m2jpFTkAAA	https://schola r.google.com/ citations?vie w op=view c itation&hl=en &user=m2ipF TkAAAAJ&cita tion for view =m2ipFTkAAA AJ:Se3ignhou fwC	AJ:UebtZRa9Y 70C



# A. R. ENGINEERING COLLEGE (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Structural characterization, spectral investigation and antimicrobial studies Of ZnWO4 and Zn0. 9Cu0. IWO4 nanoparticles synthesized by microwave and sucrose mediated solgel method	Interaction Of Acridinedione Dye With A Globular Protein In The Presence Of Site Selective And Site Specific Binding Drugs: Photophysical Techniques Assisted By Molecular	
Dr.R.Vasanthi	Dr.R. Vasanthi	
S&H	S&H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2022-2023	2021-2022	
PRINCIPAL		
https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpF principal principal principal principal principal principal	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpF TkAAAAJ:kNdYIx- mwKoC	
No	No	
https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion_for_view =m2jpFTkAAA	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpf TkAAAAJ&cita tion_for_view =m2jpFTkAAA AJ:kNdYIx- mwKoC	AJ:0EnyYjriUF MC

A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR 601.

R.EA'C



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

ES COS 601 ES COS COS COS COS COS COS COS COS COS CO	Ionic liquid supported on mesoporous Pd/SBA-15 during the manufacture of 1, 3-butadiene using ethanol at lower temperature reaction	Synthesis and characterization of (Co1-x Nix) 3 (BTC) 2.12 H2O (0≤ x≤ 0.5) MOF based Janus chemical micromotors	
	Dr.R.Vasanthi	Dr.R.Vasanthi	
	H%S	H%S	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
A.R.ENG VADA KAPPI' VILL	2022-2023	2022-2023	
A.R.ENGINEERING COMMINION A.R.ENGINEERING COMMINION OF THE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, FOST, VILLUPURAM-605 601.	EERDHAS		
AYAM, DR POST, 05 601.	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpF TkAAAAJ;YOwf2 TkAAAAJ;YOwf2 gJgpHMC pRINCIPAL n_1_EGE	https://scholar.g oogle.com/citati ons?view_op=vie w_citation&hl=e n&user=m2jpFTk AAAAJ&citation_ for_view=m2jpF TkAAAAJ:4TOpq qG69KYC	
	No	No	
	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion_for_view =m2jpFTkAAA	https://schola r.google.com/ citations?vie w_op=view_c itation&hl=en &user=m2jpF TkAAAAJ&cita tion_for_view =m2jpFTkAAA AJ:4TOpqqG6	AJ:Zph67rFs4 hoC



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Long-read bitter gourd (Momorda charantia) genome and the genomic architectof nonclassic domestication	Interconnect stack using self- aligned quad and double patterning for 10nm high volume manufacturing	
Dr.S.S. Raj Solay Anand	Dr.S.S. Raj Solay Anand	
АР/МЕСН	AP/MECH	v
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
2020-2021	2018-2019	
RINCIPAL		
https://scholar.g  oogle.co.in/citati  ons?view_op=vie  v_citation&hl=e  n&user=-  Hu7MWkAAAAJ  PRINCIPAL  PRINCIPAL  PRINCIPAL  OR ENGINEERING COLLEGEW=-	https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=- Hu7MWkAAAAJ &citation_for_vi ew=- Hu7MWkAAAAJ: ULOm3_A8WrAC	
Z °	No	
https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=- Hu7MWkAAA AJ&citation_f	https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=- Hu7MWkAAA AJ&citation_f or_view=- Hu7MWkAAA AJ:ULOm3_A 8WrAC	AJ:YOwf2qJgp HMC

VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

(S)	Experimental investigation and buckling analysis of woven glass epoxy laminated composite plate	Growth, structural, optical, spectral and mechanical studies of adp single crystal	
	G.Ganapathy	Elilarasi.R	
	Mech	S&H PHYSICS	
	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal of Electrical and Computer Engineering	
This property	2019-2020	2019-2020	
PRINCIPAL STREET, SAU,	2347-6729	2250- 1118	
ym, z., sa u.,	https://www.ijirs et.com/upload/2 015/multicon/m ech/21 ME024.p	https://www.res earchgate.net/p ublication/25611 5708 Growth st ructural spectral and optical stu dies on 24- dinitrophenol or ganic single cry stal	Hu7MWkAAAAJ: mB3voiENLucC
	N <sub>o</sub>	No	
	https://www. ijirset.com/up load/2015/m ulticon/mech /21 ME024.p	https://www.researchgate.net/publication/256115708 Growth structural spectral and optical studies on 24-dinitrophenolorganic sing le crystal	or_view=- Hu7MWkAAA AJ:mB3voiEN LucC

PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.

-----



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

(U) (VIII ) (O)	SEI RING	Power and Area Optimization	An effective GDI (Gate Diffusion Input) Based 16- bit	<b>1</b>							computations	comparators	ayer quantum dot-centuar	layer quantum det cellule	Design and analysis of the					
	7		Indhumathi			10 Apr 10 Apr 10					The Total		Geetha.T							_
		,	EEE								i=	(	CSE							
	1 1 1	Computer Engineering	l Journal of Electrical	Internationa						Sciences	and Mining	Mechanics	Rock	l Journal of	Internationa					_,
A.R ENGINEERING SOLETA	QURAPANNEERDHASS, M.E., Ph. D.,		2019-2020										2020-2021		,					-
TWATCHEN T	ERDHAS	,	2250- 1118									1435	-4C47	2454						
011701	optimization S.M.E.,Ph D.,	shift-register- design-for- power-and-area-	effective-gdi- based-16-bit-	<u>set.com/researc</u> <u>h-paper/an-</u>	https://www.ijra			/download	bit comparators	a based 1-	cellular automat	tum dot-	ngle layer quan	d analysis of si	4538 Design an	ublication/35821	earchgate.net/p	https://www.res		-
						No													No	
	area- optimization	shift-register- design-for- power-and-	effective-gdi- based-16-bit-	<u>search-</u> paper/an-	ijraset.com/re	https://www.	ors/download	bit comparat	l <del>.</del>	mata based	cellular auto	uantum dot-	ngle layer q	analysis of si	Design and	<u>n/358214538</u>	net/publicatio	researchgate.	https://www.	

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 661.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

13.1	Error control system incellular network	Power Flow of MTDC Using Droop Control & Impact of DC Voltage Drops	challenges and solutions on current-only directional overcurrent protection for distribution automation	Development of Smart Control System for Improved Energy Management in Building		
	Indhumathi	Indhumathi	Indhumathi	Indhumathi		
	HEH	ECE	EEE	EEE		
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering		
מוניייייייייייייייייייייייייייייייייייי	2021-2022	2021-2022	2020-2021	2019-2020		
3	2456- 172X	2456172 X	2454- 1435	2456- 172X		
20 27 27 27	https://dl.acm.or g/doi/pdf/10.10 23/A%3A101367 6531988#:~:text =ARQ%20is%20a n%20error%20co ntrol.parity%20b its%20have%20b	https://ieeexplor e.ieee.org/iel5/5 9/4374138/0616 9971.pdf	https://ieeexplor e.ieee.org/abstra ct/document/62 79482/	https://www.irej ournals.com/for matedpaper/170 3180.pdf		
	N <sub>o</sub>	N <sub>o</sub>	Z <sub>o</sub>	Z <sub>o</sub>		
ality/020Dits/0	https://dl.ac m.org/doi/pd f/10.1023/A% 3A101367653 1988#:~:text= ARQ%20is%2 Oan%20error %20control.p	https://ieeex plore.ieee.org /iel5/59/4374 138/0616997 1.pdf	https://ieeex plore.ieee.org /abstract/doc ument/62794	https://www. irejournals.co m/formatedp aper/170318		

Dr.R.PANNEERDHASS,M.E.Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST,

יווים מים לוּיל פוופוו דוויו

1



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Smart Drainage Management to Mitigate Summer Drought Damage in Nordic Agriculture within the Circular Economy Framework	kinetic study on the effect of water hyacinths in foodwaste biogas production	
J. Jayakodi	J.Jayakodi	
Civil	Civil	
Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	
2022-2023	2021-2022	
2454- 1435	2454- 1435	
https://research. wur.nl/en/public ations/smart- drainage- management-to- limit-summer- drought- damage-in-nordi	https://ijrst.com /admin/upload/ 1501741586 K K Dinesh Kumar C5 14.pdf	een%20added.
No.	N <sub>0</sub>	
https://resear ch.wur.nl/en/ publications/s mart- drainage- management- to-limit- summer- drought- damage-in- nordi	https://ijrst.c om/admin/up load/1501741 586 K K Din esh Kumar C 5 14.pdf	20have%20be en%20added.



Dr.R.PANNEERDHASS,ME.Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 661.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

R. FILLUPURAM TO	characterization analysis on algae methyl ester (ame) biodiesel injected in automotive ci engine	Design and analysis of knuckle joint using fea software	Investigation of properties and machinability of luffa with groundnut shell fiber reinforced epoxy polymer hybrid composites	Analysis of woven glass epoxy laminated with composite plate
	K.shakthivel	K.sakthivel	Jayakumar R	Jayakumar R
	Mech	Mech	Mech	Mech
	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences
\A.R.EN VAD KAPP	2020-2021 XD1.R.PAN	2018-2019	2020-2021	2020-2021
AKUCHINI AKUCHINI	2454- 1435	2454- 1435	2454- 1435	2454- 1435
A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPIH IYHB BOST	020-2021  1435  020-2021  1435  05 Methyl Este  PRINCIPAL diese 10 dees 10 dee	https://www.riv erpublishers.co m/pdf/ebook/ch apter/RP 97887 70227896C56.pd	https://iopscienc e.iop.org/article/ 10.1088/1757- 899X/1116/1/01	https://core.ac.u k/download/pdf/ 151646269.pdf
_	No le la lo le la	N <sub>o</sub>	N <sub>o</sub>	o V
	https://www. researchgate. net/publicatio n/367002852 An Impact of Methyl Es ters of Algae	https://www. riverpublisher s.com/pdf/eb ook/chapter/ RP 97887702 27896C56.pdf	https://iopsci ence.iop.org/ article/10.108 8/1757- 899X/1116/1/ 012032	https://core.a c.uk/downloa d/pdf/151646 269.pdf

Lus sos Vivonen Lim

KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

on of Surfac	Drig PANALERY WAS SINCE CARON IN ENS S	NECKCIPAL O	BHANNEEN	Dr			EN VIII
No	https://www.res earchgate.net/p ublication/33428 2740 Analysis_a nd Experimental Investigation_o f Surface Modifi	2456- 172X	2019-2020	Internationa I Journal of Electrical and Computer Engineering	Mech	K.Sivasubramaniyan	Analysis of surface preparation in en8 steel materials by using coating methods
Z	https://www.riv erpublishers.co m/pdf/ebook/ch apter/RP_97887 70227896C56.pd	2454- 1435	2018-2019	Internationa I Journal of Rock Mechanics and Mining Sciences	Mech	K.Sivasubramaniyan	Design and analysis of knuckle joint using fea software
No	https://ijrst.com /admin/upload/ 1501741586 K K Dinesh Kumar C5 14.pdf	2454- 1435	2021-2022	Internationa I Journal of Rock Mechanics and Mining Sciences	Civil	K.Saranya	kinctic study on the effect of water hyacinths in foodwaste biogas production
	Fuel in Diesel E ngine						

A.RIENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

R.,



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

R. H. OOS GOLD TO	reparation, achinabilit coundnut shore inforce to the property of the property	Life prediction and statistical analysis of e-glass faber with aloevera in composite specimen	
	Kamalbabu K	K.Sivasubramaniyan	
	S & H	Mech	
	Internationa I Journal for Research in Applied Science and Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	
A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST,	2019-2020	2022-2023	
IPALAYAN	2347- 6729 HASS,M.E.	2456- 172X	
EGE N, )ST,	9-2020 2347- earchgate.net/p 6729 ublication/34415 9525 Preparatio 9525 Preparatio 9525 Preparatio	https://www.res earchgate.net/p ublication/33291 1149 Evaluation of mechanical properties of e- glass and aloe vera fiber reinf orced with poly ester and epoxy resin matrices	teel by Using T hermal Spray T echnique
	No	No.	
	https://www. researchgate. net/publicatio n/344159525 Preparation	https://www.researchgate.net/publication/332911149 Evaluation of mechanica l properties of e-glass and aloe vera fiber reinforced with polyester and epoxy resin matrices	e Modificatio n in EN8 Ste el by Using Thermal Spra y Technique

A THE PARTY STATE OF THE PARTY OF

VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

100	Effect of Mechanical, Thermal Properties and Drilling Parameters on Groundnut Shell-Broom Fibre-Reinforced Epoxy Composite	
	Kamalbabu K	
	Mech	
	Internationa I Journal for Research in Applied Science and Engineering Technology	Technology
PRINCIPAL	iona le gent de la for h in 2021-2022 2347- ed and ring ogy	
	2347- 6729	
7).	ttps://www.res archgate.net/p blication/34415 525 Preparatio Properties an Machinability Study of Grou Indnut Shell- Broom Fibre- einforced Epox Y Composite	d Machinability Study of Grou ndnut Shell- Broom Fibre- Reinforced Epox y Composite
	No	
	https://www.researchgate.net/publication/344159525 PreparationProperties and Machinability Study of Groundnut Shell-Broom Fibre-Reinforced Epoxy Composite	Properties a nd Machinab ility Study of Groundnut Shell-Broom Fibre-Reinforced Epoxy Compos



A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Assessment of open central hole on the stress concentration factor of glass fibre-coconut coir-human hair hybrid composite	Hybrid Composite Materials: Machinability of Luffa with Groundnut shell Fiber Reinforced Epoxy Polymer
Kamalbabu K	Kamalbabu K
Mech	Mech
Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal of Rock Mechanics and Mining Sciences
2021-2022	2021-2022
2348-3105	23454- 1435
https://www.res earchgate.net/p ublication/27463 9850 Effect of Open Central H ole Stress Conc entration on M echanical Prope rties of Luffa fi ber Reinforced Epoxy Composit	https://www.res earchgate.net/p ublication/30800 0158 Preparatio n Properties an d Machinability Study of Luffa Fiber - Groundnut She Il Reinforced Ep oxy Composite
Zo	No O
https://www.researchgate.net/publication/274639850 Effect of Open CentralHole StressConcentration on Mechanical Properties of Luffa f	https://www.researchgate.net/publication/308000158 Preparation Properties and Machinability Study of Luffa Fiber : Groundnut Shell Reinfor ced Epoxy Composite

Dr.R.PANNEERDHASS,M.E.Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR POST,



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

2000	Z 22,000 500	R. W. VILLEPIE	OWEER	any orthocomposites	reinforced epoxy polymer	Analysis of Glass fiber / Human hair / Coir fiber	Dynamics Mechanical	Investigation of Properties and					The second secon		sensor on thin film membrane	rabrication of mems pressure						
						Kamalbabu K					た は できる		,		Namaibabu K	V 11 1 27						
				ļ	1117.011	MECH									Mech							10
				Sciences	Mechanics and Mining	Rock	Internationa		Ĭ			lechnology	Engineering	Science and	Applied	Research in	l Journal for	Internationa				_
PN	Dr.R.PANNEERDHASS,M.E. Ph. D.	and a second	<		-0-1	2021-2022	2			,					2021-2022						,	_
PRINCIPAL	RDHASS	,			6729	2347-								0100	3105	73/8-						-
	M.E. Ph D	osite	oxy resin hybrid	numan hair rei nforced with ep	sisal fibre and	al properties of	7684 Investigati	ublication/34004	earchgate.net/p	https://www.res				8220/9/8/6200	pi.com/1424-	https://www.md					ΙΦ	•
										,	No						No					
	composite	oxy resin hy brid polymer	rced with ep	e and huma	of sisal fibr	of mechanic	Investigation	n/340047684	net/publicatio	researchgate	https://www.	IC	0	8220/9/8/620	24-	mdpi.com/14	https://www.		mposite	ed Epoxy Co	iber Reinforc	

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

optimal load control for economic energy equilibrium in smart grid usingadaptiveinertia weightteaching-learning-basedoptimization	Implementation of low power 17-transist or true single-phase clocking flip –flop designs with 45 nm cmos technology	connectivity in a fuzzy graph
Kuppulakshmi	Kuppulakshmi	Kathiravan.V
CSE	CSE/ECE	S&H MATHS
Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences
7 (2020-2021	2020-2021	2022-2023
2454- 1435	2456- 172X	2454- 1435
https://inass.org /wp- content/uploads /2021/11/20220 43022-3.pdf	https://www.iri mets.com/uploa dedfiles/paper/is sue 1 january 2 022/18246/final/ fin irjmets16417 94171.pdf	https://www.ijm ra.us/project%20 doc/2017/JJESM JUNE2017/JJMR A-11528.pdf
o N	No.	No
https://inass. org/wp- content/uplo ads/2021/11/ 2022043022- 3.pdf	https://www. irjmets.com/u ploadedfiles/ paper/issue 1 january 20 22/18246/fin al/fin irjmets 1641794171. pdf	https://www. ijmra.us/proj ect%20doc/2 017/IJESM JU NE2017/IJMR A-11528.pdf



Dr.R. PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
A.R. ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	An effective GDI (Gate Diffusion Input) Based 16- bit Shift Register Design for Power and Area Optimization	9	Analysis of woven glass epoxy laminated with composite plate
	Manimegalai		Manikandan D
Y	EEE	<u>(</u>	Mech
	Internationa I Journal of Electrical and Computer Engineering		Internationa I Journal of Rock Mechanics and Mining Sciences
Tops	2019-2020		2020-2021
	2250- 1118	,	2454- 1435
<u>optimization</u>	h-paper/an- effective-gdi- based-16-bit- shift-register- design-for- power-and-area-	https://www.ijra	https://www.res earchgate.net/p ublication/37394 586 Buckling An alysis of Woven Glass Epoxy La minated Compo site Plate
		No	N <sub>o</sub>
<u>area-</u> optimization	paper/an- effective-gdi- based-16-bit- shift-register- design-for- power-and-	https://www. ijraset.com/re search-	https://www.researchgate.net/publication/37394586 Buckling Analysis of Woven Glass Epoxy Laminated Composite Plate



Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Synthesis, characterization, crystal structure and biological studies on nicotinanilide based nickel (II), copper (II) and zinc (II) complexes	Mixed ligand complexes of nickel (II), copper (II) and zinc (II) with nicotinanilide and thiocyanate	challenges and solutions on current-only directional overcurrent protection for distribution automation
Maria kulandai Raja balan	Maria kulandai Raja balan	Manimegalai
S&H	S&H	EEE
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences
2018-2019	2018-2019	2020-2021
NNEEROH		2454- 1435
Nttps://scholar.g  oogle.co.in/citati  ons?view op=vie  w_citation&hl=e n&user=2E5Ff7A AAAAAAJ&citation  AAAAJ&citation  AAAAJ&citation  AAAAAAAJ:ufryopg	https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=2E5Ff7A AAAAAJ&citation_ for_view=2E5Ff7 AAAAAJ:KIAtU1d fN6UC	https://ieeexplor e.ieee.org/abstra ct/document/62 79482
No.	Zo	No
https://schola r.google.co.in /citations?vie w op=view c itation&hl=en &user=2E5Ff7 AAAAAJ&citat ion for view	https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=2E5Ff7 AAAAAJ&citat ion_for_view =2E5Ff7AAAA AJ:KIAtU1dfN 6UC	https://ieeex plore.ieee.org /abstract/doc ument/62794 82

A.R.ENGINGERING COLLEGE OF A.R.ENGINGERING COLLEGE OF VADANUCHIPALAYAM, VADANUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

R.E.A.G. WEERLING 605 601 100	Road Accident Data Analytics Using Map – Reduce Concept	An Efficient Eco-friendly Modified Palladium, Immobilized on Imidazolium Supported Bi-functionalized Ionic Liquid for Selective Oxidation of Alcohols	
e Marie de la companio	Mr.N. Muthukumaran	Maria kulandai Raja balan	
N.	CSE	H%S	
D	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	
Dr.R.PANNEERDHASS,M.E.FR.C., A.R.ENGINEERING COLLEGE A.R.ENGINEERING POST, VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR KAPPIYAMPULIYUR KAPPIYAMAM-605 601.	2019-2020	2019-2020	
DHASS,M.	,		ŀ
E.PILEGE POST, POST,	https://www.ijit ee.org/wp- content/uploads /papers/v8i11/18 927078919.pdf	https://scholar.g oogle.co.in/citati ons?view_op=vie w_citation&hl=e n&user=2E5Ff7A AAAAJ&citation_ for_view=2E5Ff7 AAAAAJ:mVmsd 5A6BfQC	SRksC
	No	No.	
	https://www. ijitee.org/wp- content/uplo ads/papers/v 8i11/1892707 8919.pdf	https://schola r.google.co.in /citations?vie w_op=view_c itation&hl=en &user=2E5Ff7 AAAAAJ&citat ion_for_view =2E5Ff7AAAA AJ:mVmsd5A 6BfQC	=2E5Ff7AAAA AJ:ufrVoPGSR ksC

KAPPIYAMPULIYUR POST.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

smart system for controlling and monitoring water and turbidity levels in dam reservoir using microcontroller technology	Performance Analysis of Hookworm Detection using Deep Convolutional Neural Network	Design and Fabrication of Micro Strip Patch Antenna for Cognitive Radio Applications	Soil Area Network for Landslide predict and avoidance System based on ARM Cortex M3, MEMS and GSM
Muthukumaran.N	Mr.N. Muthukumaran	Mr.N. Muthukumaran	Mr.N. Muthukumaran
ECE	CSE	CSE	CSE
Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences
2020-2021	2019-2020	2019-2020	2019-2020
2454- 1435			2454- 1435
https://ijasre.net /index.php/ijasre /article/downloa 2454- 1435 92#:~:text=ln%2 Othe%20sensing %20unit%2C%20 the, the%20micro	https://ieeexplore.ieee.org/document/8748645	https://www.ijre sm.com/Vol.3_2 020/Vol3_Iss5_ May20/JJRESM_ V3_I5_57.pdf	https://papers.ss rn.com/sol3/pap ers.cfm?abstract id=3735839
No.	No	S	No
https://ijasre. net/index.ph p/ijasre/articl e/download/ 1444/1892/2 692#:~:text=l n%20the%20s ensing%20uni	https://ieeex plore.ieee.org /document/8 748645	https://www. ijresm.com/V ol.3_2020/Vol 3_1ss5_May2 0/JJRESM_V3 _15_57.pdf	https://paper s.ssrn.com/so l3/papers.cfm ?abstract id= 3735839

Dr.R.PANNEERDHASS,ME,Pho.
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

optimal load control for economic energy equilibrium in smart grid usingadaptiveinertia weightteaching-learning-basedoptimization	Implementation of low power 17-transist or true single-phase clocking flip –flop designs with 45 nm cmos technology	
Mr.N. Muthukumaran	N.Muthukumaran	
CSE	CSE/ECE	
Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	
2020-2021	2020-2021	
2454- 1435	2456- 172X	
https://inass.org /wp- content/uploads /2021/11/20220 43022-3.pdf	https://www.iri mets.com/uploa dedfiles/paper/is sue 1 january 2 022/18246/final/ fin irjmets16417 94171.pdf	controller%20for %20further%20p rocessing.
Z	Z Vo	
org/wp- content/uplo ads/2021/11/ 2022043022- 3.pdf	https://www. irimets.com/u ploadedfiles/ paper/issue 1 january 20 22/18246/fin al/fin irimets 1641794171. pdf	t%2C%20the,t he%20microc ontroller%20f or%20further %20processin E.

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601. Dr.R.PANNEERDHASS,ME.PhD.,



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	secur	Two fabri rider	Deep Hool Wire Imag Clas	Anter Patch in Co
A.R.E.	security of vehicles using N. protocol-level radiowire threats	Two wheeler design and fabrication to prevent trible riders and accidents	Deep Learning-Based Hookworm Detection in Wireless Capsule Endoscopic Image Using AdaBoost Classifier	Antenna Design: Micro Strip Patch for Spectrum Utilization in Cognitive Radio Networks
* 109 509 SON TOO SOO	N. muthu kumaran	Muthukumaran.N	Mr.N. Muthukumaran	Mr.N. Muthukumaran
	ECE	ECE	CSE	CSE
A,R KA	Internationa I Journal of Electrical and Computer Engineging	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	Internationa l Journal of Electrical and Computer Engineering
A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VILLUPURAM-605 601.	2021-2022	2021-2022	2021-2022	2021-2022
ASS,M.E.,P. AL COLLEG LAYAM, UR POST, 05 601.	2250- 1118	2454- 1435		4 .
m. D.	https://hexhive. epfl.ch/publicati ons/files/22WO OT.pdf	https://www.res earchgate.net/p ublication/33267 9028 Design of Smart Helmet for Accident Av oidance	https://www.tec hscience.com/c mc/v67n3/41581 /html	https://dl.acm.or g/doi/10.1007/s 11277-021- 08232-6
	No	N <sub>o</sub>	No	No
	https://hexhi ve.epfl.ch/pu blications/file s/22WOOT.p	https://www. researchgate. net/publicatio n/332679028 Design of S mart Helmet for Accident Avoidance	https://www. techscience.c om/cmc/v67n 3/41581/html	https://dl.ac m.org/doi/10. 1007/s11277- 021-08232-6



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Intelligent Drowsiness and Illness Detection Assist System for Drivers.	A Neuromorphic Model for Image Recognition usi	SBFET -Based Full Adder with Ultra-Low Leakage and High Speed
Mr.N. Muthukumaran	Mr.N. Muthukumaran	Muthukumaran
CSE	CSE	ECE
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
2022-2023	2021-2022	2021-2022
		2231- 2099
https://ieeexplor e.ieee.org/docu ment/9743075	https://www.res earchgate.net/p ublication/37470 0839 A Neurom orphic Model f or Image Recog nition using SN	https://www.res earchgate.net/p ublication/33267 9028 Design of Smart Helmet for Accident Av oidance
No.	N <sub>0</sub>	No
https://ieeex plore.ieee.org /document/9 743075	https://www. researchgate. net/publicatio n/374700839 A Neuromo rphic Model for Image Re cognition usi ng SNN	https://www.researchgate.net/publication/332679028 Design of Smart Helmet for Accident Avoidance

Dr.R.PANNEERDHASS,ME,PhD,
PRINCIPAL
A.R.ENGINSENING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	Intrusion Detection Systems to Secure IoT Networks	Iot based fish monitoring system for aquaculture	Secure GEDARRouting Protocol for Underwater Data Collection Using WSN.
*	Muthuarasan.R	Muthuarasan.R	Mr.N. Muthukumaran
	ECE	ECE	CSE
A.R.EN VAE KARR VILL	Internationa I Journal of Electrical and Computer Engineering Dr.R. DA	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering
A.R.ENGINEERING COLLEGE VADAMUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-805 601.	2022-2023 2250- 1118	2021-2022	2022-2023
OLLEGE YAM, POST, 601.	2250- 1118	2250- 1118	
-	https://journalof cloudcomputing. springeropen.co m/articles/10.11 86/s13677-018- 0123-6	https://ieeexplor e.ieee.org/docu ment/8745543	https://www.res earchgate.net/p ublication/36715 6989 Secure Tr ansmission of D ata Under Wate r Wireless Sens or Network wit h Improved Per formance
	S S	No	Z °
	https://journ alofcloudcom puting.spring eropen.com/ articles/10.11 86/s13677- 018-0123-6	https://ieeex plore.ieee.org /document/8 745543	https://www.researchgate.net/publication/367156989 Secure Transmission of Data UnderWater Wireless Sensor Network with Improved Performance



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

A.:	R.EA VILL	CIN		application	pedestrian safety using mobile	Pedwarn-enhancement of							. ]		Based Wind Turbine	Transformer using IFBIL	a Medium Frequency	Reduction of Voltage Stress in				<del>-</del>
501	UPURAM O	1000	F.D.		N.MALAIHY							2*				Muthukumaran, A.						
					3&H	0.011										ECE						
A.R	Dr.R.PA		Engineering	Computer	and	Electrical	l Journal of	Internationa		200				Engineering	Computer	and	Electrical	Internationa			1	_
A.R.ENGINEERING COLLEGE	3	1	5			2020-2021											2021-2022					
COLLEGI	SS,M.E.,Ph		\													1118	2250-					
sleg			kwnwAAAAJ:kNd	n_for_view=mTV	wAAAAJ&citatio	n&user=mTVkwn	w_citation&hl=e	ons?view_op=vie	oogle.com/citati	https://scholar.g			60509909	converter fig5 2	IFRTI -dc-dc-	VSW1-based-on-	control-for-the-	diagram-of-the-	gure/Block-	earchgate.net/fi	https://www.res	
											No											No
	lx-mwKoC	WAAAAJ:kNdY	ew=mTVkwn	itation_for_vi	wnwAAAAJ&c	&user=mTVk	itation&hl=en	w_op=view_c	citations?vie	r.google.com/	https://schola	5 260509909	converter fig	an-IFBTL-dc-	PMSG-and-	based-on-a-	the-VSWT-	control-for-	of-the-	net/figure/8i	researchgate.	https://www.

VADAKUĆHIPALAYAM, VADAKUĆHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

,	Two wheeler design and fabrication to prevent trible riders and accidents	smart system for controlling and monitoring water and turbidity levels in dam reservoir using microcontroller technology	Two wheeler design and fabrication to prevent trible riders and accidents	smart system for controlling and monitoring water and turbidity levels in dam reservoir using micro- controller technology	soil area network for landslide predict and avoidance system based on arm cortex m3, mems and gsm
*	605 601 (C)	Nisha.R	N.Savitha	N.Savitha	N.Saveetha
	ECE	ECE	ECE	ECE	ECE
	Internationa I Journal of Rock Mechanica	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences
1		2020-2021	2021-2022	2020-2021	2019-2020
	2454- 1435 1435 EEBDHASS, M.E., Ph. 0	2454- 1435	2454- 1435	2454- 1435	2454- 1435
	http://ijrmmae.i n/Volume7Issue 4/paper1.pdf	http://ijrmmae.i n/Volume6Issue 4/paper5.pdf	http://ijrmmae.i n/Volume7Issue 4/paper1.pdf	http://ijrmmae.i n/Volume6lssue 4/paper5.pdf	http://iirmmae.i n/Volume5- lssue- 1/paper8.pdf
	No	No	No	No	Z <sub>o</sub>
	http://iirmma e.in/Volume7 lssue4/paper	http://ijrmma e.in/Volume6 Issue4/paper 5.pdf	http://ijrmma e.in/Volume7 lssue4/paper 1.pdf	http://ijrmma e.in/Volume6 lssue4/paper 5.pdf	http://ijrmma e.in/Volume5 -lssue- 1/paper8.pdf

A.R.ENG NEERING COLLEGE VADAKUCHIPALAYAM, KABPIYAMPULIYUR POST, VILLUPURAM-SOS 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Subset  Heunstic to Find a Milder P. M.  Cost Tree Spanning a Guyen  Subset  Cost Tree Spanning a Guyen  Subset  Cost Tree Spanning a Guyen  Subset	GPU-friendly Steiner-Tree	Solar PV Applications with Varying Irradiance	Grid Connected Multilevel Inverter Topology Suitable for		Intrusion Detection Systems to Secure IoT Networks		system for aquaculture	lot based fish monitoring		
P.bakshmidevi,			P.Karthik	4.	Nisha.R		Nisha.R	, : :		
ECE			EEE		ECE		ECE			
and Computer Engineering	Internationa I Journal of Electrical	Computer Engineering	Internationa I Journal of Electrical	Computer Engineering	Electrical and	Internationa	and Computer Engineering	Internationa I Journal of Electrical		Sciences
and Computer Computer N. BANNEERD IASS, M.E., Ph. D.,	2020-2021		2020-2021		2022-2023			2021-2022		
1118 1ASS,M.E.	2250-		2456- 172X		2250- 1118		1118	2250-		
<u>20/5/4.pdf</u> ,Ph D.,	http://ijice.in/20	paper/.pdt	http://iriges.com /Volume4Issue4/		http://ijice.in/20 22/2/4.pdf		<u>22/2/2.pdf</u>	http://ijice.in/20		
	o No		S			No		No	-	
2020/5/4.pdf	http://ijice.in/	<u>.pdf</u>	http://iriges.c om/Volume41 ssue4/paper7		http://ijice.in/ 2022/2/4.pdf		<u>2022/2/2.pdf</u>	http://ijice.in/		<u>1.pdf</u>

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

min 80	soil area network for landslide predict and avoidance system based on arm cortex m3, mems and osm	Error control system incellular network	Power Flow of MTDC Using Droop Control & Impact of DC Voltage Drops	challenges and solutions on current-only directional overcurrent protection for distribution automation	GPU-friendly Steiner-Tree Heuristic to Find a Minimum Cost Tree Spanning a Given Subset
1	de P.Saravanan	ar P.M.Kumarasan	P.M.Kumarasan	P.M.Kumarasan	N.MUTHUKUMAR AN
	ECE	EEE	ECE	333	ECE
Girman Parin	Internationa I Journal of Rock Mechanics	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering
TO POLICE	2019-2020 2454- h: 2019-2020 1435 PKNNEERDHASS,M.E.,Ph.D.,	2021-2022	2021-2022	2020-2021	2020-2021
100	2454- 1435 ASS,M.E.,P	2456- 172X	2456172 X	2454- 1435	2250- 1118
	http://ijrmmae.i n/Volume5- h.D., Issue-	http://irjges.com /Volume6Issue2/ paper7.pdf	http://iriges.com /Volume7Issue2/ paper1.pdf	http://ijrmmae.i n/Volume6Issue 2/paper6.pdf	http://ijice.in/20 20/5/4.pdf
	Z	Z	ž Z	Z Z	Z Zo
	http://ijrmma e.in/Volume5 -Issue-	http://iriges.c om/Volume6l ssue2/paper7	http://iriges.c om/Volume7! ssue2/paper1 .pdf	http://ijrmma e.in/Volume6 Issue2/paper 6.pdf	http://ijice.in/ 2020/5/4.pdf

A.R.ENGINEERING COLLEGE
VAEAKUCHIPALAYAM,
WAPPIYAMPULIYUR POST,
WILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

No No	2454- 1435  2454- 1/Volume6Issue 2/paper4.pdf  2456- 2/paper4.pdf  2456- 2/volume4Issue2/ Volume4Issue2/ paper18.pdf paper18.pdf	2454- E 1435 E 172X 172X 172X	2020-2021 2019-2020 2019-2020	Technology Internationa I Journal of Rock Mechanics and Mining Sciences Internationa I Journal of Electrical and Computer	CSE Mech	Pushparaj.E	Design and analysis of single layer quantum dot-cellular automata based 1- bit comparators  Analysis of surface preparation I have in en8 steel materials by using coating methods
1- 1-	http://jrrset.com /2023/March/pa per5.pdf	2347- 6729	2019-2020	Internationa I Journal for Research in Applied Science and Engineering	Civil	Pavithra	Experimental behavior of fiber reinforced concrete using recycled aggregate with agrowaste replacement
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	http://iirmmae.i n/Volume7Issue 4/paper3.pdf	2454- 1435	2022-2023	Internationa I Journal of Rock Mechanics and Mining Sciences	S&H MATHS	Parvatha Varthini	connectivity in a fuzzy graph
	1/paper8.pdf			Sciences			

A.R.ENGINEERING COLLEGE
VABAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	characterization analysis on Relative Relation analysis on Relation Relation automorphism Relations of Relati	Relative Time Synchronization of Distributed System Clock of Applications for Software-in-the-loop SiL Simulation	Distributed Detection of Minimum Cuts in Wireless Multi-Hop Networks	Life prediction and statistical analysis of e-glass faber with aloevera in composite specimen		
23	R.Manivanan	R.Bharathi	R.Bharathi	R.Anbuzhagan		_
	Mech	CSE	CSE	Mech		
91.13	Internationa L Journal of Rock Mechanics and Mining Sciences R PA	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Engineering	
	202	2021-2022	2019-2020	2022-2023	4	
PRINCIPAL COLLEGE	2454- 1435 SS,M.E.,Ph	2231- 2099	2250- 1118	2454- 1435		<del>-</del>
SE.	http://ijrmmae.i n/Volume6Issue 1/paper10.pdf	http://njice.in/2 021/1/4.pdf	http://ijice.in/20 19/4/3.pdf	http://ijrmmae.i n/Volume7Issue 4/paper2.pdf		_
	Zo	Zo	Z o	No		
	http://iirmma e.in/Volume6 Issue1/paper 10.pdf	http://njice.in /2021/1/4.pd f	http://ijice.in/ 2019/4/3.pdf	http://ijrmma e.in/Volume7 lssue4/paper 2.pdf	<u>6. pai</u>	0 246

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, KAPPIYAMPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601;Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Power and Area Optimization	An effective GDI (Gate Diffusion Input) Based 16- bit Shift Register Design for Power and Area Optimization		recycled aggregate with agrowaste replacement	Experimental behavior of fiber reinforced concrete using	the-loop SiL Simulation	of Distributed System Clock of Applications for Software-in-	Relative Time Synchronization	composite	factor of glass fibre-coconut coir-human hair hybrid	Assessment of open central
<i>y</i> *			K.Saranra)	R.Nanthini			R.Manivanan			
	EEE		CIVII	)		CSE			Mech	
Computer Engineering	l Journal of Electrical and	Internationa	Applied Science and Engineering Technology	Internationa I Journal for Research in	Computer Engineering	Electrical and	Internationa	Engineering Technology	Research in Applied	Internationa l Journal for
de	2019-2020			2019-2020		2021-2022			2021-2022	
	2250- 1118		6729	2347-		2231- 2099			2348- 3105	
	http://ijice.in/20 19/4/4.pdf		per5.pdf	http://irrset.com		http://njice.in/2 021/1/4.pdf			/2021/Nov/pape r2.pdf	http://irrset.com
		No		No			No			N <sub>o</sub>
	http://ijice.in/ 2019/4/4.pdf		<u>rch/paper5.p</u> <u>df</u>	http://jrrset.c om/2023/Ma	1-	// // // // // // // // // // // // //			om/2021/Nov /paper2.pdf	http://irrset.c

Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM, VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

100 60	Error control system incellulate of R. Udhayakumar network	Power Flow of MTDC Using Droop Control & Impact of DC Voltage Drops	smart utilization of power using new bidirectional intelligent solid state transformer	challenges and solutions on current-only directional overcurrent protection for distribution automation	Development of Smart Control System for Improved Energy Management in Building
	Udhayakumar	R.Udhayakumar	R.Udhayakumar	R.Udayakumar	R.Udhayakumar
	EEE	ECE	EEE	EEE	EEE
	Internationa I Journal of Electrical and Computer	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering
PRHIBAN	202	2021-2022	2020-2021	2020-2021	2019-2020
	2456- 172X	2456172 X	2250- 1118	2454- 1435	2456- 172X
	http://iriges.com /Volume6Issue2/ paper7.pdf	http://irjges.com //volume7lssue2/ paper1.pdf	http://ijice.in/20 20/5/5.pdf	http://ijrmmae.i n/Volume6lssue 2/paper6.pdf	http://iriges.com /Volume4lssue3/ paper21.pdf
	Zo	Zo	Z o	Ö	Z Z
	http://iriges.c om/volume6l ssue2/paper7	http://iriges.c om/Volume7! ssue2/paper1	http://ijice.in/ 2020/5/5.pdf	http://ijrmma e.in/Volume6 lssue2/paper 6.pdf	http://iriges.c om/Volume4I ssue3/paper2 1.pdf

A.R. ENGINEERING COLLEGE VABAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

.



A. R. ENGINEERING COLLEGE (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

Non-verbal communication: focus on recruitment interview for freshers	Growth, structural, optical, spectral and mechanical studies of adp single crystal	Enhanced Photocatalytic Degradation of Textile Dye Using W, N Co-Doped ZnO Powder: Synthesis, Characterization, and Solar	Enhanced Photocatalytic Degradation of Textile Dye Using W, N Co-Doped ZnO Powder: Synthesis, Characterization, and Solar	
Revathy	Revathi.A	Revathi A	Ramya K	
English	S&H PHYSICS	S & H	S & H	
Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Engineering
2019-2020 2456- /Volum 2019-2020 172X paps PRINCIPAL NIE.,Ph.D.,	2019-2020	2019-2020	2019-2020	
2456- 172X NOBAL	2250- 1118	2347- 6729	2347- 6729	
http://irjges.com /Volume4Issue2/ paper17.pdf	http://ijice.in/20 19/4/5.pdf	http://irrset.com /2019/December /paper10.pdf	http://irrset.com /2019/December /paper10.pdf	
	25	No.	Z Z	
http://irjges.c om/Volume41 ssue2/paper1 7.pdf	http://ijice.in/ 2019/4/5.pdf	http://irrset.com/2019/Decom/2019/Decom/2019/Decomber/paper	http://jrrset.c om/2019/Dec ember/paper 10.pdf	<u>.pdf</u>

A.R. ENGINEERING COLLEGE VABBAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM, 605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

Design and analysis of knuckle joint using fea software	Relative Time Synchronization of Distributed System Clock of Applications for Software-in-the-loop SiL Simulation	Distributed Detection of Minimum Cuts in Wireless Multi-Hop Networks	Reduction of Voltage Stress in a Medium Frequency Transformer using IFBTL DC/DC Converter for PMSG Based Wind Turbine		
s.Ramamoorthy	S.Deevika	S.Deevika	s. saranya		
Mech	CSE	CSE	ECE		
Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering		
2018-2019	2021-2022	2019-2020	2021-2022		
2454- 1435	2231-	2250- 1118	2250- 1118		
http://iirmmae.i n/Volume4- lssue- 3/paper11.pdf	http://njice.in/2 021/1/4.pdf	http://ijice.in/20 19/4/3.pdf	http://ijice.in/20 21/4/3.pdf		
Z	3	Z. Zo	Z No		
e.in/Volume4 -lssue- 3/paper11.pd	http://njice.in /2021/1/4.pd f	http://ijice.in/ 2019/4/3.pdf	http://ijice.in/ 2021/4/3.pdf		

Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

- Collins	kinetic study on the effect of water hyacinths in foodwaste biogas production	Experimental behavior of fiber reinforced concrete using recycled aggregate with agrowaste replacement	Experimental investigation and buckling analysis of woven glass epoxy laminated composite plate	Experimental investigation and buckling analysis of woven glass epoxy laminated composite plate
0	S.suganya	S.Sugunya	S.Sendilkumaran	s.Ramamoorthy
	Civil	Civil	Mech	Mech
-	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal for Research in Applied Science and Engineering Technology	Internationa I Journal for Research in Applied Science and Engineering Technology
THUCHANNE	Internationa  Journal of Rock Mechanics und Mining Sciences  2454- 2454- 2454- 2454- 2454- 2454- 2454- 2454- 2454- 2454- 2454-	2019-2020	2019-2020	2019-2020
77	2454- 1435	2347- 6729	2347- 6729	2347- 6729
	http://ijrmmae.i n/Volume7Issue 3/paper7.pdf	http://jrrset.com /2023/March/pa per5.pdf	http://irrset.com /2019/December /paper9.pdf	http://jrrset.com /2019/December /paper9.pdf
	No	76	Zo	No
	http://ijrmma e.in/Volume7 lssue3/paper 7.pdf	http://jrrset.c om/2023/Ma rch/paper5.p df	http://irrset.c om/2019/Dec ember/paper 9.pdf	http://jrrset.c om/2019/Dec ember/paper 9.pdf

A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

lot based fish monitoring system for aquaculture 605 601		Two wheeler design and fabrication to prevent trible riders and accidents		controller technology	smart system for controlling and monitoring water and turbidity levels in dam reservoir using micro- controller technology		Smart Drainage Management to Mitigate Summer Drought Damage in Nordic Agriculture within the Circular Economy Framework					system for aquaculture	lot based fish monitoring							
7	Saravanan.P Saravanan.P			Saravanan.P				Saranya, B.					Saranaya.R							
	ECE		÷		FCF			ECE	E CE				Civil					ECE		
Computer P	Electrical	Internationa I Journal of	Sciences	Mechanics and Mining	Rock	Internationa l Journal of	and Mining Sciences	Mechanics	Rock	Internationa I Journal of	Sciences	and Mining	Mechanics	Rock	Internationa	Engineering	Computer	Electrical	l Journal of	Internationa
Computer PARKEERDHASS, M.E., Ph.D.	2021-2022				2021-2022				2020-2021				7022 2020	2022-2023				2021-2022		
S,M.E.,Ph.D	1118	2250-		1433	100F			1435	2454-				1435	2454-				1118	2250-	
~	22/2/2.pdf	http://ijice.in/20		4/paper1.pdf	n/Volume7Issue	http://ijrmmae.i		4/paper5.pdf	n/Volume6lssue	http://ijrmmae.i			1/paper3.pdf	n/Volume9Issue	http://iirmmae.i			22/2/2.pdf	http://ijice.in/20	
		No				No				N <sub>o</sub>				ia.	No					No
	2022/2/2.pdf	http://ijice.in/		1.pdf	e.iii/voiuiile/	http://ijrmma	o.pu	issue4/paper	e.in/Volume6	http://ijrmma		<u>3.pdf</u>	Issue1/paper	e.in/Volume9	http://ijrmma			2022/2/2.pdf	http://ijice.in/	

PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPPIYANPULIYUR POST,
VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

connectivity in a fuzzy graph in the connectivity in the		lot based fish monitoring system for aquaculture	Intrusion Detection Systems to Secure IoT Networks	Intrusion Detection Systems to Secure IoT Networks	
70	Silambarasan.I	Savitha	Savitha.N	Saravanan.P	
	S&H MATHS	ECE	ECE	ECE	
	Internationa I Journal of Rock Mechanics A and Mining	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Engineering
TATE OF THE PARTY	2022-2023	2021-2022	2022-2023	2022-2023	:
ENSWEEDING OOL TO	2454- 1435 <u>n/vol</u> 1435 <u>4/pa</u>	2250- 1118	2250- 1118	2250- 1118	
7	http://iirmmae.i n/volume7lssue 4/paper3.pdf I.E.,Ph.D.,	http://ijice.in/20 22/2/2.pdf	http://ijice.in/20 22/2/4.pdf	http://ijice.in/20 22/2/4.pdf	
	Z	Z	Z	Z o	
	http://jirmma e.in/Volume7 Issue4/paper 3.pdf	http://ijice.in/ 2022/2/2.pdf	http://ijice.in/ 2022/2/4.pdf	http://ijice.in/ 2022/2/4.pdf	

A.R. ENGINEERING COLLEGE VADAKUCHIDALIAMA KAPPIYAMALI VILLUPUNA



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam,Kappiyampuliyur post,Villupuram-605601,Tamilnadu.

F. VILLUPURAM	bal communication:	Enhanced Photocatalytic Degradation of Textile Dye Using W, N Co-Doped ZnO Powder: Synthesis, Characterization, and Solar Activity	Design and analysis of single layer quantum dot-cellular automata based 1- bit comparators	Analysis of woven glass epoxy laminated with composite plate	Investigation of properties and machinability of luffa with groundnut shell fiber reinforced epoxy polymer hybrid composites	
OF	V.Girija	Thamizhselvi D	Sugunya.P	Sivasubramaniyan	Sivasubramaniyan K	
	English	S & H	CSE	Mech	Mech	
ComputeDf	Internationa I Journal of Electrical and	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	
ComputeDITE PANNEER HASS, M.E., Ph.D.,	2019-2020	2019-2020	2020-2021	2020-2021	2020-2021	
HASS,ME	2456- 172X	2347- 6729	2454- 1435	2454- 1435	2454- 1435	
Ph.D.,	http://irjges.com /Volume4Issue2/ paper17.pdf	http://jrrset.com /2019/December /paper10.pdf	http://ijrmmae.i n/Volume6lssue 2/paper4.pdf	http://ijrmmae.i n/Volume6Issue 4/paper6.pdf	http://ijrmmae.i n/Volume4- lssue- 4/paper5.pdf	
	Z°	Z	Z	o	No	
	http://iriges.com/Volume41	http://irrset.c om/2019/Dec ember/paper 10.pdf	http://ijrmma e.in/Volume6 lssue2/paper 4.pdf	http://iirmma e.in/Volume6 lssue4/paper 6.pdf	http://ijrmma e.in/Volume4 -Issue- 4/paper5.pdf	

A.R. ENGINEERING COLLEGE VAPAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Activity	Enhanced Photocatalytic Degradation of Textile Dye Using W, N Co-Doped ZnO Powder: Synthesis, Characterization, and Safar	Relative Time Synchronization of Distributed System Clock of Applications for Software-inthe-loop SiL Simulation	Distributed Detection of Minimum Cuts in Wireless Multi-Hop Networks	English language teaching and conversational	
0	Vasanthi M	V.Maha	V.Maha	V.Girija	
	S & Н	CSE	CSE	English	
Ur	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Engineering
DT.R. PANNEERUHASS, M.E., Ph.D.,	2/6	2021-2022	2019-2020	2019-2020	
HASS, M.E.	2347- 6729	2231- 2099	2250- 1118	2456- 172X	
,Ph.O.,	http://jrrset.com /2019/December /paper10.pdf	http://njice.in/2 021/1/4.pdf	http://ijice.in/20 19/4/3.pdf	http://irjges.com /Volume4lssue4/ paper6.pdf	
		2 3		Z Z	
	om/2019/Dec ember/paper 10.pdf	http://njice.in /2021/1/4.pd f	http://ijice.in/ 2019/4/3.pdf	http://irjges.c om/Volume4  ssue4/paper6 .pdf	7.pdf

PRINCIPAL
A.B.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai) Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

in	preparation, properties and machinability study of luffa fiber - groundnut shell reinforced epoxy composite			machinability study of luffa fiber - groundnut shell reinforced epoxy composite	preparation, properties and	Epoxy Composite	Parameters on Groundnut Shell-Broom Fibre-Reinforced	Effect of Mechanical, Thermal	within the Circular Economy Framework	Smart Drainage Management to Mitigate Summer Drought
	NELRIN	R.PANNEERDHAS S		Anbazhagan R			R.PANNEERDHAS S		VIIIOIII, 7	Viinak V
	1	Mech		Mech			Mech		CIVII	; ;
	Engineering Technology	Research in Applied Science and	Internationa l Journal for	Applied Science and Engineering Technology	Internationa I Journal for Research in	Engineering Technology	Applied Science and	Internationa I Journal for Research in	Mechanics and Mining Sciences	Internationa I Journal of Rock
A PANNETH	y AME Ph O.	2021-2022		7021-2022	2021		2021-2022			2022-2023
1000	HASS.M.E	2347- 6729		6729	2347-		6729	2347-	1435	2454-
	Ph O.,	/2022/Septembe r/paper5.pdf	http://incot.com	r/paper5.pdf	http://irrset.com		r/paper4.pdf	http://irrset.com	1/paper3.pdf	http://ijrmmae.i n/Volume9Issue
			N <sub>o</sub>		Z			Zo		N <sub>o</sub>
		om/2022/Sep tember/paper <u>5.pdf</u>	http://jrrset.c	tember/paper 5.pdf	http://jrrset.c		ember/paper 4.pdf	http://jrrset.c	3.pdf	http://ijrmma e.in/Volume9

Dr.M. PANNLE PRINCIPAL
PRINCIPAL
A.R.ENGINEERING COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-505 601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

Hybrid Composites	Investigation of Properties and Dynamics Mechanical Analysis of Glass fiber / Human hair / Coir fiber reinforced epoxy polymer	optimal load control for economic energy equilibrium in smart grid using adaptive inertia weightteaching-learning-	Hybrid Composite Materials: Machinability of Luffa with Groundnut shell Fiber Reinforced Epoxy Polymer	Fabrication of mems pressure sensor on thin film membrane
ZEED	RAMAMOORTHY	A.MADHAVAN	R.PANNEERDHAS S	R.PANNEERDHAS S
	МЕСН	CSE	Mech	Mech
,	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal of Rock Mechanics and Mining Sciences	Internationa I Journal for Research in Applied Science and Engineering Technology
A MARCODELSO, M.E. Pho.	2021-2022	2020-2021	2021-2022	2021-2022
	2347- 6729	2454- 1435	23454- 1435	2348-
Ph D.,	http://www.ijrm mae.in/Volume7 lssue2/paper3.p	http://ijrmmae.i n/Volume6lssue 2/paper5.pdf	http://www.ijrm mae.in/Volume7 Issue1/paper4.p	http://irrset.com /2021/Oct/paper 2.pdf
	2		Z Z	Z No
	http://www.il rmmae.in/Vol ume7Issue2/ paper3.pdf	http://jrmma e.in/Volume6 lssue2/paper 5.pdf	http://www.ij rmmae.in/Vol ume7Issue1/ paper4.pdf	http://jrrset.c om/2021/Oct /paper2.pdf

R.E. C. WILL UP UP ON THE CONTROL OF THE CONTROL OF

Dr.R. PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
A.R. ENGINEERING COLLEGE
A.R. ENGINEERDHASS, M.E., Ph.D.,
PRINCIPAL
VADAKUC: IPALAYAM,
VADAKUC: IPALAYAM,
VADAKUC: IPALAYAM,
VILLUPURAM-605 601.



(Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)
Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu.

	1								
	security of vehicles using protocol-level radiowire threats		Distributed Detection of Minimum Cuts in Wireless Multi-Hop Networks		Development of Smart Control System for Improved Energy Management in Building		characterization analysis on algae methyl ester (ame) bio- diesel injected in automotive ci engine	Hybrid Composites	Investigation of Properties and Dynamics Mechanical Analysis of Glass fiber / Human hair / Coir fiber
	R. MAHALAKSHMI		MADHAVAN		Manimegalai		RAMAMOORTHY		PANNEERDHASS
	ECE		CSE		ЕЕЕ		Mech		MECH
Computer	, , ,	Engineering	Internationa I Journal of Electrical and Computer	Engineering	I Journal of Electrical and Computer Fnoineering	Internationa	I Journal of Rock Mechanics and Mining Sciences	Sciences	Internationa I Journal of Rock Mechanics and Mining
500	2021-2022		2019-2020		2019-2020		2020-2021		2021-2022
ACIDAL.	2250- http://i 21-2022 1118 21/2 21/2 250- http://i		2250- 1118		2456- 172X		2454- 1435		2347- 6729
	http://ijice.in/20 21/4/4.pdf 1.E.,Ph.D.;		http://ijice.in/20 19/4/3.pdf		/Volume4Issue3/ paper21.pdf	http://iriges.com	http://iirmmae.i n/Volume6Issue 1/paper10.pdf		http://www.ijrm mae.in/Volume7 Issue2/paper3.p
	i	No		No		N <sub>o</sub>		No	N <sub>o</sub>
	http://ijice.in/ 2021/4/4.pdf		http://ijice.in/ 2019/4/3.pdf		ssue3/paper2 1.pdf	http://irjges.c	e.in/Volume6 Issue1/paper 10.pdf	http://ijrmma	http://www.ij rmmae.in/Vol ume7Issue2/ paper3.pdf

A. B. ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-606-601.



Vadakuchipalayam, Kappiyampuliyur post, Villupuram-605601, Tamilnadu. (Approved by AICTE, New Delhi & Affiliated to Anna university, Chennai)

	Grid Connected Multilevel Inverter Topology Suitable for Solar PV Applications with Varying Irradiance	Grid Connected Multilevel Inverter Topology Suitable for Solar PV Applications with Varying Irradiance	,
	R.Udhayakumar	P.M.Kumarasan	
	EEE	EEE	
	Internationa I Journal of Electrical and Computer Engineering	Internationa I Journal of Electrical and Computer Engineering	Engineering
\		2021-2022	
	2456- 172X	2456- 172X	
	http://iriges.com /Volume4Issue4/ paper7.pdf	http://iriges.com /Volume4Issue4/ paper7.pdf	,
	Z	Z. No	
	http://irjges.c om/Volume41 ssue4/paper7 .pdf	http://iriges.c om/Volume4! ssue4/paper7	



A Comment

Dr.R.PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
WAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 6 Issue 1, July - Sep. 2020 - www.ijrmmae.in - Pages 31-41

# CHALLENGES AND SOLUTIONS ON CURRENT-ONLY DIRECTIONAL OVERCURRENT PROTECTION FOR DISTRIBUTION AUTOMATION

P.M.Kumarasan<sup>1</sup>, R.Udhayakumar<sup>2</sup>, Manimegalai<sup>3</sup>, Indhumathi<sup>4</sup> <sup>1,2,3,4</sup>Assistant Professor


Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram E-mail:udayalanayaeee@gmail.com

Abstract—Overcurrent relays are widely utilized for power system protection. While directional relays are prevalent on the transmission side, distribution systems often employ nondirectional types. These relays discern fault direction, which can be forward (between relay and grid) or reverse (between relay and source), considering the typical power flow from source to grid. Traditional directional overcurrent relays necessitate both current and voltage measurements, making them more costly than nondirectional ones. This paper introduces a novel current-only directional detection method, addressing its theoretical underpinnings, test signal analysis, challenges, and solutions. Additionally, potential applications of current-only directional relays in distribution-side protection, crucial for smart grid implementation, are outlined.

*Index Terms*—Distance protection, fault direction, fault isolation, fault location, medium voltage, MV, phase angle, radial network, relay, ring-main unit, smart grid, subtransmission, voltage-less direction.

### I. INTRODUCTION

Numerical feeder protection relays commonly employ nondirectional time overcurrent techniques, where overcurrent monitoring occurs over a set time to trigger protection mechanisms [1], [2]. This monitoring, typically lasting 40–100 ms, distinguishes between faults and load changes and is governed by standards like IEC 60255 [3], specifying various overcurrent magnitude and duration thresholds for nondirectional relays. Time relaying introduces delays to allow closer relays and breakers to clear remote faults effectively, necessitating complex coordination settings for distance protection [2]. On the other hand, directional overcurrent relays [4] utilize a reference voltage phasor, also known as "voltage polarization," to discern fault direction.





# International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal I stablished in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NII, Trichy Journal Indexed in JIR, DIII and SJII.

Available online at: www.jrrset.com

ISSN met : 2347-6729 ISSN met : 2348-3105

JIR 1F: 2.54 SJIF 1F: 4.334 Cosmos: 5.395

Volume 10 Issue 9 - September 2022 - Pages 32-41

# PREPARATION, PROPERTIES AND MACHINABILITY STUDY OF LUFFA FIBER - GROUNDNUT SHELL REINFORCED EPOXY COMPOSITE

- R. Panneerdhass, Professor, Department of Mechanical Engineering, A.R. Engineering College, Villupuram, Tamilnadu – 605601, India
- 2. K. Kamalbabu, Associate Professor, Department of Mechanical Engineering, SSN College of Engineering, Chennai, Tamilnadu-603110, India
  - 3. \*R. Anbazhagan, Professor, Department of Mechanical Engineering, A.R. Engineering College, Villupuram, Tamilnadu 605601, India

### Abstract

The need for eco-friendly materials and non-polluting processing techniques has made natural fibre reinforced polymer composites as potential candidates to replace GFRPs and CFRPs in semi structural applications. Ground nut shell and luffa fibre are easily available in the market at low cost. Polymer composites consisting of 30%, and 40% volume fractions of a hybrid reinforcement containing groundnut shell and luffa fibre in epoxy resin were fabricated by hand lay-up technique with varying process parameters, The variation in the mechanical properties such as Tensile, Compressive, Flexure and Impact strength are studied. The optimum mechanical properties were obtained in 40% of fiber volume fraction of treated fiber composites The machinability study was performed by drilling experiments using a drilling machine with drill tool dynamometer. Two input parameters, cutting speed and feed rate and the one output parameter, thrust force, were used for the drilling process. TiAIN coated solid carbide and HSS drills were employed in the drilling experiments and a comparative study was made based on the output parameters. Solid carbide resulted in lower thrust force values and feed rate proved to be the most influential parameter on thrust force.

**Keywords**: Natural fibre, hand layup, mechanical properties, thrust force, feed rate, open hole, solid carbide tool, drilling.

## INTRODUCTION

Environmental awareness programmers induced researchers to design materials which are more compatible to the environment. The natural fibers such as sisal, coir, jute, ramie, pineapple leaf, and kenaf are as enough potential to replace the glass or other traditional reinforcement materials. These fibers are abundant, cheap and renewable. Thiruchitrambalam et al., investigated effect of alkali and sodium Lauryl Sulfate treatment on natural fiber composite consisted of Banana and Kenaf hybrid composites. Fibers were treated with 10% of sodium hydroxide (NaOH) and 10% Sodium Lauryl Sulfate (SLS) for 30 minutes. The fiber content in the composite is kept constant at 40 %. The variables in the mechanical properties and morphological changes were studied. Raju et al., investigated mechanical properties fabricated polymer composite reinforced with various percentage of groundnut

R. Panneerdhass et.al



DI.R. PANNEERDHASS, M.E., Ph. 32
PRINCIPAL
PRINCIPAL
PRINCIPAL COLLEGE
A.R. ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR GOF, GOT.
VILLUPURAM. GOF, GOT.



# International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal I stabilished in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NII, Trichy, Journal Indexed in JIR, DIF and SJII.

Available online at: www.mrset.com

ISSN <sub>(Pres)</sub> : 2347-6729 ISSN <sub>(Pres)</sub> : 2348-3105

JIR IF: 2.54 SJIF IF: 4.334 Cosmos: 5.395

Volume 10 Issue 11 - November 2022 - Pages 15-29

# Effect of Mechanical, Thermal Properties and Drilling Parameters on Groundnut Shell-Broom Fibre-Reinforced Epoxy Composite

Panneerdhass R\*1, Kamalbabu k², Anbazhagan R³
1.2,3 Professor
Department of Mechanical Engineering, A.R Engineering College, Villupuram-605601, Tamilnadu, India.

panneerdhass@gmail.com,

## Abstract.

In this preliminary study, the potential of ground nut shell and broom fiber as a reinforcement material for polymer bonded composites was investigated. Ground nut shell and broom fiber (fiber strands extracted from broom grass) are easily available in the market at low cost. Ground nut and broom fiber reinforced epoxy resin matrix composites have been developed by hand lay-up technique with different volume fraction of fibers as in 1:1 ratio (30%, 40% and 50%). The mechanical characterization of these composites was carried out by standard tensile, compressive and flexural tests on a Universal Testing Machine with appropriate setups. Thermo gravimetric analysis was performed to compare the thermal characteristics of conventionally cured and microwave cured composites. Microwave cured samples exhibited higher thermal stability indicating a better extent of cure. Drilling parameters were performed by experiments using a CNC drilling machine with drill tool dynamometer. Two input parameters, cutting speed and feed rate and the one output parameter, thrust force, were used for the drilling process. Solid carbide and HSS drills were employed in the drilling experiments and a comparative study was made based on the output parameters. Solid carbide resulted in lower thrust force values and feed rate proved to be the most influential parameter on thrust force. SEM analysis on the composite materials was performed. The fracture surface of the composite shows that pull out and de bonding of fiber is occurred.

**Keywords:** Natural fibre, Hand layup method, Mechanical and Thermal properties, Solid carbide tool, Drilling, SEM.

## 1 Introduction

Recently, the research attempts in natural fibre reinforced polymer composites have greatly increased. Natural fibre reinforced polymer composites involve simple processing techniques, easily procurable raw materials and high biodegradability levels among all the engineering materials. Apart from researchers, manufacturers have also shown increased interest in natural fibre composites from the past decade. To substantiate this claim, the increased in the use of the natural fibres in German cars from around 10000 tonnes in the year of 2000 to 19000 tonnes in 2005 could be mentioned [1]. Hemp, sisal, kenaf, and bamboo are the natural fillers which have undergone many evaluation procedures and declared fit for a good number of applications. The mechanical properties of natural fibers and the composites developed by incorporating them in different polymer matrices and various processing techniques for fabricating them have been studied by many researchers [2–4]. In a majority of the research attempts on natural fibre reinforced polymer composites, the filler phases used were in the form of fibres. Natural filler phases in other forms like shell (eggshell), powder (sawdust) were very rarely experimented. This research work is an exploratory attempt on composite containing shell



PRINCIPAL PRINCI



# International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal Established in early 2000 as National journal and upgraded to International journal in 013 and is in existence for the last 10 years. It is run by Retired Professors from NIL, Tricky, Journal Indexed in JIR, DIH and SJR.

Available online at: www.juset.com

om (

ISSN (\*\*\*): 2347-6729 ISSN (\*\*\*): 2348-3105

JIR IF: 2.54 SJIF IF: 4.334 Cosmos: 5.395

# INVESTIGATION INTO THE IMPACT OF AN OPEN CENTRAL HOLE ON THE STRESS CONCENTRATION FACTOR OF GLASS FIBER-COCONUT COIR-HUMAN HAIR HYBRID COMPOSITE

Volume 9, Issue 11 - November 2021- Pages 15-24

- 1. R. Panneerdhass, Professor, Department of Mechanical Engineering, A.R. Engineering College, Villupuram, Tamilnadu 605601, India
- 2. \*R. Anbazhagan, Professor, Department of Mechanical Engineering, A.R. Engineering College, Villupuram, Tamilnadu 605601, India
- K. Kamalbabu, Associate Professor, Department of Mechanical Engineering, SSN College of Engineering, Chennai, Tamilnadu-603110, India

### Abstract

The recent research attempts in polymer composites are indicative of a shift of choice to synthetic fillers from natural fillers as the low eco-compatibility of the former is posing serious environmental hazards. Anyhow, the comparatively lower mechanical properties of the natural fibre reinforced polymer composites have restricted their entry into many sectors. A complementary measure by presenting a combination of natural and synthetic fibres in the polymer matrix can achieve a good balance between the degradability and performance of the material. In the recent past, a few research attempts were made on the feasibility of hybridization using selected natural and synthetic fillers. Most of the assembling operations of fibre reinforced plastic sheets involve a number of riveted joints which require the presence of holes which naturally give rise to zones of stress concentration. This factor has made the analysis of open hole behaviour of these laminate composites, a crucial step in defining their suitability for applications. The open hole mechanical properties of human hair-coconut coir-glass fibre-human hair hybrid composite (HCGHRP) are studied in this paper. The composite samples were prepared by hand lay-up. Eight sets of tensile and impact specimens with each set comprising of specimens with centrally drilled holes of a particular diameter were prepared and the experimental tensile and impact values were recorded. Additionally, Whitney Nusimer point stress model was validated for these values. The stress distribution in the open hole specimens were studied by Finite Element Method. In all these Increase in hole diameter was found to cause an increase in hole sensitivity. The finite element analysis of the loaded specimens indicated a much higher concentration of load in the regions surrounding the hole.

Keywords: Stress concentration factor, open central hole, glass fibre, human hair

## INTRODUCTION

Green environment campaign has forced the researcher to change their approach in polymer composites reinforcement material from synthetic fillers to natural fillers to enhance polymer composites properties. The key is a low eco-compatibility of the synthetic fillers is posing serious environmental hazards. Since comparatively lower mechanical properties of the natural fibre reinforced polymer composites as restricted their entry into many sectors. A complementary measure has been taken by presenting a combination of natural and synthetic fibres in the polymer matrix can achieve a good balance between the degradability and performance of PRINCIPAL COLLEGE



DE PANNEERDHASS, M.P. PRINCIPAL PRINCIPAL PRINCIPAL PRINCIPAL AYAM,

A.R. ENGINEERING COLLEGE

VADAKUCHIPALAYAM,

VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST,

KAPPIYAMPULIYUR 605 601.

VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING(IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume7, Issue 1 - April - June 2021 - www.ijrmmae.in – Pages 20-36

# Hybrid Composite Materials: Machinability of Luffa with Groundnut shell Fiber Reinforced Epoxy Polymer

Panneerdhass R\*1, Kamalbabu K², Anbazhagan R³
1.2.3 Professor

Department of Mechanical Engineering, A.R Engineering College, Villupuram-605601, Tamilnadu, India.

Email: panneerdhass@gmail.com

### Abstract:

This paper presents the study of the tensile, compressive, flexural, impact energy and water absorption characteristics of the luffa fiber and luffa with ground nut fiber reinforced epoxy polymer composites. Luffa fiber and luffa with ground nut fiber reinforced epoxy resin matrix composites have been developed by hand lay-up technique with varying process parameters such as fiber condition (treated, untreated), chopped randomly oriented and different volume fraction (30%, 40% and 50%). Tensile strength various from 18 Mpa to 23.5 Mpa, compressive strength varies from 41.5 MPa to 56.2 MPa, flexural strength varies from 61.22 MPa to 73.6 MPa and impact energy varies from 1.1 Joules to 1.6 Joules, as a function of fiber volume fraction. Thermo gravimetric analysis was performed to compare the thermal characteristics and of conventionally cured and microwave cured composites. Effects of central open hole on the tensile and impact strengths of the composites were studied by five sets of tensile specimens containing central open holes of five different diameters. The machinability study was performed by drilling experiments using a CNC drilling machine with drill tool dynamometer. Two input parameters, cutting speed and feed rate and the one output parameter, thrust force, were used for the drilling process. Solid carbide and HSS drills were employed in the drilling experiments and a comparative study was made based on the output parameters. Solid carbide resulted in lower thrust force values and feed rate proved to be the most influential parameter on thrust force. The optimum mechanical properties were obtained in 40% of fiber volume fraction of the treated fiber composite. The fracture surface of the composite shows that pull out and de bonding of fiber is occurred.

Keywords: luffa / ground nut fiber hybrid, mechanical and thermal properties, open hole, machinability, SEM.

### Introduction:

Synthetic fiber reinforced composites are being widely used in polymer composites because of their high stiffness and strength properties. The natural fibers such as jute, ramie, sisal, coir, pineapple leaf, and kenaf have the potential to be used as a replacement for glass or other traditional reinforcement materials in composites. These fibers are abundant, cheap and renewable. Martinez-Lopez et al., aims to study the Polymer Concrete were reinforced with Loofah fibers in order to improve the compressive and flexural strength. Polymer concrete specimens were prepared with, 30% of polyester resin, 70% of silicious sand and various fiber concentrations (0.3, 0.6 and 0.9 vol%). The results show decrease in the values of mechanical properties including compressive strength, flexural strength and compression modulus of elasticity [1]. Valcineide et al., studied the chemical treatments used on sponge gourd (Luffa cylindrica) fibers of Brazil to prepare their composites with polyester resin. Production of short fiber-polymer composite as well as mat-polyester composites is presented



PANNEER DE ME. PRESENTALISTA RELAI.

PRINCIPAL
POST,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VILLUPURAM.605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 7 Issue 2, July - Sep. 2021 - www.ijrmmae.in - Pages 15-33

# Investigation of Properties and Dynamics Mechanical Analysis of Glass fiber / Human hair / Coir fiber reinforced epoxy polymer Hybrid Composites

Panneerdhass R\*1, Kamalbabu k², Anbazhagan R³
1,2,3 Professor
1,2,3 Department of Mechanical Engineering. A.R Engineering College, Villupuram-605601, Tamilnadu, India.

panneerdhass@gmail.com.

### ABSTRACT

This paper presents the study of the mechanical and water absorption characteristics of the Glass fiber / Human hair / Coir fiber reinforced epoxy polymer composites. G-H-C-G, C-H-G-C, and H-C-G-H reinforced epoxy resin matrix composites have been developed by hand lay-up technique with varying process parameters such as fiber condition. Tensile strength various from 42 Mpa to 56 Mpa, Tensile modulus varies from 48 GPa to 52 GPa, flexural strength varies from 46 MPa to 52 MPa, flexural modulus varies from 42 Gpa to 50 Gpa, shear study and fracture study was carried out. Effects of central open hole on the tensile strengths of the composites were studied by five sets of tensile specimens containing central open holes of five different diameters. Dynamic mechanical analyzer (DMA) was used to examine the dynamic mechanical properties of composite laminates with increasing temperature. The optimum mechanical properties were obtained in the treated fiber composite. Results showed that the composite sample, which has human fabric at the outer layers, has the highest storage and loss modulus. Besides, it was observed that glass transition temperature (Tg) of samples are close to each other and at about 75 °C. The fracture surface of the composite shows that pull out and de bonding of fiber is occurred.

Keywords: Glass fiber / Human hair / Coir fiber fiber hybrid, mechanical, open hole, DMA, SEM.

## INTRODUCTION:

Natural fibers are derived from plants, animals and mineral sources. In modern days, the natural fibers from plants like sisal, banana and jute mixed with the glass fiber are used to get high strength (HS) hybrid composite materials which are widely used in many applications. High strength composite materials are replacing the metallic materials when used in the aerospace, structural and automobile industries.

Hybrid laminates exhibited superior dynamic mechanical performance, even compared to the pure glass laminate. Lower tan delta peak height (related to better fiber-matrix interaction) values and higher Tg were reported for the [C/G/G]s and [G/C/C]s samples which, together with the [G/C/G]s sample, exhibited the best results for reinforcement effectiveness and loss modulus peak height [1]. Polyester based hybrid composites are prepared by Hand lay-up technique followed by static compression having constant 25 wt.% of fibre content with various stacking sequences. A significant improvement in flexural properties of sisal fibre reinforced polyester composite is observed by incorporation of glass fibre [2]. Studied an effect of various curaua (C) /glass (G) interlaminar hybrid



Dr.R.PANNEERDHASS, M.E., PANNEERDHASS R ET.AL
PRINCIPAL
POST,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VILLUPURAM-605 601.



International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 6, No. 2, June, 2021 – August, 2021 | Pages 100-109

# ERROR CONTROL SYSTEM INCELLULAR NETWORK

B.Keerthana<sup>1</sup>, R.Udhayakumar<sup>2</sup>, P.M.Kumarasan<sup>3</sup>, Indhumathi<sup>4</sup>

1.2.3.4 Assistant Professor

Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram E-mail:udayalanayaeee@gmail.com

### **ABSTRACT**

In cellular communication networks, the geographical area is divided into smaller regions, called cells. In each cell, there is one Mobile Service Station (MSS) as well as a number of Mobile Hosts (MH). The communication between MSSs is, in general, through wired links, while the links between an MH and MSS is wireless. A Mobile Host can communicate with other Mobile Hosts in the system only through the Mobile Service Station in its cell. This kind of architecture is shown in Fig. 1. There are two kinds of channels available to an MH: communication channel and control channel. The former is used to support communication between an MH and the MSS in its cell, while the latter is set aside to be used exclusively to send control messages that are generated by the channel allocation algorithm.

### 1. INTRODUCTION

In this paper, henceforth, unless specified otherwise, the term channel or wireless channel refers to a communication channel.



Fig1.1

another MH, it sends a request message to the MSS in its own cell. The request can be granted only if a wireless channel can be allocated for communication between MSS and MH. Since channels are limited, they should be reused as much as possible. But, a channel cannot be used at the same time by two cells if they are within a threshold distance called the minimum channel reuse distance (Dmin), because it will cause interference. Such an interference is called co channel interference. A cell, say Ci, is said to be an interference neighbor of another cell, say Cj, if the distance between them is less than Dmin. So, if a channel r is used by a cell Ci, then none of the interference neighbors of Ci can use r concurrently. If using a channel in a cell causes no interference, then we say that this channel is available for the cell. When an MH needs a channel to support a call, it sends a request message to the MSS in its cell through a control channel. When the MSS receives such a message, it tries to assign a channel using a channel allocation algorithm.

Mobile Station (MS): This is basically the mobile phone

Base Station (BS): The covered area of a cellular network is divided into smaller areas called cells. Each cell has a base station which communicates simultaneously with all mobiles within the cell, and passes traffic to the Mobile Switching Centre. The base station is connected to the mobile phone via a radio interface.

IRJGES | Vol. 6 (2) May 2021 | www.irjges.com | B. Keerthana et. al.



A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 5 Issue 3 – www.ijrmmae.in – Pages 51-55

# Soil Area Network for Landslide Predict, And Avoidance System Based On ARM Cortex M3, MEMS And GSM

N.Muthukumaran14, P.Saravanan2, N.Saveetha3, Bharath4

1.2.3.4 Electronics and Communication Engineering A.R.Engineering College, Vadakuchipalayam, Kappiyampuliyur, Villupuram, Tamilnadu – 605601.

Email: n.muthukumaran.ece@gmail.com

### **I.ABSTRACT**

Around the world, avalanches and mudslides are not kidding topographical dangers influencing individuals, and bringing on critical harms each year. Around 15% of aggregate zone of India is powerless to avalanches. These zones are stamped as Landslide Hazard Zones. Avalanches happen for the most part because of overwhelming precipitation experienced by these zones amid the rainstorm season and infrequently as a repercussions of a tremor. The current routines utilizes satellite picture detecting innovation or a camera based picture detecting. In any case, these strategies are not the least expensive one too.

## II. INTRODUCTION

The arrangement this venture gives is based upon the idea of ease remote sensor systems (WSN). WSN system utilizes a sensor system comprising of sensor sections. Sensor sections are conveyed on slopes to locate the early flags going before a mudslide or avalanche. This sensor system comprises of a gathering of sensor segments set inside the vertical openings penetrated amid the system sending stage and they are introduced in a dispersed way over the checked range. Every sensor segment has two segments: the detecting segment that is covered underground and contains every one of the instruments, and the figuring part that keeps afloat and contains the processor and radio module. The sensor hub comprises of a MEMS speeding up sensor and a dirt dampness sensor, a low power information preparing unit (microcontroller) and remote correspondence unit in light of IEEE 802.15.4 RF handset. Measure of soil dampness (wetness) builds the likelihood of area and mudslides. MEMS speeding up sensor is utilized to survey the slant security. The slant steadiness is a measure of tilt/slant of the area. Any suggestive development of area changes the introduction (tilt) estimation of the MEMS sensor. Sensor hubs transport this data to host framework through the remote system. Recognition is performed by the host hub in the wake of accepting information from all the sensor hubs. In the event that it recognizes a drawing nearer avalanche or a happening one, the host framework instantly transmits a crisis SMS to the administering power at long separation by method for GSM unit interfaced with it. The venture gives a less expensive technique for avalanche forecast and counteractive action taking into account WSN with the assistance of ease sensors. WSN can be reached out to caution the general population in their home through hubs with sirens. By associating it with notice activity lights out and about the vehicles in the locale can be cautioned before an avalanche. The microcontroller picked depends on ARM Cortex M3 structural planning. ARM Cortex M3 is the cutting edge superior 32-bit ARM center

N.Muthukumaran¹et.al



Dr.R.PANNEERDHASS,M.Fage 51 PRINCIPAL PRINCIPAL PRINCIPAL A.R.ENGINEERING COLLEGE A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, VAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 6 Issue 1, July – Sep. 2020 - www.ijrmmae.in – Pages 14-21

# DESIGN AND ANALYSIS OF SINGLE LAYER QUANTUM DOT-CELLULAR AUTOMATA BASED 1-BIT COMPARATORS

Amutha.S<sup>1</sup>, Geetha.T<sup>2</sup>, Sugunya.P<sup>3</sup>, Pushparaj.E<sup>4</sup>

Department of Computer Science & Engineering, A.R Engineering College, Villupuram E-mail:udayalanayaece@gmail.com

## Abstract

Quantum dot-cellular automata (QCA) technology has emerged as a promising avenue for designing nanometer-scale computational circuits. In digital logic circuits, comparators serve as fundamental components for comparing binary values. This paper introduces and implements two 1-bit QCA-based comparator designs. These proposed QCA implementations are compact, utilizing only a single layer and exhibiting reduced complexity compared to previously reported designs. Functional validation of the proposed QCA structures has been conducted using the QCA Designer tool. Simulation results of the proposed comparators demonstrate significant improvements over existing counterparts in terms of the number of QCA cells, area requirements, cost, and complexity efficiency. Moreover, the proposed structures exhibit extremely low energy consumption. Therefore, these QCA-based comparators present viable options for low-power digital applications.

Keywords: 1-bit comparator, Low power, QCA technology, Single QCA layer

## 1. Introduction

The relentless pursuit of higher performance and increased integration in microelectronics, driven by Complementary Metal Oxide Semiconductor (CMOS) scaling, has been a cornerstone of technological advancement for decades [1]. However, the continued densification of transistors on a chip has led to escalating power dissipation within digital systems. Moreover, the constraints imposed by physical limitations on parameters such as effective channel length and gate oxide thickness have prompted a quest for alternative materials and device structures to sustain scaling efforts [1]-[4].

Quantum Dot-Cellular Automata (QCA) technology has emerged as a promising candidate to circumvent the challenges facing traditional CMOS technology. Offering advantages like rapid switching speeds, enhanced packing densities, and reduced energy consumption, QCA presents an enticing avenue for future device scaling [3], [5]. In QCA, logical states are encoded based on the position of electrons within quantum dots, with data transmission facilitated by electrostatic interactions among adjacent cells, in contrast to conventional CMOS where current flow conveys information [4].

Building logical circuits on the nanoscale with QCA entails employing various strategies for data transmission and computation [4], [7]. However, due to the reliance on electrostatic repulsions for data propagation, ensuring reliable information flow necessitates the incorporation of clocking mechanisms

605 Amuthal Social

A.R.ENGINEERING GREETS
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.



# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 6 Issue 1, July - Sep. 2020 - www.ijrmmae.in - Pages 22-30

# OPTIMAL LOAD CONTROL FOR ECONOMIC ENERGY EQUILIBRIUM IN SMART GRID USINGADAPTIVEINERTIA WEIGHTTEACHING-LEARNING-BASEDOPTIMIZATION

Dhanalakshmi  $V^1$ , Kuppulakshmi $^2$ , N.Muthukumaran $^3$ , A.Madhavan $^4$ 1,2,4 Computer Science and Engineering, 3° Electronics and Communication Engineering A.R.Engineering College, Vadakuchipalayam, Kappiyampuliyur, Villupuram, Tamilnadu – 605601.

Abstract: Optimal load management for energy balance in the smart grid (SG) is crucial due to various operational constraints and economic considerations. This research introduces a novel multi-objective optimization technique to achieve energy balance in SG, aiming to avoid penalties from excessive upstream network power extraction beyond contractual demands. A common challenge in optimal load control (OLC) is the inability to consistently achieve the global optimum in each run. To address this, we employ the Adaptive Teaching-Learning Based Optimization (ATLBO), an advanced variant of Teaching Learning Based Optimization (TLBO), which incorporates modifications during both the exploitation and exploration phases. Implemented on a modified IEEE 33-bus system, ATLBO produces outstanding results, improving energy balance, enhancing voltage profiles, and reducing distribution losses. Comparative analyses with Particle Swarm Optimization (PSO), basic TLBO, Backtracking Search Algorithm (BSA), and Cuckoo Search Algorithms demonstrate ATLBO's superiority.

Keywords: Smart grid, Optimal load control, Adaptive teaching-learning-based optimization, Multiobjective optimization.

## 1. Introduction:

Electricity is in high demand in today's power grids, leading to an imbalance between supply and demand. While traditional methods have been adjusted to meet these needs, they often result in time and financial inefficiencies. Challenges persist in distribution network performance and transmission system support. Achieving effective control over transmission line power flows through Flexible AC Transmission System (FACTS) devices, renewable energy (RE) sources, and other efficient power management devices has been a target for modern power systems. Load shedding (LS) is used as an emergency corrective measure to provide appropriate stability margins and prevent voltage collapse or blackouts, thus helping to restore the electrical system to normal operation. Energy balancing solutions in microgrids (MGs) include undervoltage load shedding (UVLS) and frequency load shedding (FLS) (UFLS); however, these solutions often overlook customer engagement and satisfaction.

Microgrids are capable of operating in either an islanding/stand-alone mode or a grid-integrated mode, depending on the scenario. Islanding involves assessing the MG's capacity and reallocating power to various loads once it is disconnected from the main grid. Utility operations predominantly manage these duties. Since the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, there have the global power industry restructuring in 1988, and more globally since 1998, the global power industry restructuring in 1988, and more globally since 1998, and more globa

605 601

A.R. ENGINEERING PORTE VADAKUCHIPALAYAM KAPPIYAMPULIYUR POST, VILLUPURAM 605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING(IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 6 Issue 4, Jan – Mar 2021 - www.ijrmmae.in Pages 28-35

# SMART SYSTEM FOR CONTROLLING AND MONITORING WATER AND TURBIDITY LEVELS IN DAM RESERVOIR USING MICRO-CONTROLLER TECHNOLOGY

N.Savitha\*, Saravanan.P, Nisha.R, Muthukumaran.N

Assistant professor, Department of ECE, A.R. Engineering, College, Villupuram. \*Corresponding author vasanthisavi@gmail.com

# ABSTRACT

A micro-controller-based technology has been developed for monitoring and controlling the water quality and quantity in dam reservoirs by using various sensors. This system is able to automatically detect and measure the changes in water and turbidity levels of incoming water for hydropower production. In this project, an Arduino UNO micro-controller and GSM Technology control the operations of the system through sending messages and regulating automatic water valves according to the instant status of the dam water. The developed prototype has four units: sensing unit, processing unit, displaying unit, and alerting unit. In the sensing unit, the ultrasonic sensor continuously monitors the change in water levels and the turbidity sensor takes turbidity measurements of incoming water. In the processing unit, the detected data are collected and fed to the microcontroller for further processing. This technology is expected to reduce the time and cost incurred during the hydropower plant operations by using a small amount of manpower and will facilitate fast information collection.

Keywords: Automation, Arduino Uno, Micro-controller, Sensors, Serialmonitor.

# 1. INTRODUCTION

Dam is a man-made structure designed to hold backwater for generating electricity, water supply, flood management or river flow diversion [1]. Dam and water reservoir are both built to regulate the flowing water and to store this latter for various purposes such as flood reduction, hydroelectric production, recreation, fisheries and irrigation. The most common problems encountered by the water reservoir and dams are mainly based on failure to fulfill the intended purpose which is to store

N.Savitha et.al.



Or.R.PANNEERDUASS, M. Beers D., A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 6 Issue 4, Jan – Mar 2021 - www.ijrmmae.in Pages 36-48

# ANALYSIS OF WOVEN GLASS EPOXY LAMINATED WITH COMPOSITE PLATE

Panneerdhass R\*, Manikandan D, Sivasubramaniyan K, Jayakumar R

Professor\* & Assistant Professor, Department of Mechanical Engineering, A.R Engineering College, Villupuram-605601, India.

Email: panneerdhass@gmail.com

## **ABSTRACT**

In this project the Buckling behavior of laminated composite plates subjected to in-plane loads is an important consideration in the preliminary design of aircraft components. The sizing of many structural subcomponents of the aircraft structures is often determined by stability constraints. The objective of the current study is to understand the influence of the length-to-thickness ratio, the aspect ratio, the fiber orientation and the cut-out shapes on the buckling load for the woven glass epoxy laminated composite plate in clamped-free-clamped-free configuration by finite element analysis using ANSYS software. Initially, buckling analysis was carried out on woven glass epoxy laminated composite plate, both; experimentally and numerically; for the two different geometric configurations to predict the critical buckling load and the test results were compared with the FEA predictions, to check the validity of the analysis methodology. The same methodology was further followed for analyzing the buckling behavior of the composite plates. The results shows the effect of orientation of fiber, aspect ratio, cut-out shape and length-to-thickness ratio on the buckling of the glass epoxy laminated composite plate.

Keywords: - Plate buckling, woven glass epoxy laminate, length-to-thickness ratio, aspect ratio, fiber orientation, cut-out shapes.

# 1. INTRODUCTION

# 1.1 INTRODUCTION TO COMPOSITE MATERIALS

There are many types of failures in engineering structures. Some of them include creep, fatigue, alternate stresses, bending, buckling etc. Buckling takes place in columns, plates,

Panneerdhass R et.al.

VILLUPURAN E 605 69i

DI.R.PANNEER THASS ME Page 36

PRINCIPAL
PRINC

" IILL-

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 7 Issue 4, Jan-March. 2022- www.ijrmmae.in — Pages 7 - 19

# LIFE PREDICTION AND STATISTICAL ANALYSIS OF E-GLASS FABER WITH ALOEVERA IN COMPOSITE SPECIMEN

D.Manikandan, A.Arulkumar, R.Anbuzhagan, K.Sivasubramaniyan Assistant Professor

Department Of Mechanical Engineering, A.R Engineering College, Villupuram E-mail:Manimech812@gmail.com

### ABSTRACT

Composite materials having major Applications in Aerospace industries and automobile industries. They have variability in their mechanical properties and also strength properties due to their internal structure. This leads to perform their safe utilization in design and manufacturing. In this study, the life prediction of the composite specimen is obtained by experimentally; the Experiments are carried according to standard ASTM D3039 in flexural and barcol Machine. The results are compared with the other specimen experimental results of the composite specimen.

Keywords: Life prediction, ASTM D3039

## 1. INTRODUCTION

In recent years conventional materials are replaced by composite materials due to their mechanical properties such as high specific strength, Elastic modulus, light weight and corrosion resistance. Aircraft and automobiles are examples of vehicles in which the application of fiber reinforced composite materials has been increasing. However, there are problems with fabrication of these composites, which require highly précised volume fraction methods like Resin transfer molding process (RTM), Vacuum Bag molding, compression molding. Whatever the method used for fabrication of composites, they are not isotropic and therefore have different mechanical properties in different directions. In addition to this, they present varying strengths due to their internal structure and to brittleness of the fibers and matrices, which means that there is no specific strength value to represent their mechanical behavior. This leads to the necessity of employing analyses for their safe utilization in design and manufacturing.

The Weibull distribution, which has recently been used for the determination of static and dynamic mechanical properties of ceramics and metal-matrix, ceramic- matrix, and polymer- matrix composites statistically. Weibull distribution is a practical method in the determination of 90% and 95% reliability values used in composite material mechanics. In this study, the life prediction of the carbon/epoxy and glass/polyester composite specimens was determined by both



Dr.R.PANNEEROMAPARA COLLEGE

A.R.ENGINEERING COLLEGE

VADAKUCHIPALAYAM

VADAKUCHIPALAYAM

VAPPIYAMPULIYUR 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 7 Issue 4, Jan-March. 2022- www.ijrmmae.in - Pages 20 - 26

## CONNECTIVITY IN A FUZZY GRAPH

Parvatha Varthini.N, Chandrapraba.R, Kathiravan.V, Silambarasan.I Assistant Professor, Department Of Science and Humanities, A.R Engineering College, Villupuram E-mail: varthinins15696@gmail.com

### **ABSTRACT**

The concept of connectivity play an important role in fuzzy graph theory. In this paper we discuss about cycle connectivity, arc connectivity, node connectivity and complement connectivity cyclic cut vertices, cyclic bridges and cyclically balanced fuzzy graphs. Connectivity of a complement fuzzy graph is analyzed. Also we discussed about connected domination in fuzzy graph using strong arcs.

Key words: cycle connectivity, are connectivity, node connectivity and complement connectivity cyclic cut vertices, cyclic bridges and cyclically balanced fuzzy graphs.

# I.INTRODUCTION TO FUZZYGRAPH

Graph theory is proved to be tremendously useful in modeling the essential features of systems with finite components. Graphical models are used to represent telephone network, railway network, communication problems, traffic network etc. Graph theoretic models can sometimes provide a useful structure upon which analytic techniques can be used. A graph is also used to model a relationship between a given set of objects. Each object is represented by a vertex and the relationship between them is represented by an edge if the relationship is unordered and by means of a directed edge if the objects have an ordered relation between them. Relationship among the objects need not always be precisely defined criteria; when we think of an imprecise concept, the fuzziness arises.

The notion of fuzzy graph was introduced by Rosenfeld in year 1975[2]. Fuzzy analogues of manystructures in crispngraph theory,like bridges,cut nodes,connectedness,trees and cycles etc were developed after that. Fuzzy trees were characterized by Sunitha and Vijayakumar [3]. The author have characterized fuzzy trees using its unique maximum spanning tree. A sufficient condition for a node to be a fuzzy cut node is also established. Center problems in fuzzy graph, blocks in fuzzy graphs and properties of self complementary fuzzy graphs were also studied by the same authors. They have obtained a characterization for blocks in fuzzy graphs using the concepts of strongest paths [8]. The authors have need the concepts of strong arcs and strong paths. As far as the applications are concerned (information networks, electric circuits, etc.), the reduction of flow between pairs of nodes is more relevant and many frequently occur than the total disruption of the theorem or the disconnection of the entire networks. In this paper we put forward the conditions under which a fuzzy graph and its complement will be connected.

In1965,L.A.Zadeh introduced a mathematical frame work to explain the concept to fun certainty in real life through the publication of a seminar paper.A fuzzy set is defined mathematically by assigning to each possible individual in the universe of discourse a value, representing its grade of membership, which corresponds to the degree, to which that individual is similar or compatible with the concept represented by the fuzzy set. The fuzzy graph introduced by A. Rosen feld using fuzzy relation, represents the relationship between the objects by precisely indicating the level of the relationship between the objects of the given set. Also he coined many fuzzy analogous graph theoretic concepts like bridge, cut vertex and tree. Fuzzy graphs have many more applications in modeling real time systems where the level of information inherent in the system varies with different levels of precision.

The notion of fuzzy set stems from the observation made by [18] L.A.Zadeh (1965) that more often than not, the classes of objects encountered in real physical world do not have precisely defined criterial of membership". This observation emphasis the gap existing between mental representation of reality and usual membership". This observation emphasis the gap existing occurred mathematical representation therefore, which are based onbinary logics, precies numbers differential

arvatha Varthini.N et.al.

605 601

A.R. ENGINEERING PAREIRO KAPPIYAMPULIYUR POST, VILLUPURAM SOS 601.

" .III 1.V

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 9 Issue 1, April – June. 2023 - www.ijrmmae.in – Pages 29-35

# CONNECTIVITY IN A FUZZY GRAPH

Parvatha Varthini.N, Chandrapraba.R, Kathiravan.V, Silambarasan.I
Assistant Professor, Department Of Science and Humanities,
A.R Engineering College, Villupuram
E-mail: varthinins15696@gmail.com

### **ABSTRACT**

The concept of connectivity play an important role in fuzzy graph theory. In this paper we discuss about cycle connectivity, arc connectivity, node connectivity and complement connectivity cyclic cut vertices, cyclic bridges and cyclically balanced fuzzy graphs. Connectivity of a complement fuzzy graph is analyzed. Also we discussed about connected domination in fuzzy graph using strong arcs. Key words: cycle connectivity, arc connectivity, node connectivity and complement connectivity cyclic cut

vertices, cyclic bridges and cyclically balanced fuzzy graphs.

# I.INTRODUCTION TO FUZZYGRAPH

Graph theory is proved to be tremendously useful in modeling the essential features of systems with finite components. Graphical models are used to represent telephone network, railway network, communication problems, traffic network etc. Graph theoretic models can sometimes provide a useful structure upon which analytic techniques can be used. A graph is also used to model a relationship between a given set of objects. Each object is represented by a vertex and the relationship between them is represented by an edge if the relationship is unordered and by means of a directed edge if the objects have an ordered relation between them. Relationship among the objects need not always be precisely defined criteria; when we think of an imprecise concept, the fuzziness arises.

The notion of fuzzy graph was introduced by Rosenfeld in year 1975[2]. Fuzzy analogues of manystructures in crispngraph theory, like bridges, cut nodes, connectedness, trees and cycles etc were developed after that. Fuzzy trees were characterized by Sunitha and Vijayakumar [3]. The author have characterized fuzzy trees using its unique maximum spanning tree. A sufficient condition for a node to be a fuzzy cut node is also established. Center problems in fuzzy graph, blocks in fuzzy graphs and properties of self complementary fuzzy graphs were also studied by the same authors. They have obtained a characterization for blocks in fuzzy graphs using the concepts of strongest paths [8]. The authors have need the concepts of strong arcs and strong paths. As far as the applications are concerned (information networks, electric circuits, etc.), the reduction of flow between pairs of nodes is more relevant and many frequently occur than the total disruption of the theorem or the disconnection of the entire networks. In this paper we put forward the conditions under which a fuzzy graph and its complement will be connected.

In1965,L.A.Zadeh introduced a mathematical frame work to explain the concept to fun certainty in real life through the publication of a seminar paper. A fuzzy set is defined mathematically by assigning to each possible individual in the universe of discourse a value, representing its grade of membership, which corresponds to the degree, to which that individual is similar or compatible with the concept represented by the fuzzy set. The fuzzy graph introduced by A. Rosen feld using fuzzy relation, represents the relationship between the objects by precisely indicating the level of the relationship between the objects of the given set. Also he coined many fuzzy analogous graph theoretic concepts like bridge, cut vertex and tree. Fuzzy graphs have many more applications in modeling real time systems where the level of information inherent in the system varies with different levels of precision.

The notion of fuzzy set stems from the observation made by [18] L.A.Zadeh (1965) that more often than not, the classes of objects encountered in real physical world do not have precisely defined criterial of membership". This observation emphasis the gap existing between mental representation of reality and usual mathematical representation therefore, which are based onbinary logics, precies numbers, differential

Parvatha Varthini.N et.al.



Dr.R.PANNEEROHAS Page 29 E
PRINCIPAL COLLEGE
PRINCIPAL AYAM,
A.R.ENGINEERING ALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR 601.
KAPPIYAMPURAM.605 601.



# International Research Journal in Global Engineering and Sciences. (IRJGES)

ISSN: 2456-172X | Vol. 4, No. 2, June-Aug 2019

Pages 166-176 | Cosmos Impact Factor (Germany): 5.195

Received: 02.08.2019 Published:28.08.2019

# ANALYSIS OF SURFACE PREPARATION IN EN8 STEEL MATERIALS BY USING COATING METHODS

D.Manikandan, R.Panneerdhass, R.Anbuzhagan, K.Sivasubramaniyan Assistant Professor

Department Of Mechanical Engineering, A.R Engineering College, Villupuram E-mail:Manimech812@gmail.com

### Abstract

In this present paper thermal spray surface modification technique has been used to enhance the corrosion resistances of EN8 steel substrate. After an exhaustive literature survey alloy powder Al<sub>2</sub>O<sub>3</sub>, TiO<sub>2</sub> have been selected to deposit on the substrate steel specimen with help of thermal spray techniques. The corrosion resistance of the coated and uncoated specimens was investigated according to ASTM standard AISI1040. An aim of the present study is to analyze of various coating powder like aluminium oxide, Titanium oxide and zirconium are used to compare the better coating thickness range by using ANSYS software. It can be designed using CATIA software and imported the model to ANSYS work bench software. From the result it can be choosing the better coating powder on the EN8 steel to be investigated in this project. It has been concluded that the alloy powder deposited with the help of thermal spray coating process have been found very useful to minimize the corrosion problem of carbon steels.

Keywords: Thermal spray coating, plasma spray, hardness and corrosion resistances.

### 1. INTRODUCTION

It is an unalloyed medium carbon steel. EN8 is a medium strength steel, good tensile strength, its suitable for automobile components likes shaft, stressed pin, studs, keys etc. EN8 is a very popular grade of through hardening medium carbon steel, which is readily machinable in any condition. Wear, friction and corrosion resistances are responsible for many problem and large costs in a modern civilization and engineers and designers always must take these factors into account when constructing different equipments [1]. It can be further surface- hardened typically to 50-55 HRC by induction processes components with enhanced corrosion resistances. For such application the

D.Manikandan et.al.

DIR PAHNER DHASS, ME PHO DIR PAHNER DHASS, ME PHO PRINCE PHONE PHOST. VADAKUCHIPALAY POST. VADAKUCHIPALAY POST. VADAKUCHIPALAY POST. KAPPIYAMPULIYUR 605 601. VILLUPURAM.605 601.



05 601



# International Research Journal in Global Engineering and Sciences. (IRJGES)

ISSN: 2456-172X | Vol. 5, No. 4, December - February, 2021 Pages 25-32 | Cosmos Impact Factor (Germany): 5.195

Received: 02.12.2020 Published: 28.02.2021

# IMPLEMENTATION OF LOW POWER 17-TRANSIST OR TRUE SINGLE-PHASE CLOCKING FLIP –FLOP DESIGNS WITH 45 NM CMOS TECHNOLOGY

Dhanalakshmi V<sup>1</sup>, Kuppulakshmi<sup>2</sup>, N.Muthukumaran<sup>3\*</sup>, A.Madhavan<sup>4</sup>

1.2.4 Computer Science and Engineering, <sup>3\*</sup> Electronics and Communication Engineering

A.R.Engineering College, Vadakuchipalayam, Kappiyampuliyur, Villupuram, Tamilnadu – 605601.

Email: n.muthukumaran.ece@gmail.com

### Abstract:

Flip-Flops (FFs) serve as fundamental storage components extensively employed in digital system designs, particularly in structures involving pipelining and modules constructed by FFs. However, FFs contribute significantly to both the power consumption and chip area of digital systems. Consequently, there arises a demand for FF designs that prioritize low power consumption and reduced area. In this paper, a low-power 17-True Single-Phase Clock (TSPC) flip-flop method is proposed, which has gained widespread usage in advanced design.

The proposed flip-flop operates in 45 nm CMOS and features a logic structure of the TSPCFF of master-slave type. The master stage comprises static CMOS logic, while the slave stage utilizes a mixed combination of static CMOS logic and complementary pass transistor logic. This design ensures that the TSPC FF circuit remains fully static during operation, thus preventing leakage power dissipation. The proposed TSPC FF design optimizes a 17-transistor logic structure reduction flip-flop (LRFF) concerning area and power consumption without compromising functionality. To validate the design, three FFs—Transmission Gate based Flip-Flop (TGFF), LRFF, and the proposed TSPC FF—are implemented and simulated using gpdk 45 nm technology library with a supply voltage (Vdd) of 1V and clock frequency of 500MHz in DSCH and MICROWIND tool.

Keywords: TSPC, VLSI, Flip-Flop, RAM, ROM, SRAM.

### I. Introduction:

Two essential characteristics of CMOS devices are high noise immunity and low static power consumption. The CMOS arrangement draws significant power only momentarily during transitions between on and off states due to one transistor of the pair always being off. Consequently, CMOS devices generate less waste heat compared to other logic types, such as transistor-transistor logic (TTL) or N-type metal-oxide-semiconductor logic (NMOS). CMOS also enables high logic density on a chip, making it the most widely used technology in very-large-scale integration (VLSI) chips.

The term "CMOS" refers to both a specific style of digital design and the array of techniques used to implement that electronics on integrated circuits (chips). CMOS circuits dissipate less power than logic families with resistive load. As this advantage has become increasingly important, CMOS processes and variations have come to dominate, with the majority of modern integrated circuit manufacturing utilizing CMOS processes. CMOS circuits employ a combination of p-type and n-type metal-oxide-semiconductor field-effect transistors (MOSFETs) to implement logic gates and other digital circuits. While CMOS logic can be demonstrated with discrete devices, commercial CMOS products are integrated circuits composed of billions of transistors of both types on a rectangular silicon chip ranging from 10 to 400 mm2. CMOS always uses enhancement mode MOSFETs.

VILLUPURAM CONTROL OF THE PROPERTY OF THE PROP

Dhanalakshmi V et.al.

A.R.ENGINEEHTIPALAYAMIST.

A.R.ENGINEEHTIPALAYAMIST.

VADAKUCHIPALAYAMIST.

VADAKUCHIPALAYAMIST.

VADAKUCHIPALAYAMIST.

VADAKUCHIPALAYAMIST.

VARAMPULIYUR 605.

KAPPIYAMPULIYURAM.605.601.

International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN : 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10

# Power Flow of MTDC Using Droop Control & Impact of DC Voltage Drops

B.Keerthana<sup>4</sup>, R.Udhayakumar<sup>2</sup>, P.M.Kumarasan<sup>3</sup>, Indhumathf<sup>4</sup>

Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram K-mail:udayalanayacce@gmail.com

Abstract—This paper investigates the ramifications of DC transmission voltage drops on the distribution of DC grid balancing power under the application of DC voltage droop control. In a multiterminal VSC-HVDC (MTDC) system, variations in DC line voltage due to drops lead to nonuniform adjustments in DC line voltage due to drops lead to nonuniform adjustments in DC bus voltages, thereby impacting the allocation of instantaneous balancing power. The influence of DC voltage droop constants determines the extent to which these voltage drops affect the sharing of balancing power across the DC grid. An analytical expression is formulated to estimate the distribution of balancing power, accounting for DC line voltage drops. A five-terminal MTDC system is simulated using PSCAD to demonstrate the effects of DC line voltage drops and validate the proposed analytical expression.

Index Terms: DC grid, droop control, multiterminal VSC-HVDC (MTDC), voltage source converter

# NOMENCLATURE

VSC: Voltage source converter

HVDC: High-voltage DC transmission MTDC: Multiterminal VSC-HVDC

# INTRODUCTION

In recent years, significant research efforts have been directed towards the development of VSC-based multiterminal HVDC systems, particularly driven by the expansion of offshore wind farms, such as those in the North Sea region. Multiterminal VSC-HVDC (MTDC) systems, also referred to as DC grids, offer advantages including reduced transmission losses, enhanced control flexibility, synchronization of asynchronous grids, and ease of integrating new VSC-HVDC terminals into existing MTDC setups.

Control strategies proposed in the literature for MTDC systems can be broadly classified into two groups: constant DC voltage control schemes (often termed master-slave control schemes) and DC voltage droop control schemes. The operational principle of constant DC voltage control, also known as the master-slave scheme, has been extensively discussed in prior works. However, one drawback of this approach is its dependency on the normal operation of the DC voltage regulating terminal (i.e., the master terminal). In contrast, DC voltage droop control involves two or more terminals participating in DC voltage regulation, thereby sharing the responsibility of instantaneous power balancing among them. This approach is considered more reliable as it ensures continued operation of the MTDC system even if

While the basic working principle of DC voltage droop control in MTDC systems has been explored, the impact of DC line voltage drops on primary DC grid power balancing has not been thoroughly analyzed. This paper aims to address this gap by investigating how DC line voltage drops influence the distribution This paper aims to address this gap by investigating how DC line voltage drops influence the distribution of balancing power in droop-controlled MTDC systems. The paper also sheds light on the subtle yet IRJGES [Vol. 6 (2) Juune-August 2021 | www.iriges.com | B | Keernmie RDHASS, ME., Ph.D., PRINCIPAL OF BEERING COMBET | PRINCIPAL OF BEERING COMBET | A.R. ENGINEERING COMBET | COMBET

KAPPIYAMPULIYUR POST, VILLUPURAM-GOS GOT.



# International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10

significant influence of DC line voltage drops on balancing power distribution, which is crucial for optimizing the operation of MTDC systems.

DC bus voltage variations are dependent on the topology and line conductances of the DC grid, resulting in different responses from converter terminals to changes in power flow across various locations of the grid. Additionally, the chosen DC voltage droop constants also influence the severity of the impact of DC bus voltage variations on the distribution of balancing power.

This paper compares two mathematical models for DC grid power balancing to understand the influence of DC line voltage drops on power flow. The first approach neglects DC line voltage drops, while the second one, which is the main contribution of this paper, considers these drops to describe the system interaction more accurately. A five-terminal VSC-HVDC system is simulated in PSCAD, and the results are compared with the estimations from the two mathematical models. It is demonstrated that the proposed model (the second approach) accurately describes the droop interactions in the DC grid and serves as a useful tool to understand the influence of DC line voltage drops on the power flow of DC grids.

This paper is outlined as follows:

In Section II, the different types of VSC-HVDC control are discussed.

 Section III discusses the distribution of DC grid balancing power in an ideal lossless DC grid in the presence of DC voltage droop control.

• In Section IV, the impact of DC line voltage drops is discussed.

 Section V discusses the proposed analytical expression for estimating the distribution of balancing power in DC voltage droop controlled DC grid systems.

 Section VI presents simulation studies to demonstrate the impacts of DC voltage line drops and to validate the proposed analytical estimation method.

Conclusions are drawn in Section VII.

# II. VSC-HVDC TERMINAL CONTROL![

Fun

DI.R.PANNEERDHASS,M.E.,Ph.D.,

DI.R.PANNEERDHASS,M.E.,Ph.D.,

PRINCIPAL

PRINCIPAL

A.R.ENGINEERING

POST,

A.R.ENGINEERING

IRJORSE FOIL 6 2 Hour Color of Color of

International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10




Fig. 1. Schematic diagram of the VSC controller.

## TABLEI LISTOFS YMBOLSINFIG. 1

,	DC bus power measurement of the converter;
$P_{AC}$	AC side converter power measured at PCC;
PLL	Phase locked loop;
PWM	Pulse width modulator:
labe	3-phase AC current measured at PCC;
$V_{Xabc}$	3-phase AC voltage measured at PCC;
VCabe	3-phase AC voltage output of VSC:
V Cabe	3-phase AC voltage reference for VSC:
$V_{Xd}$ , $V_{Xg}$	AC vollage at PCC in da reference from
V Cd V Cg	AC Voltage of VSC in da reference from
V Cd V Cq	AC voltage reference for VSC in dq reference frame
$I_o$	DC current of VSC behind DC capacitor;
U	DC voltage measurement (pole to pole);
$\omega$	Synchronous frequency in rad/s;
L, r	Series filter inductance and resistance:
$C_{DC}$	DC bus capacitance;
$k_p, k_i$	Proportional and integral gains of inner controller
abc/dq	abe to dq transformation
dq/abc	dq to abe transformation
$e_{d}, e_{q}$	Error signals of PI controllers of the inner current loop

# TABLE I LIST OF SYMBOLS IN FIG. 1

A. Basic VSC Controller The most commonly used control approach for VSC is the decoupled axes of axes) oriented control, where the d-axis of the synchronously rotating reference frame to tright of the voltage phasor of phase-A measured at the point of common coupling (RCA) which in the Country of the Coun


PRINCIPAL AND ARENG COLING COL

ten -

# International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10

alignment also implies that the quadrature axis (q-axis) component of the voltage measurement becomes zero. The sign convention used here for the power and current measurements of the converter ensures that power/current measured at a converter terminal is positive if it flows from the AC grid to the DC that power/current station, with positive corresponding to rectifier mode of operation and negative corresponding to inverter mode of operation.

The voltage-current relation in Fig. 1 is given by: After the abc/dqt rans formations, (1) takes the form of (2) After the abc/dqt rans formations, (1) takes the form of (2)



![Fig. 2 DC terminal control configurations and the corresponding DC voltage versus power characteristics. (a) DC bus power controller (b) DC voltage regulator (c) DC voltage droop controller](Insert URL of Fig. 2)

The apparent power and real power measured at PCC are expressed as:

SPCC=PPCC+jQPCCSPCC=PPCC+jQPCC

where PPCC and QPCC refer to apparent power and real power of the converter. Vd and Id refer to direc t-axis (d-axis) voltage and direct-axis current of the converter measured at PCC.where PPCC and QPCC refer to apparent power and real power of the converter. Vd and Id refer to direct-axis (d-axis) voltage and direct-axis current of the converter measured at PCC.

Reactive power/AC voltage control is not the focus of this paper and will not be discussed here. Depending on the mode of operation, the active current reference *IrefIref* is used to control active power or DC bus voltage of the VSC.

**B. DC Voltage and Power Control Modes** 

A VSC-HVDC terminal, hereafter simply referred to as a DC terminal, may have one of three control modes: constant power mode, constant voltage mode, or droop mode of control. The DC voltage versus power characteristic curve of the constant power mode DC terminal is shown in the top of Fig. 2(a), where PdPd is the power axis and VdVd is the DC bus voltage.

IRICE FMO (2) Juune-August 2021 | www.iriges.com | B.R.PANNEERDHASS,M.E.,Ph.D.,

A.R.ENGINEERING COLPEGE

A.R.ENGINEERING COLPEGE

VADAKUCHIPALAYAM,

VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST,

VILLUPURAM, 605 601.

MMI . I LIFU.

# International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 - August 2021 | Pages 1-10

Constant DC voltage control is represented by Fig. 2(b) (bottom), where VrefVref and VdVd refer to DC voltage reference and actual DC bus voltage, respectively. A DC terminal which regulates DC voltage will have a DC voltage versus power characteristic curve shown in Fig. 2(b) (top).

DC voltage droop control can be seen as a combination of the first two types of VSC-HVDC control. It tries to control power to its reference level while at the same time contributing some balancing power. Since these two actions are somewhat contradicting (i.e., power control and DC voltage control), one action happens at the cost of steady-state deviations for the other. DC voltage droop control is shown in Fig. 2(c) (bottom), and the corresponding PdPd versus VdVd characteristic is shown in Fig. 2(c) (top). In Fig. 2(c) (bottom), the symbol kPkP refers to the DC voltage response (analogous to the frequency response of synchronous generators in AC grids) and has the unit of MW/kV. The slope is often given in terms of the DC droop constant kdkd, which is the ratio of change in DC bus voltage to the corresponding change in converter power both in per-units. It could also be defined as the change in DC voltage in per-unit that results in a 100% change in converter power flow. The DC voltage droop constant kdkd and the DC voltage response kPkP are related to each other by:

 $kP=kd\times P$ ratedVrated $kP=kd\times V$ ratedPrated

Where PratedPrated and VratedVrated refer to rated power and rated DC voltage of the DC terminal, respectively.

From the DC voltage droop controller in Fig. 2(c) (bottom), the error signal  $\Delta V d\Delta V d$  is given by:  $\Delta V d = V ref - V d \Delta V d = V ref - V d$ 

At steady state, the relation between DC voltage and converter power then becomes:  $\Delta P d = k d \times \Delta V d \Delta P d = k d \times \Delta V d$ 

It could be noted that the steady-state characteristics in constant power control mode and constant DC voltage control mode could be represented by DC voltage droop controllers with kd=0kd=0 (i.e., kPkP) and  $kd=\infty kd=\infty$  (i.e., kP=0kP=0), respectively. For analytical purposes, a large (but finite) value of kdkdcould sufficiently represent steady-state behavior in constant DC voltage control mode.

In the absence of DC voltage error signal, the converter power will be the same as the power reference without any steady-state deviations. Hence, for precise control of power, the DC voltage reference in Fig. 2(c) (bottom) should be assigned according to results from load flow analysis conducted for the entire DC grid. For further details about DC grid load flow analysis, the reader is referred to [9].

Now let us consider an initial steady-state operating point of the controller in Fig. 2(c) (bottom) with input and output variables represented by the superscript "1," i.e., Pd1Pd1, Vref1Vref1, Vd1Vd1, and PPCC1PPCC1. The input/output variables at another steady-state point could be expressed in terms of the initial steady-state conditions expressed by  $\Delta P d\Delta P d$ ,  $\Delta V \text{ref} \Delta V \text{ref}$ ,  $\Delta V d\Delta V d$ , and  $\Delta P P C C\Delta P P C C$ . Substituting  $\Delta V d1 \Delta V d1$  into  $\Delta P d1 \Delta P d1$  yields the relation:

 $\Delta P d1 = k d \times \Delta V d1 \Delta P d1 = k d \times \Delta V d1$ 

Furthermore, we assume that during initial steady-state conditions, all error signals are zero, as in  $\Delta V$ refl= $\Delta P$ PCC1= $0\Delta V$ refl= $\Delta P$ PCC1=0. Substituting  $\Delta V$ d1 $\Delta V$ d1 into  $\Delta P$ d1 $\Delta P$ d1, we obtain:

From this, the change in output of the droop controller due to changes in inputs becomes:  $\Delta P d1 = k d \times \Delta V d1 \Delta P d1 = k d \times \Delta V d1$ 

In matrix form, this could be rewritten as:

 $\Delta Pd = kd \times \Delta Vd \Delta Pd = kd \times \Delta Vd$ 

Other vectors such as *PinPin*, *PoutPout*, and *VdVd* are also defined in a similar manner. The vector, which refers to power flow into the DC grid via the DC terminals, is given by: Pin=Y°VdPin=Y°Vd

where YY refers to the admittance matrix of the HVDC grid, and the symbol oo is the entry-wise (pointto-point) matrix multiplication operator, also called Hadamard product operator. Differentiation of the

IRJGES | Vol. 6 (2) Juune-August 2021 | www.irjges.com | B. Keerthana et.al

Dr.R.PANNEERDHASS,M.E.,Ph.D., A.R. ENGINEERING COLLEGE VADAKUCHIPALAYAM,

KAPPIYAMPULIYUR POST, " IIPURAM-605 601.



### International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10

power flow equations of individual terminals with respect to the nodal voltage vector results in the Jacobian matrix JJ of the DC grid. This is mathematically given by:

*J=∂Pin∂VdJ=∂*Vd∂Pin

If the HVDC grid has an initial state given by Vd1Vd1, the linearization of power flow equation around the initial steady-state point is given by:

 $\Delta Pin = J \times \Delta V d \Delta Pin = J \times \Delta V d$ 

Hence, the relationship between the vectors representing small DC voltage variations  $\Delta V d\Delta V d$  and small nodal power variations  $\Delta Pin\Delta Pin$  is given by:

 $\Delta Pin=J\times\Delta Vd\Delta Pin=J\times\Delta Vd$ 

If the vector  $\Delta Pin\Delta Pin$  is known, the voltage vector  $\Delta Vd\Delta Vd$  could be found by:

 $\Delta V d = J - 1 \times \Delta P i n \Delta V d = J - 1 \times \Delta P i n$ 

Care should be taken while computing J-1J-1 to avoid the singularity condition during the inverse matrix calculation. The inverse matrix gets closer to singularity if computed close to a flat DC voltage profile (i.e., when all DC bus voltages are very close to each other and DC grid power flow approaches zero). Once computed at a suitable operating point, the Jacobian matrix could be applied for a wider range of operations with negligible errors.

Equation (11) is rewritten in vector form as:

 $\Delta Pd = kd \times \Delta Vd \Delta Pd = kd \times \Delta Vd$ 

indicating the relationship between changes in power references of the DC terminals with the resulting steady-state changes in injected powers at each of the terminals. From (24) and (27), the DC voltage change becomes as:

 $\Delta Vd = \Delta Vd1 + \Delta Vd2\Delta Vd = \Delta Vd1 + \Delta Vd2$ 

Comparing (18) and (27), the differences in the two equations result from the differences between the constant matrices JJ and J-1J-1. As discussed in Section III, the matrix JJ is independent of DC grid topology since a lossless grid was assumed to establish the mathematical relation. In contrast, in the proposed analytical method, the constant matrix J-1J-1 is dependent upon DC line resistances and hence upon DC grid topology. This is reflected by the presence of the DC Jacobian matrix JJ in (27). Due to the line voltage drop considerations, the proposed method gives an accurate mathematical model of the interaction between power control reference changes and the resulting observed power flow pattern in the DC grid.

# V. EFFECT OF INCREASING/DECREASING DC VOLTAGE DROOP CONSTANT

From (5), it could be seen that the DC droop constant in physical units (i.e., kdkd, the DC voltage response in MW/kV of a single terminal) could be changed by changing either the rated power PratedPrated, rated DC voltage VratedVrated, or the DC droop constant (i.e., kdkd). Since PratedPrated and Vrated Vrated are fixed parameters for an already existing DC grid, kdkd is the only means for changing the value of kdkd. By following the same practice as in frequency droop control of synchronous generators, it may be reasonable to assign all DC terminals participating in DC voltage control the same value of kdid.

Now, consider an initial value of the DC voltage response vector kPlkP1, such that a new DC voltage response vector kPkP is given by:

 $kP = \alpha \cdot kP + kP = \alpha \cdot kP$ 

where  $\alpha\alpha$  refers to a scaling factor by which we want to vary the droop constants of the entire DC grid. Then the initial total DC voltage response will be given by  $\sum kP1\sum kP1$ . Substituting kPkP into the definition of KPKP in (15), we obtain:

KP = diag(kP)KP = diag(kP)

where diagdiag refers to a mathematical operator which transforms a vector into a diagonal matrix. Substituting (30) into the definition of YY, we obtain: HEERDHASS,M.E.,Ph.D.,

 $Y = G \times \operatorname{diag}(kP) \times GTY = G \times \operatorname{diag}(kP) \times GT$ 

PRINCIPAL Dinne-August 2021 | www.iriges.com | B. KeerthaniGeral College VADAKUCHIPALAYAM KAPPIYAMPULIYUR EF 65T, VILLUPURAM 605 601

VILLUPURAM-605 601.

VILL -

### International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 - August 2021 | Pages 1-10

Equation (26) could further be simplified as:

Pin=YoVdPin=YoVd

 $Pin=(G \times diag(kP) \times GT) \circ VdPin=(G \times diag(kP) \times GT) \circ Vd$ 

 $Pin=(G\circ Vd)\times \operatorname{diag}(kP)\times (G\circ Vd)T\operatorname{Pin}=(G\circ Vd)\times \operatorname{diag}(kP)\times (G\circ Vd)T$ 

Pin=J×VdPin=J×Vd

where II refers to the identity matrix and the matrix JJ, termed here as the steady-state sensitivity matrix, is a dimensionless quantity. Matrix JJ describes the quantitative relation between DC voltage variations and corresponding power flow variations.

Hence, in the ideal lossless model, increasing/decreasing the size of the DC droop constant in all HVDC terminals by a scalar constant will not have any impact on the steady-state power flow of the HVDC

By following a similar procedure for the matrix J-1J-1, we get the relationships given by:  $\Delta V d = J - 1 \times \Delta P in \Delta V d = J - 1 \times \Delta P in$ 

This indicates that, with increasing values of the scalar multiplier  $\alpha\alpha$ , the power flow pattern is affected more strongly by the DC grid line resistances (and hence by its topology). As a result, with larger values of  $\alpha\alpha$ , the balancing power distribution shows a larger deviation from the one predicted by the lossless analytical model. Since  $\alpha\alpha$  and kdkd are inversely proportional, larger values of  $\alpha\alpha$  correspond to smaller values of kdkd and vice versa.

Hence, we can conclude that, for smaller DC droop constants kdkd applied to the HVDC terminals, the DC line voltage drops cause larger deviations of DC grid balancing power distribution from the estimation approach which ignores DC line resistance effects.

### VI. Simulation Studies

A five-terminal VSC-HVDC network (shown in Fig. 3) was simulated using a PSCAD simulation software package. The simulation results are needed for checking the validity of the proposed analytical model, which estimates distribution of balancing power among different terminals, and for demonstrating the impact of DC line voltage drops in comparison to the ideal lossless analytical model. Since much of the focus in this paper is on the MTDC aspect, the AC grids are represented only by aggregated models. Symbols used in Fig. 3 are listed here.

| Parameters of HVDC Terminals Used in the Simulation |

Symbol	Description		
VratedVrated	Rated pole-to-pole DC grid voltage (in kV).		
kdkd	DC voltage droop constant of the <i>ithith</i> DC terminal (in per-unit).		
PmaxPmax	xPmax Maximum (rated) power capacity of ithith DC terminal (in MW).		
LijLij	DC transmission distance between terminals ii and jj.		

The parameters of the converter terminals used in the simulation are shown in Table II.

The set of values given in Table III was chosen arbitrarily to represent an initial steady-state condition for the MTDC system. In practice, this data should come from the power dispatcher (scheduler).

In order to get the desired power flow pattern, the unknown power at terminal 2 should be computed and used as the power reference for terminal 2.

Similarly, unknown DC bus voltages at terminals 1, 4, and 5 should be found and used as DC voltage references in the DC droop controllers of these terminals.

Terminal 3 is a constant power terminal of known reference value and hence does not need any more data. A short MATLAB code was written for solving the given DC load flow problem. DC load flow analysis of the given DC grid (i.e., Fig. 3) together with the desired power flow pattern (i.e., Table III) gives the set of numerical solution shown in Table IV.

The values in Table IV were used as power and DC voltage references in the respective DC terminals. Steady-state powers and DC bus voltages observed from the PSCAD simulation are shown in Table V.



IRJGES | Vol. 6 (2) Juune-August 2021 | www.iriges.com | B. Keerthana.er.er.er.ph. SS.M.E.ph.D.:

Dr.R.PANIZERONI Page 7

PRINCIPAL AYAM.

A.R.ENGINEERING COLLEGE

VADAKUCHIPALAYAM.

VADAKUCHIPALAYAM.

VADAKUCHIPALAYAM. KAPPIYAMPULIYUR POST VILLUPURAM 605 601.

International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 - August 2021 | Pages 1-10

Now, the power reference of terminal 3 is changed from 750 to 800 MW. This corresponds to a change

TABLE V: PSCAD SIMULATION RESULTS WITH DC VOLTAGE AND DC POWER REFERENCES COMING FROM TABLE IV

Terminal	DC Voltage (IV)			
1	DC Voltage (kV)	Power (MW)		
2	500	750		
3	510	750		
4	520	800		
5	530	750		
The resulting stood	540	750		

he resulting steady-state power flow pattern after applying a change of 50 MW is shown in Table VI.

A. Comparison of Simulation Results With Estimation by Ideal Lossless Model

The total DC voltage response of the HVDC grid is given by:

 $Vtotal = \sum_{i=1}^{i=1} 5kdiPi, maxVtotal = \sum_{i=1}^{i=1} 5kdiPi, max$ 

Substituting relevant values of kdkd from Table II and the value of Pi,maxPi,max from (33) into the expression of VtotalVtotal in (18), we get:

 $\label{eq:Vtotal} Vtotal = 0.00015 \times 2000 + 0.0002 \times 2000 + 0.00025 \times 2000 + 0.0003 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.0002 \times 2000 + 0.00025 \times 2000 + 0.0003 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.0002 \times 2000 + 0.00025 \times 2000 + 0.0003 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00025 \times 2000 + 0.0003 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.00035 \times 2000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.0000 = 2.15 \; \text{kV} \\ Vtotal = 0.00015 \times 2000 + 0.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.0000 = 2.000$  $= 0.00015 \times 2000 + 0.0002 \times 2000 + 0.00025 \times 2000 + 0.0003 \times 2000 + 0.00035 \times 2000 = 2.15 \text{kV}$ 

Decreasing power reference of terminal 3 by 50 MW (i.e., 50 MW) corresponds to the vector  $\Delta P = [0,0,-50,0,0] \Delta P = [0,0,-50,0,0]$  MW. Substituting this value of  $\Delta P \Delta P$  and the value of V total V totalfrom (34) into (18), we find the estimated changes in nodal power flow shown in Table VII. The changes in DC bus voltages are estimated by (15).

TABLE VII: COMPARISON OF ESTIMATED STEADY-STATE CHANGES (BY LOSSLESS MODEL) WITH PSCAD SIMULATION RESULTS

Terminal **Estimated Estimated Change** Simulation Results Simulation Results Change in Power in DC Voltage Change in Power Change in DC (MW) (kV) (MW) Voltage (kV) -1.5 -1.5-1.5-1.5-2 -2 -2 -2 3 -2.5-2.5-2.5 -2.54 -3 -3 -3 -3 -3.5 -3.5-3.5-3.5

From Table VII, it is evident that the ideal lossless model results in large errors in estimating the changes in DC bus voltages and nodal powers. It is also noticeable that, for terminals with droop control (i.e., 1, 2, 4, and 5), the estimation errors for change in power are nearly equal to the corresponding estimation error for change in DC bus voltage, suggesting that the DC bus voltage variations should be accounted for in order to accurately estimate the distribution of DC grid balancing power after the occurrence of power flow change at one terminal.

### B. Estimation of Power Sharing by Proposed Analytical Expression

Now we try to estimate the power flow after a change in power reference of terminal 3 by 50 MW, but this time using the proposed analytical method which considers DC line voltage drops. In order to do so, we first have to compute the matrix  $\partial P \partial V \partial V \partial P$ . For the initial steady state given by Table V, the resulting Jacobian matrix JJ is given by (35), shown at the bottom of the page. This is computed by deriving the power flow equation of each node with respect to the DC bus voltage vector. By substituting for kdkd (from Table II) and JJ from (35) into (32), the matrix  $\partial P \partial V \partial V \partial P$  becomes:

VILLUPURAM

605 601

IRJGES NOT 6 (2) Juune-August 2021 | www.irjges.com | BKR. PANNEERDHASS, ME., Ph.D., A.R. ENGINEERING CONS VADAKUCHIPALAYAR KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

### International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 - August 2021 | Pages 1-10

	F0.00015	0.0002	0.00025	0.0003	0.00035 0.00035 0.00035 0.00035
	0.00015	0.0002	0.00025	0.0003	0.00035
OP _	0.00015	0.0002	0.00025	0.0003	0.00035
a	0.00015	0.0002	0.00025	0.0003	0.00035
	0.00015	0.0002	0.00025	0.0003	0.00035

Multiplying  $\partial P \partial V \partial V \partial P$  by  $\Delta V = 2.15 \Delta V = 2.15$  kV, we can find the resulting power distribution  $\Delta P \Delta P$ . The DC bus voltage vector  $\Delta V \Delta V$  could be computed by (28). The estimated steady-state changes in DC bus voltages and powers from the analytical expressions are shown in Table VIII. The corresponding changes from the PSCAD simulation of the system are also included for comparison.

It is interesting to check the possibility that errors do not arise from the droop controllers not working properly. From Table VIII, it could be shown for all terminals that  $\Delta P = \partial P \partial V \Delta V \Delta P = \partial V \partial P \Delta V$ , both in the analytical and simulation results.

TABLE VIII: COMPARISON OF ESTIMATED STEADY-STATE CHANGES (BY PROPOSED MODEL) WITH PSCAD SIMULATION RESULTS, 50 MW

		Estimated Change in DC Voltage (kV)	C'letion Desults	Simulation Results Change in DC Voltage (kV)
1	-1.5	-1.5	-1.5	-1.5
2	-2	-2	-2	-2
3	-2.5	-2.5	-2.5	-2.5
4	-3	-3	-3	-3
5	-3.5	-3.5	-3.5	-3.5

The small estimation errors in Table VIII show that the derived analytical expression can indeed accurately estimate the steady-state changes of terminal powers and terminal voltages.

### C. Impact of Size of DC Voltage Droop Constant

To observe the impact of the size of the DC voltage droop constant on load sharing, three droop constants (for terminals 1, 2, 4, and 5) were tested for the same step change in power of terminal 3 (i.e., from 0 to 250 MW). Simulation results are shown in Table IX. The sizes of the converters were kept the

It is shown in Table IX that, as the droop constant decreases, the balancing power distribution deviates more and more from the one predicted by the ideal lossless model.

## D. Impact of DC Transmission-Line Distance

605 60

Due to the DC line resistance, terminals which are located further from the point where a change in power injection occurs (i.e., terminal 3 in the test case) observe smaller voltage drop at their DC bus. This describes why the changes in DC bus voltage at terminal 5 have been lowest in all previous cases. To further elaborate on this phenomenon, a similar change of reference (i.e., 250 MW) was tested for various lengths of the DC transmission line between terminals 4 and 5. The droop constant of terminals 1, 2, 4, and 5 was kept as kdkd. The results from the simulations are shown in Table X.

From Table X, it could be observed that the contribution of terminal 5 to DC grid power balancing decreases while the DC transmission distance between terminals 4 and 5 increases (compare the numbers in boldface letters). From this, it could be observed that HVDC terminals respond more strongly to power balancing demands occurring at closer distances than at further locations.

IRJGES | Vol

LUPURAN CHARLES COM | BKERTHAND FRANCIPAL CHAREGE VADAKUCHIPALAYAM KAPPIYAMPULIYUR POST. VILLUPURAM-605 601.

International Research Journal in Global Engineering and Sciences. (IRJGES) ISSN: 2456-172X | Vol. 7, No. 2, June 2021 – August 2021 | Pages 1-10

### VII. CONCLUSION

In this paper, the impact of DC line voltage drops on the distribution of balancing power is thoroughly investigated. It has been demonstrated that the response of each DC terminal to the instantaneous balancing power demand is influenced by several key factors:

1. DC Grid Topology and Line Resistances: The layout and resistances of the DC grid lines play

a crucial role in determining how power flows through the system.

 Location of Power Deficit/Surplus: The location within the DC grid where a power deficit or surplus occurs significantly affects how the system responds and redistributes power.

3. Value of the DC Voltage Droop Constant: The setting of the DC voltage droop constant applied in the DC grid influences the terminal responses and the overall power flow pattern.

Due to these factors, the power flow pattern following a change in injected power at a DC terminal exhibits significant deviations from what is predicted by a simplistic lossless DC grid model.

An analytical expression for accurately estimating terminal power has been proposed in this paper. The validity of this analytical expression has been demonstrated through close agreement between the results obtained using the proposed method and those obtained from dynamic simulations applied to a five-terminal MTDC test model.

By taking into account the complexities introduced by DC line voltage drops, this study provides valuable insights into the behavior of MTDC systems and offers a more accurate tool for analyzing and predicting their performance in practical applications.

### **REFERENCES**

- [1]. Beerten, J., Cole, S., & Belmans, R. (2010). A sequential AC/DC power flow algorithm for networks containing multi-terminal VSC HVDC systems. *Proceedings of the PES General Meeting*, 1–7.
- [2]. da Silva, R., Teodorescu, R., & Rodriguez, P. (2010). Power delivery in MTDC transmission system for offshore wind power applications. *Proceedings of the IEEE PES ISGT Europe*, 1–8.
- [3]. Hendriks, R. L., Paap, G. C., & Kling, W. L. (2007). Control of a multi-terminal VSC transmission scheme for interconnecting offshore wind farms. *Proceedings of the European Wind Energy Conference and Exhibition*, 1–8.
- [4]. Kundur, P. (1994). Power System Stability and Control. McGraw-Hill.
- [5]. Lu, W., & Ooi, B. T. (2005). Premium quality power park based on multi-terminal HVDC. *IEEE Transactions on Power Delivery*, 20(2), 978–983.
- [6]. Lu, W., & Ooi, B.-T. (2002). Multi-terminal HVDC as enabling technology of premium quality power park. *Proceedings of the IEEE PES Winter Meeting*, 719–724.
- [7]. Lu, W., & Ooi, B.-T. (2003). Optimal acquisition and aggregation of offshore wind power by multiterminal voltage-source HVDC. *IEEE Transactions on Power Delivery*, 18(1), 201–206.
- [8]. Nakajima, T., & Irowaka, S. (1999). A control system for HVDC transmission by voltage sourced converters. *Proceedings of the IEEE PES Summer Meeting*, 1113–1119.
- [9]. Xu, L., Williams, B. W., & Yao, L. (2008). Multi-terminal DC transmission systems for connecting large offshore wind farms. *Proceedings of the IEEE PES General Meeting—Conversion and Delivery of Electrical Energy in the 21st Century*, 1–7.

tr

IRJGES | Vol. 6 (2) Transe August 2021 | www.irjges.com | B. Keerthand FROHASS, M.E., Ph.D.,

Dr.R. PANNERING COPA PAGE UDGE

OR. R. ENGINEERING CAYAM.

A.R. ENGINEERING CAYAM.

VADAKUCHIPALAYAM.

VADAKUCHIPALAYAM.

KAPPIYAMPULIYUR 601.

### IJICE – International Journal on Information and Communication Engineering ISSN: 2250-1118 Volumo 9 Issuo 4 2019

July-Aug 2019 Pages 24-30

# An effective GDI (Gate Diffusion Input) Based 16- bit Shift Register Design for Power and Area Optimization

A.Chandrasekaran¹, R.Udhayakumar², Manimegalai³, Indhumathi⁴

1.2.3.4 Assistant Professor

Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram

E-mail:udayalanayaee@gmail.com

Abstract: Sequential circuit design is heavily influenced by power consumption and area reduction. Mainly consisted is shown here. Rather than using flip flops, pulsed latches are used to limit the amount of space these utilize. The shift register uses a minimal number of pulsed clock signals by combining the latches into numerous sub shifter registers and using Multiplexer and additional temporary storage latches. Multiple non-overlap delayed pulsed clock signal schemes are presented for data synchronization in a multi bit shift register to decrease power consumption. In order to maintain the current system, Tanner S- EDIT will be used with Taiwan Semiconductor (TSMC) 0.18mm technology. Designing low-power digital combinational circuits using Gate Diffusion Input(GDI) is a common practice nowadays. When used in particular operating conditions, the GDI approach restores the in-cell swing by implementing sophisticated logic functions on two transistors. This method reduces power consumption, propagation latency, and digital circuit size while maintaining low complexity of logic design. Dual Edge Triggered Flip Flop(DETFF) implementation using GDI technology is introduced as an improvement to the shift register design. This idea also takes into account time restrictions, which can be reduced with the least amount of management.

Keywords: Shift Register, Thermometer Code, Gate Diffusion Input, Dual Edge Triggered Flip-Flop, Propagation latency.

### I. INTRODUCTION

Digital circuits employ a wide range of flip-flops and latches, which have a significant impact on the recycled elemental particles. Today's digital designs incorporate advanced pipelining techniques as well as multiple flip-flops and shift register files that are simple to multiply. A reduction in chip power can be achieved by reducing the clock power used by latches and flip-flops. Other than the D-Flip flop and its variations, such as T-flip flops and JK-flip flops, there are a variety of other, there are slew of new and innovative flip-flop structures to consider. Each of the clock periods two powerful falling edges or rising edges can be triggered by a Single Edge Triggered flip-flop. Due to battery-operated systems' need for low power consumption, high-performance designs with better reliability, custom-sized and low-power configurations have been developed over the past several years. This necessitates designs that use a less amount of electricity while keeping the same level of performance VLSI designers must therefore take



A. Chandrasckaran et.al. & 24

Dr.R.PAN PRINCIPAL AYAM,

A.R.ENGINEERINAL AYAM,

VADAKUCHIPAL AYAM,

KAPPIYAMPULIYUR POST,

KAPPIYAMPULIYUR 605 601.

# IJICE - International Journal on Information and Communication Engineering

ISSN: 2250-1118 Volume 10 Issue 5 2020 Sep-Oct 2020 Pages 34-43

# **GPU-Friendly Steiner-Tree Heuristic To Find A Minimum Cost Tree Spanning A Given Subset**

### P.LAKSHMIDEVI1, N.MUTHU KUMARAN2

Department of Electronics and Communication Engineering, A.R. Engineering College, Villupuram. saranyameece@gmail.com

Rectilinear-Steiner-Minimum-Tree (RSMT) generation is a key step in VLSI routing. This paper describes a deterministic RSMT heuristic named SFP because it is simple, fast, and parallel. It is based on a rapid method for computing the optimal solution for three-pin nets, which it extends and applies to larger nets. Compared to FLUTE, a fast and high-quality RSMT algorithm, SFP incurs a wirelength penalty of 0.38 percent on the 16 ISPD 2008 inputs with 13 million nets. However, on a 16-core 2950X CPU, parallel SFP is 19 times faster than FLUTE, and on a Titan V GPU, it is 86 times faster. Serial SFP can generate an RSMT for a 10,000-pin net in under L5 seconds.

Keywords—GPU acceleration, Parallelism, Routing, RSMT heuristic, Steiner points

### I. INTRODUCTION

Signal routing is an essential step in the physical design of a VLSI chip. Its goal is to determine where to run the wires that connect the logic blocks (e.g., macros, cells, and gates) while keeping certain factors like wirelength, signal-propagation time, and power consumption low. This study focuses on the Rectilinear Steiner-Minimum-Tree generation—i.e., the first step of signal routing that involves minimizing the overall wirelength. The input is the location of the pins of each logic block as well as information about which pins to connect. A set of pins that must be connected is called a net. All nets together are referred to as the netlist.

Panel (a) in Fig. 1 provides an example of a net with three pins that connects the output (P1) of one logic gate to one input each (P2 and P3) of two other logic gates. The three pins can be connected as shown in panel (b) but doing so results in an unnecessarily long wirelength. Panel (c) shows a better solution that is optimal assuming we can only connect pins to pins. This solution can be found by computing the Minimum Spanning Tree (MST) of all possible pin connections. If waypoints, called

Steiner points [15], are allowed, the wirelength can be shortened further as illustrated in panel (d).

Due to manufacturing constraints, only rectilinear (horizontal and vertical) wires are typically allowed. Panels (e) through (h) of Fig. 1 show four possible rectilinear solutions. They are constructed by connecting the pins in P2-P1-P3 order using L-shaped wires with one turn. The solutions in panels (e), (f), and (g) all have the same suboptimal wirelength. The solution in panel (h) containing the Steiner point S is optimal. It is shorter because the part of the two L-wires between P1 and S is shared. In general, the goal of Rectilinear-Steiner-Minimum-Tree (RSMT) generation is to interconnect k pins in a plane using only horizontal and vertical wires such that the total wirelength is minimized.




Fig. 1. Several layouts of a three-pin net (blue dots denote pins, red dots indicate Steiner points, the net is blue, and solid wires are rectilinear)

Finding the set of optimal Steiner points is NP-hard [15]. However, interconnecting given pins and Steiner points can be accomplished by computing an MST, a polynomial-time algorithm, of a complete graph where the vertices are the pins and Steiner points, and the edge weights are the rectilinear distance (Manhattan distance) between the edge's endpoints. Despite the NP-hardness, the optimal solution can often be computed in practice because nets tend to comprise just a few pins. Finding the optimal solution is trivial for two-pin nets and easy for three-pin nets (cf. Section III). Taken together, two- and three-pin nets

This material is based upon work supported by the Defeuse Advanced Research Projects Agency under award number DARPA HR001117S0054. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the Defense Advanced Research Projects Agency.

P. LAKSHMIDEVI, N. MLITHIO KIMARANE STANDER OF REPRING COYAND A.R. ENGINEERING CAYANDAR A.R. ENGINEERING COYANDAR OF GOT.

WAPPLYAMPULIYUR POSTI
WAPPLYAMPULIYUR AM. 605 601.

WAPPLYAMPULIYUR AM. 605 601.



### IJICE - International Journal on Information and Communication Engineering

ISSN: 2250-1118 Volume 10 Issue 5 2020 Sep-Oct 2020 Pages 44-51

### SMART UTILIZATION OF POWER USING NEW BIDIRECTIONAL INTELLIGENT SOLID STATE TRANSFORMER

### D.Sureshkumar, A.Chandrasekaran, R.Udhayakumar, B.Keerthana Assistant Professor

Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram E-mail:Ramamoorthy2610@gmail.com

Abstract -This project proposes a smart grid application system using new bidirectional intelligent semiconductor transformer (BIST) With frequency range in terms of KHZ in which the magnitude and frequency of the operation voltage are various and high-quality power is required.lt provides bidirectional power flow and hybrid switching using MOSFET and IGBT. The system comprises of highvoltage part and low-voltage part .The highvoltage part is composed of several halfbridge ac/dc converters connected in series through high-frequency transformers to cope with high input voltage. While the low-voltage part is composed bidirectional half-bridge dc/dc converter and dc/ac **PWM** inverter. In prototype BIST, the input voltage on the high-voltage side is 1900 V and the output voltage on the low-voltage side is the intermediate 180V, and DC-DC converter component output is found to be 1000V with improved power factor correction and compensation of sag and swell respectively so that the efficiency is improved and it posses small

light weight, with realization of three phase structure on a single module . This can be analysed MATLAB simulation.

### LINTRODUCTION

By using conventional transformer we can only step up or step down the voltage and it will not overcome the power quality problems.so it is not fit for smart grid applications, since in case of smart grid frequency mismatch is a major problem while connecting various renewable resources. so for this purposes, BIST(Bidirectional Intelligent Solid state Transformer is used widely in railway stations and substations since it provides light weight. This single phase BIST is used in case of distribution automation.BIST operates at much higher frequency in terms of KHZ since it distributes DC power as well as AC power with compensation of sag, swell and harmonics and such that it can be implemented for smart grid which is also termed as Microgrid.In some bidirectional power flow can be achieved but power factor is not been controlled.In some other cases voltage sag and swell can

44



D.Sureshkumar erral. T. THINKE ENDINE OULLEGE

A.R. ENGINEERING VADAXUCHIPALAYAM KAPPIYAMPULIYUR POST, VILLUPURAM-605 601.

# IJICE – International Journal on Information and Communication Engineering, 2018 ISSN: 2250-1118 Volume 12 Issue 2, 2022

Mar-Apr 2022 Pages 40-51

# **Intrusion Detection Systems to Secure IoT Networks**

Saravanan.P, Nisha.R, Savitha.N, Saranaya.R, Muthuarasan.R

Assistant Professor

Department Of Electronics and Communication Engineering,

A.R Engineering College, Villupuram

E-mail:saravanankarunika@gmail.com

Abstract – The Internet of Things (IoT) and its rapid advancements will lead to everything being connected in the near future. The number of devices connected to the global network is increasing every day. IoT security challenges arise as a result of the large-scale incorporation of smart devices. Security issues on the Internet of Things have been the most focused area of research over the last decade. As IoT devices have less memory, processing capacity, and power consumption, the traditional security mechanisms are not suitable for IoT. A security mechanism called an Intrusion Detection System (IDS) has a crucial role in protecting the IoT nodes and networks. The lightweight nature of IoT nodes should be considered while designing IDS for the IoT. In this paper, the types of IDS, the major attacks on IoT, the recent research, and contributions to IDS in IoT networks are discussed, and an analytical survey is given based on the study. Though it is a promising area for research, IDS still needs further refinement to ensure high security for IoT networks and devices. Hence, further research, development, and lightweight mechanisms are required for IDS to provide a higher level of security to the resource-limited IoT network.

Index Terms - Attack, IoT, Intrusion, IDS, RPL, Security.

### I. INTRODUCTION

The Internet of Things (IoT) is a robustly evolving trend that incorporates technical, scientific, social, and economic implications. It is essential to all facets of human life [1]. Healthcare, logistics, smart-cities, smart-homes, and agriculture are just a few of the applications for IoT. Due to its resource-constrained characteristics, the IoT tends to have more vulnerability that can be easily exploited by an attacker. The number of connected unsecured IoT devices on the global network is rapidly increasing [2]. Researchers are mainly focusing on various encryption and authentication mechanisms to ensure data confidentiality, authentication, and privacy among users and things. Most of the IoT devices have been developed without considering the fundamental security requirements [3].

The tools and techniques available for securing the IoT are inadequate because of the large number of interconnected devices. Moreover, the security mechanisms based on cryptography are mainly used to prevent external attacks such as eavesdropping and message alternation. When the cryptographic techniques hold the valid key and are compromised by the attack, they cannot detect the vulnerable nodes. Intruders can easily access the security details from the compromised nodes and immediately launch several internal attacks. Hence, to offer an extra level of security to the IoT, the Intrusion Detection System (IDS) acts as a tool [4].

Anthea Mayzaud et al. [5] categorized the Routing Protocol for Low Power Lossy Networks (RPL) attacks into

Saravanan.P ET.AL.



Dr.R.PANNEEROHASS, M.E., Ph.O.

Dr.R.PANNEEROHASS, M.E., Ph.O.

PRINCIPAL
COLLEGE
PRINCIPAL
COLLEGE
PRINCIPAL
A.R.ENGINEERING
VADAKUCHIPALAYAM
VADAKUCHIPALAYAM
KAPPIYAMPULIYUR
VILLUPURAM-605 601.



### International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal Established in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NIT, Trichy, Journal Indexed in JIR, DIIF and SJIF.

Available online at: www.jrrset.com

ISSN == : 2347-6729 ISSN (Creline): 2348-3105

Volume 8, Issue 1 January 2020. JIR IF: 2.54

SJIF IF: 4.334 Cosmos: 5.395

Received on: 04.12.2019 Published on: 21.01.2020 Pages: 83-89

# Highly Solar active green oxidant combined W, N Co-doped ZnO powder: Synthesis Characterization and Photo catalytic Degeneration of textile Dye

Thamizhselvi D, Revathi A, Vasanthi M, Ramya K

Department of Science and Humanities, A.R. Engineering College, Vadakuchipalayam, Villupuram-605601, Tamil Nadu. \*Corresponding Author: E-Mail: thamizhkymari2020@gmail.com

Abstract: The photocatalytic degradation of Reactive Blue 4 (RB 4) under solar irradiation was investigated using W, N co-doped ZnO. Various mole ratios (0.02 mol%, 0.03 mol%, 0.04 mol%, 0.05 mol%, and 0.06 mol%) of W, N co-doped ZnO photocatalysts were prepared via the sol-gel technique. Pure ZnO exhibited low photocatalytic activity due to poor surface properties, photo-corrosion, and limited utilization of visible light. These drawbacks were mitigated by doping ZnO with W, N. The photocatalytic activity of W, N co-doped ZnO significantly surpassed that of pure ZnO. XRD, SEM, UV-DRS, PL, and FTIRB analyses confirmed the enhanced photocatalytic properties of W, N co-doped ZnO. Furthermore, W, N co-doped ZnO exhibited photostability and long-term durability.

Keywords: W, N Codoped ZnO, Sol-gel route, photocatalytic degradation, Reactive Blue 4, solar light

The last centuries have seen a steady increase in human activities, causing remarkable technological development and soaring human populations. However, the industrial expansion has brought atmospheric, ground, and water pollution, all harmful to humans and the environment. Indeed, major pollution can cause human diseases like breathing problems, cardiovascular problems, cancers, neurobehavioral disorders, etc. It can also affect global warming, which worsens climate change, increases sea level rises, and causes serious

Among the water pollutants, synthetic dyes pose significant issues. Synthetic dyes are commonly used by various industries, especially textile ones. These physically and chemically stable compounds are harmful to the environment. Synthetic dyes are recalcitrant compounds that exhibit high solubility in water and accumulate in both wastewater and industrial effluents. Consequently, the recovery of wastewater by conventional methods is not suitable for emergent pollutants. Heterogeneous photocatalysis can be satisfactorily applied for the decontamination of natural samples through the photocatalytic degradation of toxic pollutants from complex matrices, such as river water and wastewater. All renewable technologies have become a promising alternative for both energy generation and wastewater treatments. Solar photocatalysis is a suitable option to degrade

The absorption of a photon initiates the photodecomposition of a semiconductor with energy greater than or equal to the bandgap of the semiconductor, producing electron-hole pairs. It is important for prolonging electron-hole recombination before a designated chemical reaction occurs on the semiconductor surface. Several semiconductor photocatalysts such as TiO<sub>2</sub>, ZnO, WO<sub>3</sub>, SnO<sub>2</sub>, CdS, and ZnS have been used for the Several semiconductor photosens under visible light irradiation. Among semiconductors, zinc oxide (ZnO) has treatment of wastewater pollutants under visible light irradiation.

Thamizhselvi D. Revathi A. Vasanthi M., Ramya K

LLUPURAL 605 601

Dr.R.PANNERONHASS, ME.PhO.,
PRINCIPAL CO. PARE 83
A.R. ENGINEERING CO. PARE 83 WARPOYAMPULLY ENE ENT. WILLUPURAM-605 601.



### International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal I stablished in early 2000 as National Journal and appraised to International Journal in 13 and is in existence for the last 10 years. It is run for Bette of Paulicones from SIL Friches Journal Indexed in JIR, DHF and SJIF.

Available online at: www.jifigt.com ISSN one : 2347-6729 ISSN one : 2348-3105

JIR IF: 2.54 SJIF IF: 4.334 Cosmos: 5.395

Volume 10 Issue 12 - December 2022 - Pages 29-49

### Investigation of Properties and Dynamics Mechanical Analysis of Glass fiber / Human hair / Coir fiber reinforced epoxy polymer Hybrid Composites

Panneerdhass R\*, Kamalbabu K, Anbazhalagan R, Ramamoorthy S

Professor, Department of Mechanical Engineering, A.R Engineering College, Villupuram, Tamilnadu-605601, India.

E-mail: panneerdhass@gmail.com

#### **ABSTRACT**

This paper presents the study of the mechanical and water absorption characteristics of the Glass fiber / Human hair / Coir fiber reinforced epoxy polymer composites. G-H-C-G, C-H-G-C, and H-C-G-H reinforced epoxy resin matrix composites have been developed by hand lay-up technique with varying process parameters such as fiber condition. Tensile strength various from 42 Mpa to 56 Mpa, Tensile modulus varies from 48 GPa to 52 GPa, flexural strength varies from 46 MPa to 52 MPa, flexural modulus varies from 42 Gpa to 50 Gpa, shear study and fracture study was carried out. Effects of central open hole on the tensile strengths of the composites were studied by five sets of tensile specimens containing central open holes of five different diameters. Dynamic mechanical analyzer (DMA) was used to examine the dynamic mechanical properties of composite laminates with increasing temperature. The optimum mechanical properties were obtained in the treated fiber composite. Results showed that the composite sample, which has human fabric at the outer layers, has the highest storage and loss modulus. Besides, it was observed that glass transition temperature (Tg) of samples are close to each other and at about 75 °C. The fracture surface of the composite shows that pull out and de bonding of fiber is occurred.

Keywords: Glass fiber / Human hair / Coir fiber fiber hybrid, mechanical, open hole, DMA, SEM.

### INTRODUCTION:

Natural fibers are derived from plants, animals and mineral sources. In modern days, the natural fibers from plants like sisal, banana and jute mixed with the glass fiber are used to get high strength (HS) hybrid composite materials which are widely used in many applications. High strength composite materials are replacing the metallic materials when used in the aerospace, structural and automobile industries.

Hybrid laminates exhibited superior dynamic mechanical performance, even compared to the pure glass laminate. Lower tan delta peak height (related to better fiber-matrix interaction) values and higher Tg were reported for the [C/G/G]s and [G/C/C]s samples which, together with the [G/C/G]s sample, exhibited the best results for reinforcement effectiveness and loss modulus peak height [1]. Polyester based hybrid composites are prepared by Hand lay-up technique followed by static

Panneerdhass R et .. al.



Dr.R.PANNEERDHASSME.Ph.D.

Dr.R.PANNEERDHASSME.Ph.D.

PRINCIPAL COLLEGE

PRINCIPAL COLLEGE

PRINCIPAL COLLEGE

PRINCIPAL COLLEGE

A.R.ENGINEERING CAYAM.

VADAKUCHIPALAYAM.

KAPPIYAMPULIYUR

KAP



### International Journal on Recent Researches in Science, Engineering & Technology (LJRRSET)

A Journal I stablished in early 2000 as National journal and upgraded to International journal 603 and is in existence for the last 10 years. It is run by Retired Professors from NIT, Tricky, Journal Indianal Still.

Available online at: www.preet cold.

ISSN - 2347-6729 ISSN - 2348-3105

JIR IF: 2.54 SJIF IF: 4.334 Cosmos: 5.395

Volume 10 Issue 10 - October 2022 - Pages 65-75

### A REVIEW ON BIO COMPOSITE MATERIALS

R.Panneerdhass\*, S.Ramamoorthy, D.Manikandan, M.Jayaprabhabanc Professor\* & Assistant Professor

Department Of Mechanical Engineering, A.R Engineering College, Villupuram E-mail:panneerdhass@gmail.com

#### ABSTRACT:

Bio composites are natural fiber reinforced biopolymers, due to their excellent properties and less weight, Composite materials are considered as a significant part of our day to day life. Bio composites are fabricated by combining natural fibers in a matrix material. The matrix material can be biodegradable, non-biodegradable, or synthetic. Synthetic matrix materials, along with natural fibers, are used to form hybrid bio-composites. Naturals fibers are abundant and have low harvesting costs with adequate mechanical properties, eco-friendly nature and sustainability, so the natural fibers are getting attention from researchers and academician. This review article provides a review of the widely used natural fiber reinforced polymer composites and their applications. Drawbacks of natural fiber composites such as higher water absorption, low fire resistance, and mechanical properties limited its application also the applications of natural bio composites in automobile, construction, marine, aerospace industry are discussed.

Keywords: Bio-composites, Synthetic matrix, Naturals fibers.

### 1.INTRODUCTION:

A bio composite material is a combination of matrices such as polymer and reinforced natural fibers. These composites mimic the morphology of the living materials with excellent biocompatibility. The polymer matrix protects the fibers from mechanical damage and environmental degradation. Moreover, bio fibers are natural fibers produced from biological origins such as wood, crops, and regenerated cellulose. Bio composites enhance the safety in their production.

### 2.BIO COMPOSITE CONSTITUENTS:

ILLUPURAM 605 601

The term 'bio-composites' for the most part covers composite materials where in any event one segment ought to be bio-based:

R.Panneerdhass et.al.

Dr.R.PANNEEROHASSME.Pho.,
PRINCIPAL COLLEGE
PRINCIPAL COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
VAPRIYAMPULIYUR
VILLUPURAM, 605 601.



### International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

ournal I stablished in each 2000 as National journal and upgraded to International journal in and is in existence for the last 19 years. It is run by Retired Professors from S11, Tricky, Journal Indexed in JIR, DHI and SHF.

Available on these of the professors from S11, Tricky, Journal ISSN rose 2347-6729 ISSN rose 2348-3105

JIR IF (2.54 SJIF II') 4.334 Cosmos: 5.395

Available online at: www.mpet.com

Volume 11 Issue 3 – March 2023 - Pages 49-58

# EXPERIMENTAL BEHAVIOR OF FIBER REINFORCED CONCRETE USING RECYCLED AGGREGATE WITH AGRO-WASTE REPLACEMENT

Email:veensann@gmail.com

A.Vinoth, S.Kavari, S.Sugunya, D.Thulabamani
Assistant Professor
Department of Civil Engineering, A.R Engineering College, Villupuram

ABSTRACT:

Utilization of industrial waste materials in concrete compensates the lack of natural resources, solving the disposal problem of waste and to find alternative technique to safeguard the nature. There are a number of agro wastes used as fully or partial replacement of coarse aggregates or fine aggregates. This review carries out a assessment about agro waste substances, which can be adequately utilized in concrete as fine aggregate substitution. This paper reviewed some of these materials like fiber reinforced concrete, recycled aggregates, groundnut shell, superplasticizers are the replacement in concrete. Different physical and mechanical properties of recycled fine aggregates and recycled coarse aggregates as well as agro waste materials has been substituted and it has been reviewed and comparisons are made between them. Deflection and leaching study review are carried out additionally and compared. It can observed that the concrete where river sand is replaced by M - sand and natural aggregates is replaced aggregates which exhibits improved strength and durability properties, but it's slump increases as the rate of replacement increase in the case of superplasticizers and the slump decreases in the case of superplasticizers. There is a less research work reported on agro waste ad groundnut shell, so it is felt that further detailed investigation are required. ready mix concrete each year. It is used in highways, big apartments, bridges, dams, and numerous other applications. Sand is used as fine aggregate in mortars and concrete. Natural river sand is the most preferred choice as the fine aggregate materials.

River sand is a product of natural weathering of rocks over a period of millions of years. It is mined from the river beds and sand mining has disastrous environmental consequences. River sand is becoming a scarce commodity and hence exploring alternatives to it has become imminent. Fiber Reinforced Concrete, Groundnut shell powder, Recycled Coarse aggregates are the alternative materials is used.

Concrete is a mixture comprised of cement (10-15 percent), coarse and fine aggregates (60-75 percent) and water (15-20 percent) by volume. Fiber Reinforced Concrete, Groundnut

A.Vinoth et.al.



Or.R.PANNEEROHASS M.E.Ph.D.,
PRINCIPAL COLLEGE
PRINCIPAL COLLEGE
PRINCIPAL AVAM.
PRINCIPAL AVAM.
A.R.ENGINEERING AVAM.
VADAKUCHIPALAV.
KAPRIYAMPULIYUR POST.
KAPRIYAMPULIYUR SOS 601.

### INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 4 Issue 3, October – Dec. 2018 - www.ijrmmae.in – Pages 84-96

# DESIGN AND ANALYSIS OF KNUCKLE JOINT USING FEA SOFTWARE

S.Ramamoorthy, K.Sakthivel, K.Sivasubramaniyan, D.Manikandan Assistant Professor

Department Of Mechanical Engineering, A.R Engineering College, Villupuram Email:Ramamoorthy2610@gmail.com

### ABSTRACT:

Knuckle joint is a joint between two parts allowing movement in one plane only. It is a kind of hinged joint between two rods, often like a ball and socket joint. Knuckle joints are most common in steering and drive train applications where it needs to move something but also need to allow for offset angles. The main aim of this project work is to study and calculate the maximum stresses induced in Knuckle joint, The load carrying capacity is considerably very low in mild steel pin. So we can also use high strength, high modulus molybdenum pin that can augment the capacity to withstand higher loads. The knuckle joint is proposed to develop in this study for an applied force of 150 KN. The diameter of the pin is planned, expected to be 24 mm. The material of the knuckle joint is considered as molybdenum material, in order to do the stress analysis the knuckle joint is designed using CATIA software and the mesh was developed for the same using ANSYS software. Based on the analytical calculations and ANSYS result, it shows that a pin of 24mm diameter can resist a load of 150 KN.

### I) INTRODUCTION:

A knuckle joint is used when two or more rods subjected to tensile and compressive forces are fastened together such that their axes are not in alignment but meet in a point. Knuckle joint is a joint between two parts allowing movement in one plane only. It is a kind of hinged joint between two rods, often like a ball and socket joint. There are many situations where two parts of machines are required to be restrained, for example two rods may be joined coaxially and when these rods are pulled apart they should not separate i.e. should not have relative motion and continue to transmit force. Similarly if a cylindrical part is fitted on another cylinder (the internal surface of one contacting the external surface of the other) then there should be no slip along the circle of contact. Such situations of no slip or no displacements are achieved through placing a third part or two parts at the jointing regions. A knuckle joint is understood to be a hinged joint in which projection in one part enters the recess of the other part and two are held together by passing a pin through coaxial holes in two cylindrical parts should not have relative motion and continue to transmit force. NEEROHASS, M.E. Ph.D.

Ramamoorthy, K.Sakthivel, K.Sivasubramaniyan, D.Manikandao PA

605 601

VILLUPURAM.605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING(IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 4 Issue 3, October – Dec. 2018 - www.ijrmmae.in – Pages 97-106

# EXPERIMENTAL BEHAVIOR OF FIBER REINFORCED CONCRETE USING RECYCLED AGGREGATE WITH AGRO-WASTE REPLACEMENT

R.Saranraj, B.Anandhakumar, Pavithra, S.Sugunya
Assistant Professor
Department Of civil Engineering, A.R Engineering College, Villupuram
Email:veensann@gmail.com

### ABSTRACT:

Utilization of industrial waste materials in concrete compensates the lack of natural resources, solving the disposal problem of waste and to find alternative technique to safeguard the nature. There are a number of agro wastes used as fully or partial replacement of coarse aggregates or fine aggregates. This review carries out a assessment about agro waste substances, which can be adequately utilized in concrete as fine aggregate substitution. This paper reviewed some of these materials like fiber reinforced concrete, recycled aggregates, groundnut shell, super plasticizers are the replacement in concrete. Different physical and mechanical properties of recycled fine aggregates and recycled coarse aggregates as well as agro waste materials has been substituted and it has been reviewed and comparisons are made between them. Deflection and leaching study review are carried out additionally and compared. It can observed that the concrete where river sand is replaced by M - sand and natural aggregates is replaced aggregates which exhibits improved strength and durability properties, but it's slump increases as the rate of replacement increase in the case of superplasticizers and the slump decreases in the case of superplasticizers. There is a less research work reported on agro waste ad groundnut shell, so it is felt that further detailed investigation are required. ready mix concrete each year. It is used in highways, big apartments, bridges, dams, and numerous other applications. Sand is used as fine aggregate in mortars and concrete. Natural river sand is the most preferred choice as the fine aggregate materials.

River sand is a product of natural weathering of rocks over a period of millions of years. It is mined from the river beds and sand mining has disastrous environmental consequences. River sand is becoming a scarce commodity and hence exploring alternatives to it has become imminent. Fiber Reinforced Concrete, Groundnut shell powder, Recycled Coarse aggregates are the alternative materials is used.

R.Saranraj, B.Anandhakumar, Pavithra, S.Sugunya

609 601

Dr.R.PANNEER CHASS, M.E.PhD.,
PRINCERING POST,
A.R.ENGINEERING ALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
KAPPIYAMPULIYUR AM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 4 Issue 4 – www.ijrmmae.in – Pages 61-80

# INVESTIGATION OF PROPERTIES AND MACHINABILITY OF LUFFA WITH GROUNDNUT SHELL FIBER REINFORCED EPOXY POLYMER HYBRID COMPOSITES

Panneerdhass R\*, Manikandan D, Sivasubramaniyan K, Jayakumar R
Professor\* & Assistant Professor, Department of Mechanical Engineering, A.R Engineering College,
Villupuram-605601, India.

Email: panneerdhass@gmail.com

### **ABSTRACT**

This paper presents the study of the mechanical, thermal properties and water absorption characteristics of the luffa with ground nut fiber reinforced epoxy polymer composites. luffa with ground nut fiber reinforced epoxy resin matrix composites have been developed by hand lay-up technique with varying process parameters such as fiber condition (treated, untreated), chopped randomly oriented and different volume fraction (30%, 40% and 50%). Tensile strength various from 18 Mpa to 23.5 Mpa, compressive strength varies from 41.5 MPa to 56.2 MPa, flexural strength varies from 61.22 MPa to 73.6 MPa and impact energy varies from 1.1 Joules to 1.6 Joules, as a function of fiber volume fraction. Effects of central open hole on the tensile and impact strengths of the composites were studied by five sets of tensile specimens containing central open holes of five different diameters. The machinability study was performed by drilling experiments using a CNC drilling machine with drill tool dynamometer. Two input parameters, cutting speed and feed rate and the one output parameter, thrust force, were used for the drilling process. The optimum mechanical properties were obtained in 40% of fiber volume fraction of the treated fiber composite. The fracture surface of the composite shows that pull out and de bonding of fiber is occurred.

Keywords: luffa / ground nut fiber hybrid, mechanical and thermal properties, open hole, machinability,

### 1. INTRODUCTION

Synthetic fiber reinforced composites are being widely used in polymer composites because of their high stiffness and strength properties. The natural fibers such as jute, ramie, sisal, coir, pineapple leaf, and kenaf have the potential to be used as a replacement for glass or other traditional reinforcement materials in composites. These fibers are abundant, cheap and renewable. Martinez-Lopez et al., aims to study the Polymer Concrete were reinforced with Loofah fibers in order to improve the compressive and flexural

Panneerdhass R\*, Manikandan D, Sivasubramaniyan K, Jayakumar R



Dr.R.PANNEEROHASENEERO Dr.R.PANNEEROHAL COLLEGE Dr.R.PANNEERING COLLEGE PRINCIPAL COLLEGE PRINCIPAL COLLEGE PRINCIPAL COLLEGE PRINCIPAL COLLEGE A.R. ENGINEERING AN. 605 601. KAPPIYAMPURAM. 605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 6 Issue 1, April-June. 2020 - www.ijrmmae.in – Pages 77-95

# CHARACTERIZATION ANALYSIS ON ALGAE METHYL ESTER (AME) BIODIESEL INJECTED IN AUTOMOTIVE CI ENGINE

K.Sakthivel<sup>1</sup>, S.Ramamoorthy<sup>2</sup>, R.Panncerdhass<sup>3</sup>, R.Manivanan<sup>4</sup>
Assistant Professor<sup>1,2,4</sup> & Professor<sup>3</sup>
Department Of Mechanical Engineering, A.R Engineering College, Villupuram
E-mail:Sakthi.2678@ @gmail.com

### ABSTRACT

Biodiesel is derived primarily from the base catalytic trans-etherification reaction of oils or fats and lipids. Biodiesel has become highly attractive due to its biodegradable, renewable, and non-toxic nature. Currently, biodiesel is being promoted by researchers as an alternative fuel. Biodiesel quality analysis is important because consistency and high quality are critical to the success of its commercialization and market acceptance. Appropriate and accurate analysis methods are needed to meet this requirement. Some analytical techniques, such as high-performance liquid chromatography (HPLC), infrared spectroscopy (IR), CHN analysis and physical properties are considered and used in algae methyl ester (AME) biodiesel analysis. In the spectroscopic technique, the infrared spectrum plays an important role. This experimental study is focused on performance, emission and combustion characteristics of CRDI automotive diesel engine developments in biodiesel quality analysis with appropriate spectroscopy techniques. The use of biodiesel has been found to lower air pollutant and greenhouse gas emissions, but can be potentially harmful to the engines if it contains impurities. This paper proposes a method using high-performance liquid chromatography to test the quality of biodiesel. This method can also be used to optimize the procedure used to make the biodiesel. An optimized production procedure and a test method to assess the final product will ensure high quality fuel that can be used with confidence in diesel engines. This will likely add strength to proposals to increase the use of the on-campus reactor and produce biodiesel for campus grounds equipment from waste vegetable oil. In a results of CRDI engine based on performance biodiesel blend B60 and B80 shows higher brake thermal efficiency, based on emission HC and NO are lower in blend of B60 and B20.

K.Sakthivel<sup>1</sup>, S.Ramamoorthy<sup>2</sup>, R.Panneerdhass<sup>3</sup>, R.Manivanan<sup>4</sup>

GOS 601

A.R. ENGINE PARRY DUR POST A.R. ENGINE PARRY DUR POST VADAKUMPULIYUR 605 601. KAPPIYAMPURAM.605 KAPPIYAMPURAM.605

### INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING(IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 7 Issue 2, July - Sep. 2021 - www.ijrmmae.in - Pages 50-56

# KINETIC STUDY ON THE EFFECT OF WATER HYACINTHS IN FOODWASTE BIOGAS PRODUCTION

J.Jayakodi, A.Vinoth, K.Saranya, S.Sugunya Assistant Professor Department Of civil Engineering, A.R Engineering College, Villupuram Email:kavivacivil03010@gmail.com

### ABSTRACT:

Due to rapid growth of population and industrial globalization day to day energy demand increases and has an adverse effect on the fossil fuel depletion. This is the major problem accounted for the present and future economy. So in order to reduce our energy demands, there should be a need of distinguishing new concepts on renewable energy source because they are ecofriendly in nature. In the present paper, kinetics study on the effect of water hyacinths in food waste biogas production was carried out. The experiments consists of bio digester setup of 75litres capacity with 10% solid concentration at mesophilic temperature range of 35°C and 20days retention times and by using modified Gompertz equation kinetics were determined for each bio digester. The kinetic parameters are Biogas yield potential (P), Maximum biogas production rate (Rm) and the Duration of lag phase (λ) were estimated for each bio digester. In the experiments cow manure is used as the inoculums and food waste is added daily .The results show that the mixture of water hyacinths and food waste will enhancing the biogas productions of about 1.2% when compared with food waste substrate sands:

Keywords: Anaerobic Digestion (AD), Food waste (FW), Cow Manure (CM), Water Hyacinths (WH). Hydraulic Retention Time (HRT)

J.Jayakodi, A.Vinoth, K.Saranya, S.Sughpray C.PAL COLLEGE Dr.R. Dr.R. P. Sughpray R. R. ENGINEERING A.A. P.O.S. A.R. ENGINEERING ALAY POST. VILLUPURAM-605 601.



## INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING(IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online) Volume 7 Issue 2, July – Sep. 2021 - www.ljrmmae.in – Pages 50-56

# KINETIC STUDY ON THE EFFECT OF WATER HYACINTHS IN FOODWASTE BIOGAS PRODUCTION

J.Jayakodi, A.Vinoth, K.Saranya, S.Sugunya **Assistant Professor** Department Of civil Engineering, A.R Engineering College, Villupuram Email:kaviyacivil03010@gmail.com

### **ABSTRACT:**

Due to rapid growth of population and industrial globalization day to day energy demand increases and has an adverse effect on the fossil fuel depletion. This is the major problem accounted for the present and future economy. So in order to reduce our energy demands, there should be a need of distinguishing new concepts on renewable energy source because they are ecofriendly in nature. In the present paper, kinetics study on the effect of water hyacinths in food waste biogas production was carried out. The experiments consists of bio digester setup of 75litres capacity with 10% solid concentration at mesophilic temperature range of 35°C and 20days retention times and by using modified Gompertz equation kinetics were determined for each bio digester. The kinetic parameters are Biogas yield potential (P), Maximum biogas production rate (Rm) and the Duration of lag phase (λ) were estimated for each bio digester. In the experiments cow manure is used as the inoculums and food waste is added daily .The results show that the mixture of water hyacinths and food waste will enhancing the biogas productions of about 1.2% when compared with food waste substrate alone.

Keywords: Anaerobic Digestion (AD), Food waste (FW), Cow Manure (CM), Water Hyacinths (WH), Hydraulic Retention Time (HRT)



R.PANNEEROHASS,ME.Pho. KAPPIYAMPULIYUR POST. J.Jayakodi, A.Vinoth, K.Saranya, S.Sugun VILLUPURAM-605 601.

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAE)

ISSN: 2454-1435 (Print) | 2454-1443 (online)

Volume 7 Issue 2, July - Sep. 2021 - www.ijrmmae.in - Pages 57-62

# ASSESSMENT OF OPEN CENTRAL HOLE ON THE STRESS CONCENTRATION FACTOR OF GLASS FIBRE-COCONUT COIR-HUMAN HAIR HYBRID COMPOSITE

R.Panneerdhass\*, S.Ramamoorthy, D.Manikandan, R.Manivanan Professor\* & Assistant Professor Department Of Mechanical Engineering, A.R Engineering College, Villupuram E-mail:panneerdhass@gmail.com

### **ABSTRACT**

The recent research attempts in polymer composites are indicative of a shift of choice to synthetic fillers from natural fillers as the low eco-compatibility of the former is posing serious environmental hazards. Anyhow, the comparatively lower mechanical properties of the natural fibre reinforced polymer composites have restricted their entry into many sectors. A complementary measure by presenting a combination of natural and synthetic fibres in the polymer matrix can achieve a good balance between the degradability and performance of the material. In the recent past, a few research attempts were made on the feasibility of hybridization using selected natural and synthetic fillers.

Most of the assembling operations of fibre reinforced plastic sheets involve a number of riveted joints which require the presence of holes which naturally give rise to zones of stress concentration. This factor has made the analysis of open hole behaviour of these laminate composites, a crucial step in defining their suitability for applications.

The open hole mechanical properties of human hair-coconut coir-glass fibre-human hair hybrid composite (HCGHRP) are studied in this paper. The composite samples were prepared by hand lay-up. Eight sets of tensile and impact specimens with each set comprising of specimens with centrally drilled holes of a particular diameter were prepared and the experimental tensile and impact values were recorded. Additionally, Whitney Nusimer point stress model was validated for these values. The stress distribution in the open hole specimens were studied by Finite Element Method. In all these Increase in hole diameter was found to cause an increase in hole sensitivity. The finite element analysis of the loaded

specimens indicated a much higher concentration of load in the regions surrounding the hole.

Keywords: Stress concentration factor, open central hole, glass fibre, human hair

#### INTRODUCTION

Green environment campaign has forced the researcher to change their approach in polymer composites reinforcement material from synthetic fillers to natural fillers to enhance polymer composites properties. The key is a low ecocompatibility of the synthetic fillers is posing serious environmental hazards. Since comparatively lower mechanical properties of the natural fibre reinforced polymer composites as restricted their entry into many sectors. A complementary measure has been taken by presenting a combination of natural and synthetic fibres in the polymer matrix can achieve a good balance between the degradability and performance of the material. In the recent past, a few research attempts were made on the feasibility of hybridization using natural and synthetic fillers. Raghavendra et al., studied an effect of hybrid combination of jute and glass fibres in epoxy matrix. They reported that composite with glass fiber showed tensile strength of 78MPa and this value was approximately equal to the average of the tensile strength of the composites reinforced by jute and glass fibres. Hazizan et al., investigated on the mechanical behavior of pultruded jute/glass fibre composites which shows much higher mechanical properties. Atiqah at al., have been investigated mechanical properties of kenaf and glass fibres reinforced in epoxy and unsaturated polyester. This combination has produced good mechanical properties in case of epoxy, but unsaturated polyester composite showed no

VILLUPURAM EN 605 601 CO

DI.R. PANNEEROHASS. MERING PANNEEROHASS. MERING PANNEEROHASS. A.R. ENGINEEROHALAYAMA. A.R. ENGINEEROHA. A.R. ENGINEEROHA

# INTERNATIONAL JOURNAL OF RESEARCH IN MECHANICAL, MECHATRONICS AND AUTOMOBILE ENGINEERING (IJRMMAZ)

INSN: 2454-1435 (Print) | 2454-1443 (online) Volume 7 Issue 4, Jan-March, 2022- www.ijrmmae.in — Pages 1-6

# TWO-WHEELER DESIGN AND FABRICATION TO PREVENT TRIBLE RIDERS AND ACCIDENTS

N.Savitha', Sarayanan.P, Nisha.R, Muthukumaran.N

Assistant professor, Department of RCB, A.R. Engineering, College, Villaparam,
\*Corresponding author
vasanthisavi@gmail.com

### Abstract

Road site visitor accidents (RTAs) are becoming a critical public health issue that require a multidisciplinary response. In countries like India, the trend of RTA accidents and deaths is becoming concerning. The approach used to enforce the laws and regulations available to stop traffic accidents is frequently unsuccessful. The majority of bike accidents are caused by more than two riders who are not wearing safety helmets. These incidents can be prevented by designing bikes with smart device integration. We provide a bike with an integrated helmet detector, a piezoelectric sensor, a load phone device, and an electricity-generating gadget. The number of rides on the two-wheeler is realized using a load movable system and a piezoelectric sensor, which can assist prevent triple riders. Helmet detector; employing a Raspberry Pi 3, it can identify individuals who wear helmets or not. These ingenious bike safety measures will lower bike accidents. Furthermore, power is generated via thermoelectric conversion, which operates on the Peltier effect principle.

Keywords—smart blke, blke inbuilt helmate detector, avoiding triple riders, power generation system replacing dynamometer

### 1. INTRODUCTION

Mostly the usage of 4 wheelers is extensively decreased than the two wheelers. Which means usage of two wheelers by way of the society had extended more? Riding on two wheelers with over load, more than two members on bike and not wearing the helmet humans are regularly located on India. This a essential trouble that leads to unexpected and tremendous accidents. To reduce the probability of accident the format

and implementation of clever bikes with clever units have been preceded.

The World Health Organization (WHO) reports, India is susceptible for street accidents and most of the instances are of two wheeler accidents. From the latest surveys in India 4 individuals are loss of life for each and every one hour due to no longer wearing helmet and additionally many accidents are taking place due to more than 2 riders on bike. On the basis of these troubles we added a device which is to

N.Savitha\*, Saravanan.P, Nisha.R, Muthukumacah.





# International Research Journal in Global Engineering and Sciences. (IRJGES)

ISSN: 2456-172X | Vol. 4, No. 3, SEP-NOV 2021

Pages 163-171 | Cosmos Impact Factor (Germany): 5.195

Received: 02.09.2019 Published: 28.11.2019

# Development of Smart Control System for Improved Energy Management in Building

A.Chandrasekaran, R.Udhayakumar, Manimegalai, Indhumathi Assistant Professor

Department of Electrical & Electronics Engineering, A.R Engineering College, Villupuram E-mail:udayalanayaeee@gmail.com

### Abstract:

The advancement of technology has led to a rapid increase in modern appliances, transitioning from time-consuming manual processes to advanced smart control systems. However, many circuits, especially power supply circuitry, utilize inductors and transformers that draw higher currents than specified by manufacturers. Oversizing or undersizing these components can lead to adverse effects such as fire outbreaks or reduced equipment lifespan, ultimately costing more to replace. In response, this research proposes a smart control system to monitor, regulate, and balance energy demand and supply, employing load shedding in critical situations based on priority scheduling. The system, designed using Arduino IDE software for monitoring and decision-making, and simulated using Proteus software with the Senate building in FUTO as a case study, aims to optimize energy consumption and conserve usage. A hardware prototype validates the system, demonstrating proposed control organized shedding during peak load periods and reducing manual intervention. The proposed system offers a payback period of 2 months if implemented in the Senate building, providing efficiency, reliability, and cost savings.

Indexed Terms: Total Connected Load Current (CABC), Section A&B Load Current (CAB), Section A Load Current (CA), Renewable Energy Source Current (CRES), Battery Voltage (VB).

### I. Introduction:

Despite increasing integration of renewable energy sources, residential energy supply still heavily relies on non-renewable resources through public utility services. Efforts to minimize energy usage, including adjusting usage times and employing efficient devices, are incentivized by governments to promote energy efficiency [1]. Efficient energy consumption is vital for balancing supply and demand, leading to benefits such as increased financial capital, environmental quality, and human comfort [2].

II. Objective: The rapid increase in energy demand due to technological advancement poses challenges, particularly in power supply circuitry, where inductors and transformers draw significant inrush currents. Additionally, the efficiency of solar panels declines over time due to exposure to UV light and adverse weather conditions. Poorly sized systems can lead to fire outbreaks or reduced battery lifespan, necessitating costly replacements. To address these issues, a smart control system is proposed to monitor and compare renewable energy source power output with electrical load, prioritizing based on need. This system aims to reduce human intervention while ensuring resilience and reliability.

The primary objective of this research is to develop a smart control system for managing specific renewable energy resources at FUTO. To accomplish this, the following secondary objectives will be pursued:

i. Develop a block diagram for the smart control system. ii. Create a system algorithm and flowchart. iii. Design a circuit diagram for the smart control system. iv. Assess load demand and available resources at the Senate Building, FUTO. v. Develop and implement a



Dr.R.PANNEEROHAGS.ME.Ph.D.,

Dr.R.PANNEEROHAGS.ME.Ph.D.,

A.R.ENGINEERING ALAVAMIST.

A.R.ENGINEERING AM. 605 601.

KAPPINAMPURAM.605 601.



# International Research Journal in Global **Engineering and Sciences. (IRJGES)**

ISSN: 2456-172X | Vol. 4, No. 2, June-Aug 2019

Pages 157-165 | Cosmos Impact Factor (Germany): 5.195

Received: 02.08.2019 Published:28.08.2019

# NON-VERBAL COMMUNICATION: FOCUS ON RECRUITMENT INTERVIEW FOR FRESHERS

V.Girija, Revathy, D.Sampathkumar Professor, Department of English, A.R Engineering College, Villupuram-605 601 E-mail: girijasaravan27@gmail.com

### ABSTRACT.

For years, the psychology is concerned with the study of communication, and time is entered in he enterprise. This study probes the impact of nonverbal communication in the outcome of the ove-rall interview. They examined the nonverbal behaviors of the candidates to the talks, in particular: posture, eye contact, hand gestures and facial expressions, nonverbal behaviors were recorded at regular time intervals for the first 10 minutes of interview, for a total of 20 surveys per candidate. At the same time, the study examines the impact of the style of the interviewer (measured on the scale SYMILOG) and the experience gained by the candidate. The assumptions included: 1. Candidates with work experience have a non-verbal behavior than candidates without experience. 2. The style of interviewer may influezare nonverbal behavior of the candidate: the attitude more or less friendly breeder can cause certain non-verbal styles in the selected data were analyzed by ANOVA results that confirm the hypothesis: The level of experience, nonverbal behaviors and styleof the interviewer are expressed in significant interaction between them.

Keywords: non verbal Communication, recruitent interview, work experience, facial expression, body posture.

### INTRODUCTION

The professional contexts, are characterized by the assumption people's well-defined and specific roles. It happens then that nonverbal behaviors in human interaction are determined from the physician or the patient, the candidate rather than the interviewer in a job interview, or from any pub-lie official rather than the citizen.

What is interesting is groped to identify those non-verbal behavior patterns and thus for the most part unconscious and unaware that help us understand who we face if a person is important or not, whether confident or not or whether it is manipulated or not.

Rozelle, Drukman and Baxter (1986), propose to consider the 'non-verbal' as a skill you can develop and manage. Edinger and Patterson (1983), they also stress this possibility, arguing that the ability to manage nonverbal behaviors would lead to an improvement in working relationships and facilitating a comfortable interaction.

If the behavior is of interest as non-verbal skills, you can think of it as a potential that they may develop or learn, which, converging with the verbal communication skills, making people more competent and effective in their interpersonal relationships.

Noting the importance of the latter in organizational contexts, it was considered important to

V.Girija, Revathy, D.Sampathkumar VILLUPURAM 605 601

PIYAMPULIYUR POST, VILLUPURAM-605 601.

# ENGLISH LANGUAGE TEACHING AND **CONVERSATIONAL**

V.Girija, D.Sampathkumar

Professor, Department of English A.R Engineering College, Villupuram-605 601 Mail ID: girijasaravan27@gmail.com

#### Abstract

There has been extensive discourse about the role of conversational methods in English language teaching (ELT), generating both agreement and disagreement among scholars. A review of the literature reveals that ELT is deeply rooted in the discipline and sub-disciplines of linguistics, roots which it has never fully severed. This paper aims to trace the influence of linguistics on ELT over the last six decades, highlighting the linear and nonlinear relationships that linguistics maintains with ELT. The core objective is to elucidate how linguistic theories and methodologies have shaped and continue to shape the field of English language teaching. Keywords: Discourse, ELT, Improvement, Innovation, Conversational

### Introduction

The question of whether linguistics plays a role in English Language Teaching (ELT) is highly pertinent and has been the subject of much debate. Reviewing literature on the topic reveals a spectrum of opinions: some scholars assert that linguistics and ELT are intrinsically linked, while others believe they are distinct fields. This intense partisanship and lack of objectivity complicate the task of evaluating the role of linguistics in ELT.

Examining the history of linguistics over the past hundred years, and particularly the last six decades, shows that linguistics and its sub-disciplines have profoundly impacted all phases of language teaching. The evolution of theoretical linguistics—from traditional Grammar to Structuralism, from Transformational Generative Grammar to Systemic Functional Grammar, and the current emphasis on Semantics, Pragmatics, and Sociolinguistics—illustrates this influence. These linguistic theories and their associated methods have significantly shaped the design and implementation of ELT curricula and methodologies.

Linguistics has provided a theoretical foundation that informs various approaches to language teaching. For instance, the structuralist approach emphasized the systematic study of language structures, leading to methods that focus on grammar and syntax. Transformational Generative Grammar introduced concepts of deep structure and surface structure, influencing approaches that emphasize understanding the underlying rules of language use. Systemic Functional Grammar, with its focus on language function and use in context, has informed communicative language teaching methods that prioritize real-world language use.

Moreover, the rise of Semantics, Pragmatics, and Sociolinguistics has shifted the focus toward meaning, context, and the social aspects of language. These fields emphasize the importance of understanding language in use, which has led to the development of teaching methods that incorporate authentic language materials and real-life communication scenarios.

www.irjges.com | V.Girija, D.Sampathkumar



Dr.R.PANNEERDHASSME,Ph.D. A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM KAPPIYAMPULIYUR POST VILLUPURAM 605 601.

The interplay between linguistics and ELT is complex and multifaceted. Linguistic theories provide essential insights and tools that have shaped, and continue to shape, effective language teaching practices. This paper seeks to explore these relationships in depth, shedding light on the ongoing dialogue between linguistics and ELT, and highlighting the innovations and improvements that have arisen from this dynamic interaction.

### Structuralism

Structural linguistics developed as a reaction against traditional grammar, fundamentally altering scholars' perceptions of grammar. Richards and Rodgers (2006, p.54) noted that this reaction was influenced by the movement towards positivism and empiricism, spurred by Darwin's *The Origin of Species*. Structuralism emphasized treating linguistics as a scientific study of language, advocating for objectivity, verifiable descriptions, discovery procedures, the primacy of oral language, and the unique patterns of each language. These principles provided sound theories and techniques for language teaching.

Structuralists offered a more comprehensive and detailed description of language, which significantly influenced both the theory and methods of the Audio-lingual Method (ALM). They viewed language as a highly structured, rule-governed system that is meaningful within a given cultural community. Grammar was seen as "the set of formal patterns in which the words of a language are arranged to convey larger meanings" (Richards and Rodgers, 2006, p.55). Structural linguists analyzed language by identifying the smallest meaningful sounds (phonemes) and grammatical units (morphemes, stems, prefixes, suffixes) and then larger units such as phrases, clauses, and sentences. Language was viewed as a system of structurally related elements used to encode meaning, with these elements being phonemes, morphemes, and words. Language learning, according to structuralists, meant mastering these building blocks and the rules for combining them from phoneme to morpheme to word to phrases and sentences (Richards and Rodgers, 2006, p.55). This belief led to the development of the Audio-lingual Method, which focused on the mastery of speech through the four skills of listening, speaking, reading, and writing.

The structuralist notion of language as a system allowed for viewing second or foreign language learning as the juxtaposition of two systems. Fries and Pike (1949, as cited in Richards, 1974, p.4) suggested that this juxtaposition could lead to a new system combining features of both languages, and even to inter-systematic interference (Weinreich, 1953, as cited in Richards, 1974, p.4). This idea of interference resonated with both linguists and language teachers, as it seemed to explain the challenges of second language learning. This led to the emergence of the Contrastive Analysis (CA) approach.

The origins of CA were pedagogic, and it helped language teachers by identifying similarities and differences between the learner's native language and the target language, thus highlighting areas of facilitation and interference (Ellis, 1986, p.23). As S.P. Corder (1973, p.280) proposed, areas of facilitation and interference (Ellis, 1986, p.23) are similarities, emphasizing both facilitation and interference. language teachers should leverage the similarities, emphasizing both facilitation and interference. Although CA did not always predict errors accurately, it was useful for retrospectively explaining errors.

www.iriges.com KWilliam Sampathkumar

VILLUPURAM

605 601

Dr. R. PANNEEROHASS, M.E. Pho.

Dr. R. PANNEEROHASS, M.E. Pho.

PRINCIPAL PROST.

A. R. FARRING WELLING POST.

KAPPINAMPULINAS 601.

Structuralism provided a robust framework for understanding and teaching languages. By emphasizing the systematic and scientific study of language, it laid the groundwork for methods like the Audio-lingual Method, which sought to develop language skills through structured practice and mastery of linguistic elements. The introduction of concepts like interference and the development of Contrastive Analysis further enriched the field of language teaching, offering valuable insights into the complexities of learning a second language.

Error Analysis and Transformational Generative Grammar

As an alternative to Contrastive Analysis (CA), a more refined approach known as Error Analysis (EA) evolved. This approach shifted the focus from merely identifying similarities and differences between languages to systematically studying the errors learners make. Errors were viewed as a window into the learner's competence, offering insights into what the learner has mastered and what still needs to be learned. This systematic study of errors provided valuable feedback to teachers about the effectiveness of their instruction and the areas where learners needed more support.

With the publication of *Syntactic Structures* by Noam Chomsky in 1957, the emphasis in linguistic theory shifted from describing language to understanding the internalization of language. Chomsky's work marked a departure from the behaviorist view of language learning as habit formation and memorization of dialogues. Instead, Chomsky posited that language learning involves the acquisition of an abstract set of rules that enable speakers to generate grammatically correct sentences.

Chomsky's focus was on characterizing the abstract abilities that speakers possess, which allow them to produce grammatically correct sentences in a language (Richards and Rodgers, 1986, p.159). He introduced the concept of Transformational Generative Grammar, which claims that knowledge of a few basic sentence structures (kernel sentences) and transformational rules enables learners to generate a wide variety of sentences. According to Chomsky, "the grammar is a device for generating the sentences in a language" (Thomas, 1967, p.197).

A kernel sentence is a simple, active, declarative sentence. All other sentences are derived from these kernel sentences by applying transformational rules. Transformational rules either introduce new elements (e.g., negatives, adjectives), rearrange elements of a kernel sentence (e.g., interrogatives), or do both (e.g., passives). Chomsky implies that passive, interrogative, negative sentences, and those with adjectives, adverbs, and conjunctions, are more sophisticated than kernel sentences (Thomas, 1967, p.197).

For teachers, this notion of kernel sentences and transformational rules proved to be very helpful. It allowed for the organization of language instruction according to the increasing sophistication of structures. By teaching learners simple, active, declarative sentences and some transformational rules, teachers could help them produce grammatically correct and more complex sentences. This approach provided a logical order for selecting and arranging grammatical elements, building effectively on preceding material.

The most important contribution of Chomsky's theory is that it permits a teacher to select and arrange grammatical elements in a logical sequence, making it easier to build on previous

www.iriges.com | V.Girija, D.Sampathkumar



Dr.R.PAHNEEROHASS.ME.Pho.

Page 59

Dr.R.PAHNEEROHAL COLLEGE PRINCIPAL COLLEGE PRINCIPAL AVAILABLE POST.

A.R.ENGINEER POST.

A.R.ENGINEER POST.

KAPPIYAMPULIPUR. 605 601.

lessons. This method not only aids in teaching grammar systematically but also enhances learners' ability to generate creative and grammatically correct sentences in the target language. By focusing on the internal rules that govern sentence construction, teachers can help students develop a deeper understanding of the language, moving beyond rote memorization to true linguistic competence.

Besides this, Chomsky's theory of competence and performance, along with the concept of the Language Acquisition Device (LAD), provided evidence that language learning is a mental phenomenon. It involves processes of trial and error and the deduction of rules from the input to which learners are exposed. According to Chomsky, if a person has competence in a language, they can produce grammatically correct sentences and distinguish between grammatical and ungrammatical sentences.

However, Chomsky's theory faced criticism from sociolinguists like Campbell and Wales (1970) and Dell Hymes (1971). Campbell and Wales argued that Chomsky's idea of competence omitted "by far the most important linguistic ability... the ability to produce and understand utterances which are not so much grammatical, but, more importantly, appropriate to the context in which they are made" (Campbell and Wales, 1970, as quoted in George, 1992, p.135). Dell Hymes proposed that a native speaker must not only produce grammatically well-formed sentences but also understand and produce sentences appropriate to the context (Corder, 1973, p.92). George (1992) quotes Newmeyer, who in turn quotes Lakoff, suggesting that Chomsky's framework "sets up artificial boundaries and rules out of the study of language such things as context, social interaction, and deixis" (Newmeyer, 1982, as quoted in George, 1992, p.135).

This critique led to the concept of communicative competence, highlighting the importance of developing learners' ability to use language appropriately in various contexts. Hymes (1971) emphasized that communicative competence involves not only grammatical correctness but also the ability to use language effectively and appropriately in social contexts. This shift in focus was foundational for the development of the Communicative Language Teaching (CLT) approach.

Michael Halliday's (1975) focus on the functions of language rather than its forms, and Canale and Swain's (1980) notion of communicative competence, provided the linguistic foundation for CLT. These theories underscored the need to teach language as a tool for communication, not just as a set of grammatical rules. CLT methods emphasize interaction and real-life communication, preparing learners to use language in various social contexts. This approach influenced several language teaching methods, including Wilkins' Notional-Functional Approach, Widdowson's discourse-oriented approach, and English for Specific Purposes (ESP) approaches.

Strevens (1965, p.73) remarked that "the place of linguistics is behind the classroom teachers." He argued that the real contribution of linguistics is to enhance the teacher's understanding of the nature of language, making them more competent and effective. Linguistically oriented teaching materials yield satisfactory results only when used by teachers who are aware of the linguistic ideas and assumptions upon which they are based (Verma, 1993, p.76).

www.iriges.com | V.Girija, D.Sampathkumar

EH

VILLUPUPAN 605 601 Dr.R.PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL against PANNEER INCIPAL against POST,
A.R.ENGINEER INCHIPALAYAM,
KAPRIYAMPULIYUR POST,
KAPRIYAMPULIYUR SOL

The question posed at the beginning—"What has linguistics contributed to the field of English language reaching?"—can still be answered only partially and semi-objectively. Despite this, it is clear that linguistics has made significant contributions to ELT, particularly in terms of methods and techniques. While acknowledging the ongoing debates and evolving perspectives, it is evident that linguistic theories have profoundly shaped the way English is taught and learned, enhancing both pedagogical practices and learner outcomes.

### References

- 1. Canale, M., and M. Swain. "Theoretical Bases of Communicative Approaches to Second Language Teaching and Testing", Applied Linguistics. 1 (1), 1980, 1-47.
- Corder, S.P. Introducing applied linguistics. England: Penguin Books, 1973.
- 3. Ellis, R. Understanding second language acquisition. Oxford: Oxford University Press, 198
- 4. Halliday, M.A.K. Learning How to Mean: Explorations in the Development of Language. London: Edward Arnold, 1970.

Dr.R.PANNEERDHASS,ME.,Ph.O., A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM KAPPIYAMPULIYUR POST. VILLUPURAM EOS 601.

Page 61

umar www.iriges.com

# Grid Connected Multilevel Inverter TopologySuitable for Solar PV Applications with Varying Irradiance

B. Keerthana, P.Karthik, D.Sureshkumar, A.Sugunaya Assistant Professor

Department Of Electrical & Electronics Engineering, A.R Engineering College, Villupuram Email: Keerthanagow10@gmail.com

Abstract—A new asymmetrical multilevel inverter topology is reported that is capable to operate satisfactorily with wide varia- tion in dc-link voltage, while feeding power to the ac grid. A topo-logical building block is first introduced that has one full-bridge inverter connected in series with a level doubling network. Follow-ing this, the interconnection of such building blocks is attempted to increase the number of levels at the output voltage waveform. The investigation reveals that for a three-phase system, a converter configuration with two such building blocks is capable to generate a nominal asymmetry of 14:7:2:1 using only four voltage sources. In solar Photovoltaic (PV) applications, one main source may be fed by PV array and the other three auxiliary sources may be fed through separate dc/dc converters, each having power rating of 3.2% of the peak power rating of PV arrays. The proposed converter can generate 3097 space vectors. Asymmetrical hexagonal decomposition is modified (to ensure satisfactory operation of LDN and to eliminate any dc component in the phase voltage waveform) to control such converter. The converter is extensively simulated in MATLAB/Simulink. A solar PV system of 9.4 kWp available in the laboratory is used to feed power to the grid at different irradiance. Simulation results match well with the prototype experiments con-firming the usefulness of the proposed topological alternative for solar PV applications.

Index Terms—Gridconnected photovoltaic inverter, central inverter, multilevel inverter, level doubling network, inverter topology.

### INTRODUCTION

PHOTOVOLTAIC inverter is in the core of a grid connected Photovoltaic (PV) system. Leakage current (due to stray capacitance between the terminal and frame of PV module) is a key issue that influences selection of topology for such inverters.

Energy yield from a PV power plant depends on both *efficiency* and *reliability* of these inverters [1]. While a great attentionis paid to increase the efficiency to enhance energy capture, a considerable loss in the evacuation of power is observed due to inverter failure. The main reason for inverter failure is high frequency switching of few hundreds of ampere of output current. This current could be reduced by elevating the voltage level of the PV arrays. However, this is not recommended due to severalissues such as potential induced degradation (PID) [2], dielectric breakdown [3] etc., those limit the PV array voltage to a maximum of 600–900 volts. This leaves no other alternative but to have a central inverter with rated current of hundreds of ampere.

The key design constraints for a PV inverter are:

1) Leakage current must be below recommended standards,

2) Peak dc bus voltage has to be limited to 600-900 V,

3) Power quality has to be maintained as per grid code,

4) The solar park should not inject unbalanced current in tothe grid.

To satisfy the above requirements, many PV converter topolo-gies came up in last three decades. The section briefly highlights the merits and limitations of few potentially important topolo-gies in inpresse the converted topolo-gies and impresse topolo-gies and impresse topolo-gies and impr

www.iriges.com | B Kaerthana

rinik, D.Sureshkumar, A.Sugunaya

RENGINEER ING COLLEGE



### International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal Established in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NIT, Trichy, Journal Indexed in JIR, DIIF and SJIF.

Available online at: www.jrrset.com

ISSN == : 2347-6729 ISSN ....: 2348-3105

Volume 7, Issue 12 December 2019. JIR IF: 2.54

SJIF IF : 4.334 Cosmos: 5.395

Received on: 04.12.2019 Published on: 21.01.2020 Pages: 58-63

# **EXPERIMENTAL INVESTIGATION AND BUCKLING ANALYSIS OF WOVEN** GLASS EPOXY LAMINATED **COMPOSITE PLATE**

D.Manikandan, S.Ramamoorthy, S.Sendilkumaran, G.Ganapathy **Assistant Professor** 

Department Of Mechanical Engineering, A.R Engineering College, Villupuram E-mail:manimech812@gmail.com

#### ABSTRACT

In this project the Buckling behavior of laminated composite plates subjected to in-plane loads is an important consideration in the preliminary design of aircraft components. The sizing of many structural subcomponents of the aircraft structures is often determined by stability constraints. The objective of the current study is to understand the influence of the length-tothickness ratio, the aspect ratio, the fiber orientation and the cut-out shapes on the buckling load for the woven glass epoxy laminated composite plate in clamped-free-clamped-free configuration by finite element analysis using ANSYS software. Initially buckling analysis was carried out on woven glass epoxy laminated composite plate, both; experimentally and numerically; for the two different geometric configurations to predict the critical buckling load and the test results were compared with the FEA predictions, to check the validity of the analysis methodology. The same methodology was further followed for analyzing the buckling behavior of the composite plates. The results shows the effect of orientation of fiber, aspect ratio, cut-out shape and length-to-thickness ratio on the buckling of the glass epoxy laminated composite plate.

Keywords: - Plate buckling, woven glass epoxy laminate, length-to-thickness ratio, aspect ratio, fiber orientation, cut-out shapes.

D.Manikandan, S.Ramamoorthy, S.Sendilkumaran, G.Ganapathy



Dr.R.PANNEEROHASS, M.E. Ph D. A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM 605 601.



# International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal Established in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NIT, Trichy, Journal Indexed in JIR, DIIF and SJIF.

Available online at: www.jrrset.com

Received on: 04.12.2019 Published on: 21.01.2020 Pages: 64-70

ISSN (Price): 2347-6729

ISSN (value) : 2348-3105

Volume 7, Issue 12 December 2019. JIR 1F: 2.54

SJIF IF: 4.334 Cosmos: 5.395

# Enhanced Photocatalytic Degradation of Textile Dye Using W, N Co-Doped ZnO Powder: Synthesis, Characterization, and Solar Activity

Thamizhselvi D, Revathi A, Vasanthi M, Ramya K

Department of Science and Humanities, A.R. Engineering College, Vadakuchipalayam, Villupuram-605601, Tamil Nadu. \*Corresponding Author: E-Mail: <a href="mailto:thamizhkymari2020@gmail.com">thamizhkymari2020@gmail.com</a>

Abstract: The photocatalytic degradation of Reactive Blue 4 (RB 4) under solar irradiation was investigated using W, N co-doped ZnO. Various mole ratios (0.02 mol%, 0.03 mol%, 0.04 mol%, 0.05 mol%, and 0.06 mol%) of W, N co-doped ZnO photocatalysts were prepared via the sol-gel technique. Pure ZnO exhibited low photocatalytic activity due to poor surface properties, photo-corrosion, and limited utilization of visible light. These drawbacks were mitigated by doping ZnO with W, N. The photocatalytic activity of W, N co-doped ZnO significantly surpassed that of pure ZnO. XRD, SEM, UV-DRS, PL, and FTIRB analyses confirmed the enhanced photocatalytic properties of W, N co-doped ZnO. Furthermore, W, N co-doped ZnO exhibited photostability and long-term durability.

Keywords: W, N Codoped ZnO, Sol-gel route, photocatalytic degradation, Reactive Blue 4, solar light

#### 1. INTRODUCTION

The last centuries have seen a steady increase in human activities, causing remarkable technological development and soaring human populations. However, the industrial expansion has brought atmospheric, ground, and water pollution, all harmful to humans and the environment. Indeed, major pollution can cause human diseases like breathing problems, cardiovascular problems, cancers, neurobehavioral disorders, etc. It can also affect global warming, which worsens climate change, increases sea level rises, and causes serious damage to animals and flora.

Among the water pollutants, synthetic dyes pose significant issues. Synthetic dyes are commonly used by various industries, especially textile ones. These physically and chemically stable compounds are harmful to the environment. Synthetic dyes are recalcitrant compounds that exhibit high solubility in water and accumulate in both wastewater and industrial effluents. Consequently, the recovery of wastewater by conventional methods is not suitable for emergent pollutants. Heterogeneous photocatalysis can be satisfactorily applied for the decontamination of natural samples through the photocatalytic degradation of toxic pollutants from complex matrices, such as river water and wastewater. All renewable technologies have become a promising alternative for both energy generation and wastewater treatments. Solar photocatalysis is a suitable option to degrade recalcitrant pollutants from water.

The absorption of a photon initiates the photodecomposition of a semiconductor with energy greater than or equal to the bandgap of the semiconductor, producing electron-hole pairs. It is important for prolonging electron-hole recombination before a designated chemical reaction occurs on the semiconductor surface. Several semiconductor photocatalysts such as TiO<sub>2</sub>, ZnO, WO<sub>3</sub>, SnO<sub>2</sub>, CdS, and ZnS have been used for the treatment of wastewater pollutants under visible light irradiation. Among semiconductors, zinc oxide (ZnO) has attracted attention due to its environmental stability as compared to other metal oxides. The application of photocatalysis, especially using semiconductors such as ZnO, appears to be a more appealing option.

Thamizhselvi D, Revathi A, Vasanthi M, Ramya K



Dr.R.PANNETIDHASS, M.E., Ph.D.,
PRINCIPAL COLPEGE 64

A.R.ENGINEERING COLPEGE 64

VADAKUCHIPAL AYAM,
VADAKUCHIPAL AYAM,
VADAKUCHIPAL OS 601.

KAPPIYAMPULIYUR 605 601.
VILLUPURAM-605 601.

### International Journal on Recent Researches in Science, Engineering and Technology, Vol.7, Issue 12, December 2019. ISSN (Print) 2347-6729; ISSN (Online) 2348-3105

Approach to Photocatalysis

ZnO serves as a superior alternative to conventional chemical oxidation methods for the decomposition of toxic compounds due to its nonhazardous product[12]. This is because semiconductors have unique properties such as inexpensive, non-toxic, high surface area, broad absorption spectra, and facilitating multi-electron transfer processes. ZnO has been demonstrated as an improved photocatalyst as compared to commercialized TiO2 based on its more significant rate of activities and higher absorption efficacy of solar radiations[13]. However, ZnO has almost the same bandgap as TiO2. Surface area and surface defects play an essential role in the photocatalytic activities of metal oxide. The photocatalytic activity of ZnO is restricted to the irradiation wavelengths in the UV region because of its wide bandgap of about 3.2 eV and low quantum efficiency[14]. The fast recombination of ZnO's electrons poses additional constraints to its application. Some alternative strategies to extend ZnO's photoresponse in the visible light region are: (a) ZnO doping[15], (b) co-doping [16], (c) coupling with lower band gap semiconductors[17], (d) surface plasmon resonance[18], (e) quantum dots[19], and (f) sensitization with natural and synthetic dyes[20].

Several attempts have also been made to improve the efficiency of photocatalysts by using doping materials. Doping is required to improve the efficiency of photocatalysts. The reduction of the optical energy gap of ZnO by doping is an advantage for use in photocatalytic devices. Among these doping materials, Ag-doped

ZnO[21], N-doped ZnO[22], Mg-doping on ZnO[23] shows good photocatalytic activity.

Doping of non-metallic elements can form an intermediate energy level in the band gap of ZnO, which can reduce the band gap of ZnO and increase the photocatalytic activity of visible light. Anion doping can achieve better optical response of ZnO, especially in V group elements N, P, As[24]. Substitution by N doping is one of the best ways to lower down the band gap of ZnO, owing to the atomic size and electronegativity of the nonmetal element N and the closest to O atom[25], and the mixing p state of N and 2p state of O narrow the band gap of semiconductor oxide[26]. Furthermore, the introduction of N atoms into ZnO lattice will bring the energy band into intermediate energy level and reduce the absorption energy, which can increase photocatalytic

The combination between the properties of the nonmetals with that of transition metals may induce desirable optical and photocatalytic properties in ZnO. The integration between the visible-light responsive properties of nonmetal and the metal as trap centers can prompt more efficiency for practical applications. A. M. Youssef and S. M. Yakout designed effective visible light photocatalysts composed of C/La or Ce codoped ZnO

nanostructures were prepared by sol gel method.

Chemical structure of Reactive Blue 4

2.2. Preparation of W, N- codoped ZnO photocatalyst

10 g of zinc chloride and 0.01 mol% of Sodium tungstate and Urea were dissolved in 100 ml of double distilled water for the preparation of W, N- codoped ZnO photocatalyst. The dopant concentrations were added at the ratios like 0 to 0.05 mol percentage. To that solution required amount of sodium bicarbonate was then added in portions with vigorous stirring for several minutes, finally the precipitate was formed. The doped photocatalysts portions with vigorous stiffing to stiffing the distilled water to remove NaCl formed. The precipitate was then dried at 100°C are washed several times with distilled water to remove NaCl formed. The precipitate was then dried at 100°C to remove the water. The obtained precipitate was grinded in an agate mortar and pressed into a ceramic

Vasanthi M, Ramya K Thamizhselvi D, R

FERDHASS, M.E., Ph.D., BRINGIPA BOLOSEGE KNCHIBALAYAM, PIYAMPULIYUR POST, ULLUPURAM. 602 601.

### International Journal on Recent Researches in Science, Engineering and Technology, Vol.7, Issue 12, December 2019. ISSN (Print) 2347-6729; ISSN (Online) 2348-3105

crucible. The material was calcinated at 500°C for 4 hrs. The undoped ZnO was also synthesized in the same 2.3. Characterization

X-ray powder diffraction (XRD) patterns of the photocatalysts were recorded on a Philips X'pert-MPD diffractometer in the 20 range 20-80° using Cu-Kα radiation. The data were collected with a step of 0.028°. The atom temperature. Determe structure of the products was determined by comparing the experimental X-ray powder patterns to the standard compiled by the Joint Committee on Powder Diffraction and Standards (JCPDS). The crystallite sizes were calculated from the peak width using the Scherrer equation. The surface morphologies and particle size were observed by Scanning Electron Microscopy (JEOL, JSM-6360LV). UV-Visible diffuse reflectance spectra were acquired by a PerkinElmer Lambda 35 spectrometer. BaSO4 was used as the reflectance standard. The photoluminescence emission spectra of the samples were measured at room temperature using Perkin-Elmer LS 55 Luminescence spectrophotometer. 2.4. Photocatalytic studies

# 2.4.1. Photocatalytic degradation study of RB 4

All the photocatalytic experiments were performed under natural sunlight on clear sky days during the period of June to October 2020. In a typical experiment, 50 ml of dye solution (concentration 50 mg·l^-1) was taken with 50 mg of photocatalyst in a 250 ml glass beaker. Then the dye solution was kept in direct sunlight with continuous aeration and the concentration of the dye remains was measured periodically by measuring its light absorbance at the visible  $\lambda$  max by using Elco SL-171 Visible spectrophotometer. To avoid variation in results due to fluctuation in the intensity of the sunlight, a set of experiments have been carried out simultaneously. For pH studies the pH of the dye solutions were modified to different values (3, 5, 7, 9 and 12) by using 0.1M HCl

# 2.4.2. Chemical Oxygen Demand Analysis

The chemical oxygen demand (COD) is the indirect measurement of the oxygen needed for the complete oxidation of all the compounds present in solution. The COD of the degraded dye solution were analyzed in standard dichromate method. For the analysis, 0.4g of HgSO4 was added to 20ml of the degraded dye solution in a 250 ml round bottom flask. To that 10ml of 0.25N K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub> was added and mixed well. Then 30 ml of H<sub>2</sub>SO<sub>4</sub>-Ag<sub>2</sub>SO<sub>4</sub> reagent (prepared by dissolving 0.5g of Ag<sub>2</sub>SO<sub>4</sub> in 30ml of Concentrated H<sub>2</sub>SO<sub>4</sub>) was added slowly with constant stirring. After that few pieces of pumice stones were added and the flask was fitted with a condenser and refluxed for 2 hours. The solution was cooled and diluted to 150ml with distilled water and the entire content was titrated against 0.25N Ferrous Ammonium Sulphate (FAS) solution using ferroin as

# COD in mg·l^-1 = $(V_1 - V_2) \times N \times 8 \times 1000 V samp V samp 1000$

Where V1 & V2 are the volume of FAS solution consumed for blank and test sample respectively, N is the normality of FAS solution and VsampVsamp is the volume of sample taken for analysis. 3. RESULTS AND DISCUSSION

## 3.1 Physicochemical characterization of the photocatalyst

### 3.1.1 X-ray Diffraction Studies

The powder XRD patterns of ZnO and 0.04 mol% W, N- codoped ZnO were as shown in Figure 1. Both samples were identified as a single phase wurtzite ZnO by XRD analysis (JCPDS card nos.: 89-1397, 89-0511). The W, N codoped ZnO shows high intensity of the peaks, indicating that the samples are highly crystalline. On the other hand, codopants such as W and N incorporation on ZnO lattice increased the crystallinity. The mean crystallite sizes of the samples calculated by using the Scherrer formula for ZnO and W, N- codoped ZnO was given in Table 1. The results show that W, N doping decreases the particle size of the ZnO. An XRD pattern of W, N- codoped ZnO indicates the uniform dispersion of W and N ions. Moreover, the bulk structure remains virtually unchanged by the W and N- incorporation.




Figure 1: XRD patterns of ZnO and W, N- codoped ZnO,

, Vasanthi M, Ramya K Thamizhselvi D, Revethi

A.R. ENGINEERING COLLEGE VARAKUCHIPALAYAM, KAPPIYAMPULIYUR POST, VILLUPURAM-SOS 601.

Table 1: XRD Calculation Results of ZnO and W. N. codoned ZnO

		Full Width Half Maximum	Average Crystallite Size
	(Å)	(nm)	(nm)
ZnO	2.4753	0.342°	73
0.04% W, N- codoped ZnO	2.4710	0.400°	38

### 3.1.2 SEM Analysis of the Photocatalyst

The SEM micrographs of ZnO and 0.04% W, N- codoped ZnO photocatalysts were shown in Figure 2 a, b respectively. The micrographs show that ZnO particles have blunter particle morphology whereas W, Ncodoped ZnO has irregular arrangement patterns composed of spherical ZnO. This type of morphology could be able to completely degrade dye solutions. The reason is doped photocatalyst has shown a highly rough surface.




Figure 2: SEM micrograph of (a) ZnO, (b) 0.04% W, N codoped ZnO photocatalyst.

### 3.1.3 Diffused Reflectance UV-Visible Analysis of the Photocatalyst

Diffused reflectance spectra UV-visible spectra of ZnO and W, N- codoped ZnO absorption in Figure 3. The results show that the absorption onset of ZnO and W, N- codoped ZnO were 390 nm and 480 nm respectively. Therefore W, N- codoped ZnO can utilize visible light than the pure ZnO for photoexcitation process and expected to have more activity in the solar radiation than the undoped ZnO. The red shift in the light absorption of ZnO on W and N doping has been interpreted by Kim et al., as the sp-d exchange interaction between the band electrons and the localized "d" electrons of the transition metal ion at the cationic site.




Figure 3: Diffused Reflectance UV-Visible spectra of ZnO and W, N-codoped ZnO.

NEERDHASS,ME.,Pho., EER Thamizhselvi D, Revathi A, Vasanthi M ULLYUR POST, VILLUPURA VILLURURAM SAE EAL 605 601

International Journal on Recent Researches in Science, Engineering and Technology, Vol.7, Issue 12, December 2019. ISSN (Print) 2347-6729; ISSN (Online) 2348-3105

3.1.4 Photoluminescence Spectra

To study the optical properties of the synthesized solar active W, N codoped ZnO, the photoluminescence (PL) spectrum is recorded at room temperature. The PL spectrum compared with pure ZnO powder and W, N Codoped ZnO are shown in Figure 4.

The UV emission located at 391 nm is the band-edge emission resulting from the recombination of free excitons, and the broad green emission centered at 451 nm is caused by the radiative recombination of the photogenerated holes with electrons around the surface oxygen vacancy. In comparison with the pure spectrum of as-prepared ZnO, the UV emission of W, N codoped ZnO is enhanced, while the electron hole recombination might be suppressed. This phenomenon can be attributed to the reduction of band gap energy while doping W and N. The similar observation has been reported previously[32].





Figure 4: Photoluminescence spectrum of pure ZnO and 0.04 mol% W, N codoped ZnO.

3.1.5 FT-IR Spectroscopic Analysis

Fourier transform infrared spectroscopy of the hydrolyzed particles (Fig. 5) show strong peaks at 1564 cm<sup>-1</sup> and at 1399 cm<sup>-1</sup>. The previously mentioned peak at 1564 cm<sup>-1</sup> indicates the formation of ZnO[33]. When tungsten doping is with ZnO, the peak value shifted to 1627, this indicates O-W bond has elongated. Peaks at 475 cm<sup>-1</sup> and 452 cm<sup>-1</sup> correspond to N-O stretching and bending. These peaks confirm integration of tungsten (W) ion and nitrogen (N) with zinc (Zn) ion.



Thamizhselvi D, Revathi A, Vasanthi L, Ramya K

Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIP PARE EGE
A.R.ENGINEERING BOOS LEGE
VADAKUCHIPALAYAM,
VADAKUCHIPALAYAM,
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 601.

International Journal on Recent Researches in Science, Engineering and Technology, Vol.7, Issue 12, December 2019. ISSN (Print) 2347-6729; ISSN (Online) 2348-3105




Figure 5: FT-IR spectra of (a) pure ZnO and (b) 0.04 mol% W, N codoped ZnO photocatalyst.

### 3.2 Photocatalytic Studies

### 3.2.1 Photocatalytic Activity of W, N -codoped ZnO

The photocatalytic activity of the W, N-codoped ZnO photocatalysts has been evaluated from their activity in the degradation of Reactive Blue 4 (RB 4) in the presence of solar light. This dye has been chosen for the studies since it has a strong light absorption in UV-visible region. The UV-visible transmittance spectrum of the RB 4 solution show that more than 80% of incident light in the wavelength range 200-450 nm was absorbed by 50 mg·l<sup>-1</sup> dye solution in a path length of 1 cm. Hence, the degradation of the RB 4 solution with concentration above 50 mg·l<sup>-1</sup> in a simple photocatalytic process over a UV active photocatalyst like ZnO is difficult and will take more treatment time for complete degradation. The degradation of 50 mg·l<sup>-1</sup> RB 4 on W, N-codoped ZnO in a photocatalytic process was shown in Figure 6. The results show that W, N-codoped ZnO have higher activity than pure ZnO in simple photocatalytic process. The W, N-codoped ZnO with 0.01 mol % W, N content has shown maximum activity for the degradation of the dye and increase of W, N ion above 0.04 mol % decreases the activity of the ZnO. The high activity of the above 0.04 mol % W, N-codoped ZnO might suggest.

HO<sub>2</sub> (hydroperoxyl radicals) are less reactive than both hydroxyl radicals and hydrogen [37]. Figure - 11: Effect of concentration of H<sub>2</sub>O<sub>2</sub> on the efficiency of degradation of RB 4 (Initial concentration C<sub>0</sub>= 100 mg l<sup>-1</sup>; pH=5; Photocatalyst dosage 1 g l<sup>-1</sup>)

### 4. CONCLUSION

Pure ZnO and W, N codoped ZnO powder prepared in co-precipitation method followed by thermal treatment at 500°C for 5 hours has shown good activity for the degradation of reactive dyes in solar light. The prepared photocatalyst characterized by various techniques also compared them photocatalytic activity. 0.04 mol% W, N codoped ZnO demonstrated highest activity for the degradation of RB 4 with a chlorotriazine functional group. The rate of degradation of RB 4 over W, N codoped ZnO was maximum when the solution pH was 5, and the dosage of the photocatalyst was 1 g l<sup>-1</sup>. A hydrogen peroxide concentration of 10 mM was found to be optimum for the achieving the maximum activity in a oxidant combined Photocatalytic process. The 0.04 mol% W, N codoped ZnO also has good reusability; the 0.04 mol% W, N codoped ZnO completely degraded RB 4 in 120 minutes even in oxidant combined photocatalytic processes in its fourth reuse. Hence oxidant combined photocatalytic process over 0.04 mol% W, N codoped ZnO will be an efficient and cost-effective method for the degradation of organic dyes and other organic pollutants in industrial effluent.

### 5. REFERENCES

1. M.A. Khan, A.M. Ghouri, Res. World J. Arts Sci. Commer. 2 (2011) 276.

2. B. Lellis, C.Z. Fávaro-Polonio, J.A. Pamphile, J.C. Polonio, Biotechnol. Res. Innov. 3 (2019) 275.

3. M.M. Hassan, C.M. Carr, Chemosphere 209 (2018) 201-219.

Thamizhselvi D, Revathi A, Vasanthi M, Ramya K



# International Journal on Recent Researches in Science, Engineering and Technology, Vol.7, Issue 12, December 2019. ISSN (Print) 2347-6729; ISSN (Online) 2348-3105

- 4. D. Fabbri, M.J. López-Muñoz, A. Daniele, C. Medana, P. Calza, Photochem. Photobiol. Sci. 18 (2019) 845-852.
- 5. D.W. Zelinski, T.P.M. dos Santos, T.A. Takashina, V. Leifeld, L. Igarashi-Mafra, Water. Air. Soil Pollut. 229 (2018) 1-12.
- 6. E. Regulska, D. Rivera-Nazario, J. Karpinska, M. Plonska-Brzezinska, L. Echegoyen, Molecules 24 (2019) 1118.
- 7. S.A. Ansari, S.G. Ansari, H. Fouad, M.H. Cho, New J. Chem. 41 (2017) 9314-9320.
- 8. A. Naldoni, F. Riboni, U. Guler, A. Boltasseva, V.M. Shalaev, A.V. Kildishev, Nanophotonics 5 (2016) 112.
- 9. U. I. Gaya, A. H. Abdullah, J. Photochem. Photobiol C., 9 (2008) 1-12.
- 10. J.M. Herrman, Catalysis Today, 53 (1999) 115-129.
- 11. C. Shifu, Z. Wei, Z. Sujuan, L. Wei, Chem. Eng. J., 148 (2009) 263-269.
- 12. D. Chatterjee, D. Shimanti, Photochem. Rev., 6 (2005) 186-205.
- 13. S. Saktihvel, M. Janczarek, H. Kisch, J. Phys. Chem., 108 (2004) 19384-19387.
- M. Pera-Titus, V. Gar'cia-Molina, M. Baños, J. Gim'enez, S. Esplugas, Appl. Catal B:Environ., 47 (2004) 219-256.
- 15. U. Poornaprakash, K. Chalapathi, S.V. Subramanyam, Y. Prabhakar Vattikuti, S.P. Shun, Mater. Res. Express 6 (2019) 105356.
- 16. B. Poornaprakash, U. Chalapathi, P.T. Poojitha, S.V.P. Vattikuti, M.S.P. Reddy, J. Mater. Sci. Mater. Electron. 30 (2019) 9897-9902.
- 17. M. Kaur, A. Umar, S.K. Mehta, S. Singh, S.K. Kansal, H. Fouad, O.Y. Alothman, Material 11 (2018) 2254
- 18. C. Díaz-Uribe, J. Viloria, L. Cervantes, W. Vallejo, H. Navarro, E. Romero, C. Quiñones, Int. J. Photoenergy 2018 (2018) 1-8.
- 19. B. Poornaprakash, U. Chalapathi, P.T. Poojitha, S.V.P. Vattikuti, S.H. Park, J. Supercond. Nov. Magn. 33 (2020) 539-544.
- C. Diaz-Uribe, W. Vallejo, G. Camargo, A. Muñoz-Acevedo, C. Quiñones, E. Schott, E. X. Zarate, J. Photoc. Photobiol. A Chem. 2019, 384, 112050.
- 21. D.G. Fan, R. Zhang, Y. Li, Solid State Commun. 39 (2010) 1911-1914.

Dr.R.PANNEERDHASS,M.E.,Ph.D.

PRINCIPAL
PRINCIPAL
COLLEGE
PRINCIPALAYAM
POST
KAPEIYAMPULIYUR POST
VILLUPURAM-6898870

Thamizhselvi D, Revathi A, Vasanthi M, Hamya K, VILLUPURAM 603 601



# International Journal on Recent Researches in Science, Engineering & Technology (IJRRSET)

A Journal Established in early 2000 as National journal and upgraded to International journal in 2013 and is in existence for the last 10 years. It is run by Retired Professors from NIT, Trichy. Journal Indexed in JIR, DIIF and SJIF.

Available online at: www.jrrset.com

Received on: 04.12.2019 Published on: 21.01.2020 Pages: 76-82

ISSN (Print) : 2347-6729 ISSN (Online) : 2348-3105

Volume 8, Issue 1 January 2020. JIR IF: 2.54 SJIF IF: 4.334

Cosmos: 5.395

# PREPARATION, PROPERTIES AND MACHINABILITY STUDY OF GROUNDNUT SHELL-BROOM FIBRE-REINFORCED EPOXY COMPOSITE

Panneerdhass R\*, Kamalbabu K

Dept. of Mechanical Engg., A.R Engineering College, Villupuram-605601, India. Corresponding author\*:panneerdhass@gmail.com

Abstract. The need for eco-friendly materials and non-polluting processing techniques has made natural fibre reinforced polymer composites potential candidates to replace GFRPs and CFRPs in semi structural applications. Ground nutshell and broom fibre (fibre strands extracted from broom grass) are easily available in market at low cost. Polymer composites consisting of 30% and 40% volume fractions of a hybrid reinforcement containing groundnut shell and broom fibre in epoxy resin were fabricated by compression moulding. The mechanical characterization of these composites was carried out by standard tensile, compressive and flexural tests in a Universal Testing Machine with appropriate set-up. The machinability study was performed by drilling experiments using a CNC drilling machine with drill tool dynamometer. Two input parameters, cutting speed and feed rate and the one output parameter, thrust force, were used for drilling process. TiAIN coated solid carbide and HSS drills were employed in the drilling experiments and a comparative study was made based on the output parameters. Solid carbide resulted in lower thrust force values and feed rate proved to be the most influential parameter on thrust force.

Keywords: Natural fibre, compression moulding, Solid carbide tool, Drilling

### 1 Introduction

Recently, the research attempts in natural fibre reinforced polymer composites have greatly increased. Natural fibre reinforced polymer composites involve simple processing techniques, easily procurable raw materials and relatively high biodegradability levels among all the engineering materials. Apart from researchers, manufacturers have also shown increased interest in natural fibre composites from the past decade. To substantiate this claim, the increased in use of the natural fibres in German cars from around 10000 tonnes in the year of 2000 to 19000 tonnes in 2005 could be mentioned [1]. Hemp, sisal, kenaf, and bamboo are the natural fillers which have undergone many evaluation procedures and declared fit for a good number of applications. The mechanical properties of natural fibers and the composites developed by incorporating them in different polymer matrices and various processing techniques for fabricating them have been studied by many researchers [2–4]. Groundnut shell is highly

Panneerdhass R\*, Kamalbabu K.



Dr.R.PANNEERDHASS, MESPADIN PRINCIPAL COLLEGE A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM, VADAKUCHIPALAYAM, VABRIYAMPULIYUR GOS GOS.

### IJICE - International Journal on Information and Communication Engineering ISSN: 2250-1118 Volume 9 Issue 4 2019

July-Aug 2019 Pagos 14-23

### Distributed Detection of Minimum Cuts in Wireless Multi-Hop Networks

V.Maha<sup>1</sup>, S.Deevika<sup>2</sup>, R.Bharathi<sup>3</sup>, A.Madhavan<sup>4</sup>

<sup>1,2,3,4</sup> Computer Science and Engineering, A.R.Engineering College, Vadakuchipalayam, Kappiyampuliyur, Villupuram, Tamilnadu – 605601.

### Abstract

A wireless sensor network can get separated into multiple connected components due to the failure of some of its nodes, which is called a "cut". Here consider the problem of detecting cuts by the remaining nodes of a wireless sensor network. Here propose an algorithm that allows (i) every node to detect when the connectivity to a specially designated node has been lost, and (ii) one ormore nodes (that are connected to the special node after the cut) to detect the occurrence of the cut. The algorithm is distributed and asynchronous: every node needs to communicate with only those nodes that are within its communication range. The algorithm is based on the iterative computation of a fictitious "electrical potential" of the nodes. The convergence rate of the underlying iterative scheme is independent of the size and structure of the network. All cut nodes information is been updated and created into a log file of system and filtered log records of cut nodes are maintained.

### I. INTRODUCTION

Wireless sensor networks (WSNs) are a promising technology for monitoring large regions at high spatial and temporal resolution. In fact, node failure is expected to be quite common due to the typically limited energy budget of the nodes that are powered by small batteries. Failure of a set of nodes will reduce the number of multi-hop paths in the network. Such failures can cause a subset of nodes that have not failed to become disconnected from the rest, resulting in a "cut". Two nodes are said to be disconnected if there is no path between them. Wireless sensor networks (WSNs), consisting of large numbers of low-cost and low-power.

V.Maha, S.Deevika, R.Bharathi, A.Madhavan |

VILLUPURAM COLL COS 601 TO TO TO THE PROPERTY OF THE PROPERTY

Brathi, A.Madhavan | 14

Br.R.PANNEERDHASS, M.E., Ph.D.,

Br.R.PANNEERDHASS, M.E., Ph.D.,

PRINCIPAL

PRINCIPAL

COLLEGE

A.R. ENGINEERING COLLEGE

ISSN: 2250-1118 Volume 10 Issue 5 2020 Sep-Oct 2020 Pages 24-33

# **GPU-friendly Steiner-Tree Heuristic to** Find a Minimum Cost Tree Spanning a Given Subset

### P. LAKSHMIDEVI

Department of Electronics and Communication Engineering, A.R. Engineering College, Villupuram.

Email: saranyameece@gmail.com N. MUTHU KUMARAN

Department of Electronics and Communication Engineering, A.R. Engineering College, Villupuram.

Email: n.muthukumaran.ece@gmail.com

Rectilinear-Steiner-Minimum-Tree (RSMT) generation is a key step in VLSI routing. This paper describes a deterministic RSMT heuristic named SFP because it is simple, fast, and parallel. It is based on a rapid method for computing the optimal solution for three-pin nets, which it extends and applies to larger nets. Compared to FLUTE, a fast and high-quality RSMT algorithm, SFP incurs a wirelength penalty of 0.38 percent on the 16 ISPD 2008 inputs with 13 million nets. However, on a 16-core 2950X CPU, parallel SFP is 19 times faster than FLUTE, and on a Titan V GPU, it is 86 times faster. Serial SFP can generate an RSMT for a 10,000-pin net in under 1.5 seconds.

Keywords—GPU acceleration, Parallelism, Routing, RSMT heuristic, Steiner points

### I. INTRODUCTION

Signal routing is an essential step in the physical design of a VLSI chip. Its goal is to determine where to run the wires that connect the logic blocks (e.g., macros, cells, and gates) while keeping certain factors like wirelength, signal-propagation time, and power consumption low. This study focuses on the Rectalinear Steiner-Minimum-Tree generation—i.e., the first step of signal routing that involves minimizing the overall wirelength. The input is the location of the pins of each logic block as well as information about which pins to connect. A set of pins that must be connected is called a net. All nets together are referred to as

Panel (a) in Fig. 1 provides an example of a net with three pins that connects the output (P1) of one logic gate to one input each (P2 and P3) of two other logic gates. The three pins can be connected as shown in panel (b) but doing so results in an unnecessarily long wirelength. Panel (c) shows a better solution that is optimal assuming we can only connect pins to pins. This solution can be found by computing the Minimum Spanning Tree (MST) of all possible pin connections. If waypoints, called

Steiner points [15], are allowed, the wirelength can be shortened further as illustrated in panel (d).

Due to manufacturing constraints, only rectilinear (horizontal and vertical) wires are typically allowed. Panels (e) through (h) of Fig. 1 show four possible rectilinear solutions. They are constructed by connecting the pins in P2-P1-P3 order using Lshaped wires with one turn. The solutions in panels (e), (f), and (g) all have the same suboptimal wirelength. The solution in panel (h) containing the Steiner point S is optimal. It is shorter because the part of the two L-wires between P1 and S is shared. In general, the goal of Rectilinear-Steiner-Minimum-Tree (RSMT) generation is to interconnect k pins in a plane using only horizontal and vertical wires such that the total wirelength




Fig. 1. Several layouts of a three-pin net (blue dots denote pins, red dots indicate Steiner points, the net is blue, and solid wires are reculinear)

Finding the set of optimal Steiner points is NP-hard [15]. However, interconnecting given pins and Steiner points can be accomplished by computing an MST, a polynomial-time algorithm, of a complete graph where the vertices are the pins and Steiner points, and the edge weights are the rectilinear distance (Manhattan distance) between the edge's endpoints. Despite the NP-hardness, the optimal solution can often be computed in practice because nets tend to comprise just a few pins. Finding the optimal solution is trivial for two-pin nets and easy for threepin nets (cf. Section III). Taken together, two- and three-pin nets

P. LAKSHMIDEVI, N. MUTHU KUMARAN





### IJICE – International Journal on Information and Communication Engineering ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

# Reduction of Voltage Stress in a Medium Frequency Transformer using IFBTL DC/DC Converter for PMSG Based Wind Turbine

S. SARANYA<sup>1</sup>
Assistant Professor Dept of ECE
A.R Engineering College
saranyameece@gmail.com

N.MUTHUKUMARAN<sup>2</sup>
Assistant Professor Dept of ECE
A.R Engineering College
n.muthukumaran.ece@gmail.com

A.SUGUNYA<sup>3</sup>
Assistant Professor Dept of ECE
A.R Engineering College
asugunyaece@gmail.com

ABSTRACT- In this process we are improving the voltage in dc/dc converter and we are controlling voltage stress in the full bridge three level dc/dc converter. This paper presents an improved full bridge three level dc/dc converter for wind turbine in dc grid by inserting a passive filter into the dc/dc converter. This passive filter can effectively reduce the voltage stress of the medium frequency transformer in the IFBTL dc/dc converter.

Keywords- DC/DC Converter, improved full bridge three level (IFBTL), wind turbine, PMSG, DC grid.

### I. INTRODUCTION

I now a day's power demand is increasing so we are going to develop more efficiency power in a wind turbine .we are reducing the voltage stress in a dc/dc converter using an improved full bridge three level dc/dc converter in this process we are using IGBT. IGBT is a voltage controlled semiconductor device. Passive filter can effectively reduce the voltage stress of the medium frequency transformer in the IFBTL dc/dc converter. A DC-to-DC converter is an electronic circuit which converts a source of direct current (DC) from one voltage level to another. As the three-level converters with the advantages in the aspects of power quality, semiconductor electrical and thermal stresses, and EMI for high-power applications, the switches in the basic HB three-level converter, FB three-level converter, and the SMs-based FB three-level converter only take half of the dc bus voltage, which effectively reduces dv/dt in comparison with the FB two-level converter. For the N-level configuration, a total number

of 8(N-1) switches are needed for the SMs-based FB converter, which is much more than 2(N-1) and 4(N-1) switches required in the basic HB and FB converters, respectively. Besides, the corresponding numbers of voltage sensors are normally required for the SMs, and the voltage balancing control would be complicated for the SMs-based FB converter. The basic full-bridge three-level (FBTL) converter, with the advantage of the reduced voltage stress of the switches, reduced filter size, and improved dynamic response, is becoming highly suitable for medium-voltage and highpower conversion. Although both the basic FBTL and the SMs-based FBTL configurations can create fivelevel output voltage to minimize voltage steps and reduce dv/dt in comparison with the basic HBTL configuration, particularly in the medium-voltage and high-power applications, the basic FBTL converter has a simpler circuit structure and less number of switch devices than the SMs-based FBTL configuration, which leads to a small footprint and high reliability for the basic FBTL converter. The FB converter has been evaluated to be a suitable choice for wind farm application from an energy efficiency point of view. Hence, the isolated FBTL dc/dc converter is to be studied for high-power wind turbine systems in this paper. Some work about the isolated FBTL converter control has been reported, such as the chopping phaseshift (CPS) control and double phase-shift (DPS) control presented, respectively, but they have a highvoltage change rate dv/dt, and thus may not be applicable for the medium-voltage and high power systems. So far, the application of the isolated FBTL dc/dc converter for offshore wind turbines within a dc

S. SARANYA, N. MUTHUKUMARAN, A. SUGUNYA





ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

grid has not been addressed in detail in the literature. In this paper, an improved FBTL (IFBTL) dc/dc converter is presented for an offshore wind turbine based on permanent magnet synchronous generators (PMSGs) in a dc grid as shown in Fig. 2, where the IFBTL dc/dc converter is applied to boost the dc voltage from a diode rectifier to a high voltage for the dc grid integration.

This paper is organized as follows. In Section II, the IFBTL dc/dc converter and the corresponding modulation strategy are proposed. In Section III, the voltage balancing control for the IFBTL dc/dc converter is proposed. Section IV presents the control of the wind turbine system based on the DC/DC converter.

TABLE I
POSSIBLE DC/DC CONVERTER OPTIONS

Convo	rter topology	Valve number	Switch number in each valve	Valve voltage	Produced voltage level	Voltage balance control complexity
2- level	Basic FB converter	4	6×1.7 kV IGBTs	DC bus voltage	2	No
3- level	Basic IIB converter	4	3×1.7 kV IGBTs	Half DC bus voltage	3	Easy
3- level	Basic FB converter	8	3×1.7 kV IGBTs	Half DC bus voltage	5	Easy
3- level	FB converter based on SMs	16	3 ×1.7 kV IGBTs	Half DC bus voltage	5	Calculation is proportional to the SMs number




Fig. 1. Block diagram of the wind turbine connected to a de grid.

II. SWITCHED-MODE CONVERSION

Electronic switch-mode DC to DC converters convert one DC voltage level to another, by storing the input energy temporarily and then releasing that energy to the output at a different voltage. The storage may be in either magnetic field storage components (inductors, transformers) or electric field storage components (capacitors). This conversion method is more power efficient (often 75% to 98%) than linear voltage regulation (which dissipates unwanted power as heat). This efficiency is beneficial to increasing the running time of battery operated devices. Most AC-to-DC converters are designed to move power in only one direction, from

17

S. SARANYA, N. MUTHUKUMARAN, A. SUGUNYA



Dr.R.PANNEERDHASS,ME.,Ph.D.,
PRINCIPAL
PRINCIPAL
PRINCIPAL
A.B. ENGINEERING COLLEGE
VADAKUCHIDAL AVAM.
VADAKUCHIDAL AVAM.
KAPPIYAMPIRAM. OUD I

# IJICE – International Journal on Information and Communication Engineering ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

the input to the output. However, all switching regulator topologies can be made bi-directional by replacing all diodes with independently controlled active rectification. A bi-directional converter can move power in either direction, which is useful in applications requiring regenerative braking. The basic FBTL converter, with the advantages of the reduced voltage stress of the switches, reduced filter size, and improved dynamic response, and it is a simple circuit structure and less number of switching devices than the SMs-based configuration, which leads to a small foot-print and high reliability for the basic FBTL converter. In this paper, an improved FBTL dc/dc converter is presented for an offshore wind turbine based on permanent magnet synchronous generator (PMSGs) in a dc grid.




Fig.2 Block diagram for FBTL circuit.

### III. IFBTL DC/DC Converter

The IFTBL dc/c converter, which is composed of eight switches (S1-S8), eight freewheeling diode or fly back diode (D1-D8), four clamping diodes (D9-D12), an mft, four rectifier diodes (Dr1-D), a passive filter (Ls and Cs), an output filter inductor Ld, an output capacitor C0, and two voltage divided capacitor (Ci1 and Ci21), which are used to spilt the dc bus voltages Vi into two equal voltages Vc1 and Vc2.




Fig ,3 Block diagram for IFBTL circuit.

In the project we are using medium pass filter for controlling the voltage level in the output side. A freewheeling diode (sometimes called a snubber diode, fly back diode, suppressor diode, or catch diode) is a diode used to eliminate fly back, which is the sudden voltage spike seen across an inductive load when its supply voltage is suddenly reduced or removed. Fly back diodes are used whenever inductive loads are switched off by silicon components: in relay drivers, H-bridge motor drivers, and so on. A switched-mode power supply also exploits this effect, but the energy is not dissipated to heat and instead used to pump a packet of additional charge into a capacitor, in order to supply power to a load. We are using IGBT, The insulated-gate bipolar transistor or IGBT is a three-terminal power semiconductor device primarily used as an electronic switch and in newer devices is noted for combining high efficiency and fast switching. The IGBT is a semiconductor device with four alternating layers (P-N-P-N) that are controlled by a metal-oxidesemiconductor (MOS) gate structure without regenerative action. An IGBT has a significantly lower forward voltage drop compared to a conventional MOSFET in higher blocking voltage rated devices. As the blocking voltage rating of both MOSFET and IGBT devices increases, the depth of the n- drift region must increase and the doping must decrease, resulting in roughly square relationship decrease in forward conduction vs. blocking voltage capability of the device. By injecting minority

S. SARANYA, N. MUTHUKUMARAN, A. SUGUNYA



Dr.R.PANNEERDHASE II E. PinBin PRINCIPAL PRINCIPAL PRINCIPAL A.R. ENGINEERING COLLEGE WARPIYAMPULINUR POST, WILLUPURAM. GL. 2. 601.

### IJICE - International Journal on Information and Communication Engineering ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

carriers (holes) from the collector p+ region into the n- drift region during forward conduction, the resistance of the n- drift region is considerably reduced. The IGBT is used in medium- to high-power applications such as switched-mode power supplies, traction motor control and induction heating.




Fig ,4 Block diagram of the proposed voltage balancing control strategy for IFBTL converter.

### IV. PROPOSED MODULATION STRATEGY

The main difference between the two operation modes is the capacitor charger and discharge situations in of cycles. In operation mode I capacitor Ci2 discharges more energy than capacitor ci1


### 1) Voltage control strategy Mode I

The PWM waveform for the pairs S8–S6, S5–S7, and S4–S2 lags behind that for pair S1–S3 by (D – Dc) Ts/2, Ts /2, Ts/2and (D – Dc + 1) Ts/2respectively. Ts are the switching cycle. The overlap time between S1–S3 and S8–S6 is Dc Ts /2, which is also for S4–S2 and S5–S7. Dc is defined as the overlap duty ratio.


### 2) Voltage control strategy Mode II

The PWM waveform for pair S8–S6 leads before that for pair S1–S3 by (D-Dc) Ts/2, and the PWM waveform for pairs S4–S2 and S5-S7 lags behind that for the pair S1–S3 by (1-D+Dc) Ts/2 and Ts/2, respectively. The overlap time between S1–S3 and S8–S6 and between S4–S2 and S5–S7 is also both Dc Ts/2.

In each half cycle, while capacitor ci1 and the CI2 exchange the situation in operation mode 2.In operation mode 2 capacitor ci1 discharges more energy than the capacitor ci2 in each half cycle. The operation modes can be alternately used for the adaptive voltage balancing control. The study state operation of the convertor under the proposed modulation strategy re explain with assumption that ci1=ci2.



**FBTL** Inductor current



IFBTL Inductor current

Fig ,5 Waveform for inductor current.

# V. PROPOSED VOLTAGE BALANCING CONTROL STRATEGY

A voltage balancing control strategy is proposed for the IFBTL dc/dc converter in the section, which can be realized by alternating the operation modes I and II

A. In Voltage control strategy Mode I

S. SARANYA, N. MUTHUKUMARAN, A. SUGUNYA




OF RPANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
PRINCIPAL
PRINCIPAL
A.R. ENGINEERING COLLEGE
VADAKUCHIPALAYAM,
KAPRIMAMPULIYUR POST,
VILLUPURAM-605 601.

ISSN: 2250-1118 Volume 11 Issue 4, 2021


Jul-Aug 2021 Pages 16-21

If both the capacitor currents ic1 and ic2 are with the period of Ts /2. In the first half cycle, the charge or discharge Situations for capacitors Ci1 and Ci2 in stages A, C, and E are the same. In stage B, current ic2 is more than ic1, while ic2 is far less than ic1 in stage D. Owing to that, the periods of stages B and D are (D - Dc) Ts /2. Suppose Vc1 = Vc2 = Vi/2; Ci2 would provide more energy to the load than Ci1in the first half cycle under the operation mode I. The situation in the second half cycle is similar to that in the first half cycle. Consequently, voltage Vc1 would be increased and voltage Vc2 would be reduced in operation mode I which would result in the trend that voltage Vc1 would be more than Vc2 in operation mode I.

that current.ic2 is less than ic1 in stage D, while ic2 is far more than ic1 in stage B in operation mode II which is contrary to that in operation mode I. The periods for stages B and D are both (D - Dc)Ts/2. Suppose Vc1 = Vc2 = Vi/2; Ci1 would provide more energy to the load than Ci2 in the first half cycle under the operation mode II. The situation in the second half cycle is similar to the first half cycle. Therefore, voltage Vc1 would be reduced and voltage Vc2 would be increased in Operation mode II, which would result in the trend that voltage Vc1 would be less than Vc2 in operation Mode II.



FBTL O P voltage




IFBTL O/P voltage


Fig, 6 Waveform for output voltage.

### B. In Voltage control strategy Mode II

The same to operation mode I, the charge and discharge situations for capacitors Ci1 and Ci2 in stages A, C, and E are the same as in the first half cycle. The only difference is



FBTL O/P current



### IFBTL O/P current

Fig ,7 Waveform for output current

VI. CONTROL OF AN IFBTL CONVERTER-BASED WIND TURBINE:

S SARANYA, N MUTHUKUMARAN, A SUGUNYA



Dr.R.PANNEERDHASS,ME.,Ph.D.,
PRINCE COLLEGE
PRINCE COLLEGE
VADAKUCHIPALAYAM.
KAPPIYAMPULIYUR POST;
VILLUPURAMA 601.

ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

The control structure of the variable-speed wind turbine (VSWT) based on a PMSG and an IFBTL dc/dc converter, where the wind turbine is connected into the dc grid. The optimal power P \* g can be obtained with the measured wind turbine speed  $\omega$  based on the maximum power point tracking method neglecting the power electronics losses, the power relationship can be presented as

### Pg = Vi ii = Vo iLd

Where Pg is the generator power and ii is the input current of the IFBTL converter. A PI regulator is used as the power controller and produces the current reference i\*Ld. The other PI regulator is used as the current controller and produces the duty cycle D for the IFBTL converter so as to follow the optimal power of the VSWT.

#### VII. CONCLUSION

This paper has presented the control of the IFBTL dc/dc converter for the wind turbine system to facilitate the integration of wind turbines into a dc grid. The corresponding modulation strategy, including operation modes I and II, is proposed for the IFBTL dc/dc converter. The proposed two operation modes are discussed in detail. A voltage balancing control strategy is proposed for the IFBTL dc/dc converter, where the alternation of the proposed two operation modes can keep the capacitor voltage balanced. With the passive filter and the modulation strategy, the voltage stress of the transformer in the IFBTL dc/dc converter can be effectively reduced, which is very significant in the medium-voltage and high-power application. The control of the wind turbine system based on the IFBTL dc/dc converter is presented as well.

### VIII. REFERENCE

- X. Ruan, B. Li, Q. Chen, S. C. Tan, and C. K. Tse, "Fundamental considerations of three-level dc-dc converters: Topologies, analyses, and control," *IEEE Trans. Circuits Syst. I, Reg. Papers*, vol. 55, no. 11, pp. 3733–3743, Dec. 2008.
- P. J. Grbovic, "High-voltage auxiliary power supply using seriesconnected MOSFETs and

- floating self-driving technique," *IEEE Trans. Ind. Electron.*, vol. 56, no. 5, pp. 1446–1455, May 2009.
- 3. P. J. Grbovi'c, P. Delarue, P. Le Moigne, and P. Bartholomeus, "A bidirectional three-level dc-dc converter for the ultracapacitor applications," *IEEE Trans. Ind. Electron.*, vol. 57, no. 10, pp. 3415–3430, Oct. 2010.
- 4. S. Inoue and H. Akagi, "A bidirectional isolated dc-dc converter as a core circuit of the next-generation medium-voltage power conversion system," *IEEE Trans. Power Electron.*, vol. 22, no. 2, pp. 535-542, Mar. 2007.
- J. Rodriguez, S. Bernet, B. Wu, J. O. Pontt, and S. Kouro, "Multilevel voltage-sourceconverter topologies for industrial mediumvoltage drives," *IEEE Trans. Ind. Electron.*, vol. 54, no. 6, pp. 2930–2945, Dec. 2007.
- M. N. Slepchenkov, K. M. Smedley, and J.Wen, "Hexagram-converterbased STATCOM for voltage support in fixedspeed wind turbine generation systems," *IEEE Trans. Ind. Electron.*, vol. 58, no. 4, pp. 1120–1131, Apr. 2011.
- 7. S. S. Fazel, S. Bernet, D. Krug, and K. Jalili, "Design and comparison of 4-kV neutral-point-clamped, flying-capacitor, and series-connected Hbridge multilevel converters," *IEEE Trans. Ind. Appl.*, vol. 43, no. 4, pp. 1032–1040, Jul./Aug. 2007.
- 8. P. Samuel, R. Gupta, and D. Chandra, "Grid interface of wind power with large split-winding alternator using cascaded multilevel inverter," *IEEE Trans. Energy Convers.*, vol. 26, no. 1, pp. 299–309, Mar. 2011.

S. SARANYA, N. MUTHUKUMARAN, A. SUGUNYA



Dr.R. PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL COLLEGE
A.R. ENGLICHERALAYAM,
KAPRIYAM PULIYUR POST,
VILLURURAM: 606. 601.

ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 16-21

Flar

A.RVADAKUCHIPALAYAM.

KAPPIYAMPULIYUR POST.

VILLUPURAM-005 601.





### IJICE – International Journal on Information and Communication Engineering ISSN: 2250-1118 Volume 11 Issue 4, 2021

Jul-Aug 2021 Pages 22-32

# SECURITY OF VEHICLES USING PROTOCOL-LEVEL RADIOWIRE THREATS

### R. MAHALAKSHMI¹, N. MUTHU KUMARAN²

<sup>1</sup>Department of Electronics and Communication Engineering, A.R. Engineering College, Villupuram, saranyameece@gmail.com, Number: +91-7708932286

<sup>2</sup>Department of Electronics and Communication Engineering, A.R. Engineering College, Villupuram, n.muthukumaran.ece@gmail.com, Number: +91-7708363460

#### Abstract

Devices today offer a plethora of infotainment features, catering to owners' desires for rich audio, hands-free calls, contact management, and navigation through their connected mobile phones. However, these features also expose infotainment units to exploitable wireless attack surfaces. This study assesses protocol-level RadioWire threats on vehicles, a significant yet overlooked wireless attack surface. These threats are critical as they can be transported across vehicles and achieve impactful goals, such as accessing sensitive data or even gaining remote control of the vehicle. This evaluation is groundbreaking as previous research primarily focused on other wireless attack surfaces, particularly RadioWire implementation bugs. Among the pertinent protocol-level threats, we focus on the KNOB and BIAS attacks, which offer the most effective strategy for impersonating arbitrary RadioWire devices and have not yet been evaluated against vehicles.

Testing vehicles poses several challenges, leading us to design a cost-effective methodology based on hybrid lab/on-the-road experiments. We assessed five popular infotainment units (e.g., KIA and Toyota units) in the lab and three recent cars (e.g., Suzuki and Skoda cars) in a controlled on-the-road environment. We provide a detailed description of our methodology to enable other researchers to replicate and build upon our findings. Our protocol-level security evaluation of RadioWire uncovers concerning findings regarding vehicular security. For instance, despite patches in the RadioWire standard, all tested devices remain vulnerable to BIAS and KNOB attacks. Additionally, the tested devices accept keys with insufficient entropy, contrary to the standard's mandate of 7 bytes of entropy. Furthermore, these devices employ weak and outdated RadioWire security parameters, such as weak authentication protocols and ciphers.

I. INTRODUCTION Vehicles, including cars, trucks, and motorbikes, utilize numerous wireless technologies, such as RadioWire for hands-free services, cellular for internet access, Wi-Fi for sharing internet connections, and keyless entry systems for wireless locking and unlocking. Since 2020, it's estimated that one in five vehicles has employed wireless technologies, constituting more than 25% of over a billion cars.

R. MAHALAKSHMI, N. MUTHU KUMARAN



DIR PANNEEROHASS, M.E., Ph.D.,
PRINCIPAL
PRINCIPAL
A.R. ENGINEERING COLLEGE
A.R. ENGINEERING COLLEGE
KAPPIYAMPULIYUR POST,
VILLUPURAM-605 801...

IJICE – International Journal on Information and Communication Engineering, 2018 ISSN: 2250-1118 Volume 12 Issue 2, 2022 Mar-Apr 2022 Pages 10-29

# IOT BASED FISH MONITORING SYSTEM FOR AQUACULTURE

Saravanan.P, Nisha.R, Savitha.N, Saranaya.R, Muthuarasan.R Assistant Professor

Department Of Electronics and Communication Engineering, A.R Engineering College, Villupuram E-mail:saravanankarunika@gmail.com

### ABSTRACT:

Aquaculture mainly refers to cultivating aquatic organisms providing suitable environments for various purposes, including commercial, recreational, public purposes. This paper aims to enhance the production of fish and maintain the aquatic environment of aquaculture in Bangladesh. This paper presents the way of using Internet of Things (IoT) based devices to monitor aquaculture's basic needs and help provide things needed for the fisheries. Using these devices, various parameters of water will be monitored for a better living environment for fish. These devices consist of some sensors that will detect the Potential of Hydrogen (pH) level, the water temperature, and there will be two extra sections where the measurement of dissolved oxygen level and ammonia level using the testing kits can be determined which are needed for proper fish farming in the right water. An android-based mobile application has also been developed. In this system, farmers, fishermen, and people related to aquaculture will be the users of an android application. Via that application and with the help of a device, users will be notified about the amount of dissolved oxygen, ammonia level, pH level, and water body temperature. This monitoring system will help fish farmers to take the necessary steps to prevent any disturbance in an aquatic environment. Though Bangladesh is a riverine country and fish farming has a huge impact on this country's economy, it is necessary to keep in good health to produce more and more fish. But the fisheries of this country are not expert enough to understand how to provide necessary elements to fish and what to do. They might get help from this system and measure the parameters they can give necessary things to grow more fish.

**Keywords:** Aquaculture; and roid application; IoT; sensors; dissolved oxygen; pH level; temperature; water pollution; fish health; fish farmers.

### 1.Introduction:

The importance of aquaculture is beyond description. In the aquaculture system, fish are cultured in confined artificial water bodies such as a tank where they live, eat, grow, and extract waste. There is no This work is licensed under a Creative Commons Attribution 4.0

Saravanan.P ET.AL.



Dr.R.PANNEERDHASS,M.E.,Ph.D.,
PRINCIPAL
PRINCIPAL
PRINCIPAL
A.R.ENGINEERING COLLEGE
A.R.ENGINEERING COLLEGE
VADAKUCHIPALAYAM;
VADAKUCHIPALAYAM;
KAPPIYAMPULIYUR POSTI

ISSN: 2250-1118 Volume 12 Issue 2, 2022

Mar-Apr 2022 Pages 30-39

# Grid Connected Multilevel Inverter TopologySuitable for Solar PV Applications with Varying Irradiance

B.Keerthana, P.M.Kumarasan, R.Udhayakumar, A.Sugunya **Assistant Professor** 

Department of Electrical & Electronics Engineering, A.R Engineering College, Villupuram E-mail: keerthanagow10@gmail.com

Abstract-A new asymmetrical multilevel inverter topology is reported that is capable to operate satisfactorily with wide variation in dc-link voltage, while feeding power to the ac grid. A topological building block is first introduced that has one full-bridge inverter connected in series with a level doubling network. Following this, the interconnection of such building blocks is attempted to increase the number of levels at the output voltage waveform. The investigation reveals that for a three-phase system, a converter configuration with two such building blocks is capable to generate a nominal asymmetry of 14:7:2:1 using only four voltage sources. In solar Photovoltaic (PV) applications, one main source may be fed by PV array and the other three auxiliary sources may be fed through separate dc/dc converters, each having power rating of 3.2% of the peak power rating of PV arrays. The proposed converter can generate 3097 space vectors. Asymmetrical hexagonal decomposition is modified (to ensure satisfactory operation of LDN and to eliminate any dc component in the phase voltage waveform) to control such converter. The converter is extensively simulated in MATLAB/Simulink. A solar PV system of 9.4 kWp available in the laboratory is used to feed power to the grid at different irradiance. Simulation results match well with the prototype experiments confirming the usefulness of the proposed topological alternative for

Index Terms-Gridconnected photovoltaic inverter, central inverter, multilevel inverter, level doubling network, inverter topology.

### I. INTRODUCTION

HOTOVOLTAIC inverter is in the core of a grid connected Photovoltaic (PV) system. Leakage current (due to stray capacitance between the terminal and frame of PV module) is a key issue that influences selection of topology for such inverters. Energy yield from a PV power plant depends on both efficiency and reliability of these inverters [1]. While a great attention is paid to increase the efficiency to enhance energy capture, a

Manuscript received June 28, 2016; revised November 21, 2016 and January Manuscript received June 28, 2016; revised November 21, 2016 and January 20, 2017; accepted March 19, 2017. Date of publication April 7, 2017; date of current version September 15, 2017. This work was supported in part by the Department of Science and Technology, India, through a project entitled Rehable and Efficient Systems for Community Energy Solution (RESCUES), which is a joint cellaboration initiative between India and U.K. Governments, Paper no. TSTE-06493-2016 (Convergonaling author Sount & Chartopodivav).

The authors are with the Department of Electrical Engineering, Indian Institute of Technology Kharaspur, Kharaspur 721302, India (e-multisumitke 1981) from the Convergence of the figures in this paper are available online.

Color versions of one or more of the figures in this paper are available online at http://ieeexplore.ieee.org.

considerable loss in the evacuation of power is observed due to inverter failure. The main reason for inverter failure is high frequency switching of few hundreds of ampere of output current. This current could be reduced by elevating the voltage level of the PV arrays. However, this is not recommended due to several issues such as potential induced degradation (PID) [2]. dielectric breakdown [3] etc., those limit the PV array voltage to a maximum of 600-900 volts. This leaves no other alternative but to have a central inverter with rated current of hundreds of

The key design constraints for a PV inverter are:

- 1) Leakage current must be below recommended standards.
- 2) Peak dc bus voltage has to be limited to 600-900 V.
- 3) Power quality has to be maintained as per grid code,
- 4) The solar park should not inject unbalanced current in to the grid.

To satisfy the above requirements, many PV converter topologies came up in last three decades. This section briefly highlights the merits and limitations of few potentially important topologies. To increase the efficiency, it was attempted to reduce iron losses by removing the transformer. Many transformerless topologies were evolved [4]. None of these topologies are suitable for central inverter applications. Neutral point clamped (NPC) structures were proposed and analyzed for transformerless PV inverters in [5]-[7]. However, as shown in [8], NPC structures also require due attention to mitigate leakage current in its three-phase version, which reduces its peak voltage by a factor of 0.866 rejecting certain space vectors. This introduces additional loss in filter coupling inductor. Moreover, any stray inductance in the neutral line may cause leakage current higher than the limit

Z-source inverters or its derived topologies [9]-[11] are reported for solar PV applications. This has the advantage of having higher range of MPPT operation. However, this is achieved at the cost of high frequency switching. Additional loss of energy is obvious in the passive components (mainly in the inductors) in these converter topologies.

The other approach to develop grid connected PV inverter is to explore cascaded multilevel inverter topologies to maintain power quality with reduced switching and inductor losses [12]-[18]. In [12]-[14], cascaded H-bridge is directly used as PV inverter. Due to inter-array capacitance, these topologies will have leakage current even in case of transformer isolation

Saravanan.P ET.AL.



Dr.R.PANNEERDHASS,M.E.,Ph.D., A.R.ENGINEERING COLLEGE VADAKUCHIPALAYAM KAPPIYAMPULIYUR POST, VILLUPURAM. EGS GOT.

ISSN: 2231-2099Volume 11 Issue 1 Jan-March 2021 Pages 31-35

# SBFET -Based Full Adder with Ultra-Low Leakage and High Speed

B.LAKSHMI<sup>1</sup>
Department of Electronics and Communication Engineering, A.R. Engineering College,

Villupuram. saranyameece@gmail.com Number: +91-7708932286 N.MUTHU KUMARAN<sup>2</sup> Department of Electronics and Communication Engineering, A.R.Engineering College,

Villupuram. n muthukumaran ece@gmail.com Number: +91-7708363460

Abstract-The design of full adder has always been considered by designers over the years and the main efforts in this field have been on low operating voltage, low-power consumption, high speed, low chip area and high energy efficiency. For this purpose, in this paper, graphene nanoribbon field effect transistors (SBFETs) that compete with conventional MOSFET technology due to their higher current drive capabilities, ballistic transport, lower power-delay product (PDP), and higher thermal stability, are used for designing a full adder. Based on the promising properties of SBFETs, an ultra-low-leakage and low-voltage full adder cell with 18 transistors is proposed. The proposed design utilizes the unique features of MOSFET-like SBFETs for high performance. The simulations were performed using Synopsys HSPICE with 16nm MOS-SBFET technology and the simulation results show the superiority of the SBFET-based design in terms of speed and PDP compared to conventional and modern structures even at 0.5V supply voltage.

Keywords—Ultra-low leakage, 1-bit full adder, Graphene nano-ribbon field effect transistor (SBFET), Power-delay product (PDP), Low-Voltage.

### I. INTRODUCTION

Transistors are used as a major component in all electronic devices such as flash drives, laptop and desktop computers, radios, mobile phones and smartwatches. Due to the growing demand for electronic equipment, the production of high quality devices and various functions is important for electronic equipment manufacturers. As the scale of the MOSFET process in CMOS technology decreases, traditional silicon MOSFETs are no longer able to maintain Moore's law. Hence, engineers and scientists are trying to find a solution to overcome this challenge. One solution to this problem is to replace the conductor channels of MOSFETs with new materials such as silicon nanowires, carbon nanotubes, graphene, and graphene nano-ribbon [1]. According to reports published by International Technology Roadmap for Semiconductors ITRS, more research will be done on graphene and graphene nano-ribbon to replace silicon in the semiconductor industry, and it is predicted that traditional

silicon will be replaced by graphene nano-ribbon in the coming years [2].

Since graphene was discovered by Novoselov et al. in 2004, many researchers have become interested in research in this field [3]. Graphene is an open form of carbon nanotube, and carbon-based families include fullerene, graphene, and graphene nano-ribbon. Due to the special structure and excellent properties of graphene, studies on its mechanical and electronic properties have been done in many articles and it is predicted that in the near future graphene will be used as one of the best candidates in nano-devices as a conductive channel. Due to the fact that graphene nano-ribbon and carbon nanotubes originate from the same source and the process of making graphene nano-ribbon is easier compared to carbon nanotubes, there is a lot of interest in studying the performance of graphene nano-ribbon.

The demand for a full adder design with low operating voltage, low power consumption, high speed, low chip area and high energy efficiency has always been of interest [1,4]. Due to the severe limitations of the nanometer-scale MOSFET, the use of MOSFET as a main unit in full adder has now reached its functional limitations such as average power dissipation and speed. Therefore, in this paper, a new one-bit full adder based on SBFET is presented, whose structure hasan extremely low leakage and has a very high performance.

The rest of this article is organized as follows. In the second part, the proposed full adder cell design based on SBFET is presented. In the third part, the simulation results are presented and in the fourth part, the article ends with a conclusion.

### II. SBFET-BASED FULL ADDER DESIGN

Addition is the most important computational operation and is commonly used in any digital electronics and computational logic unit (ALU) to add any numeric value. Usually a one-bit adder cell is a full adder that has three inputs (A, B, and C<sub>in</sub>), and when these three inputs are added together, the Sum and Cout outputs are generated. The

31 B.Lakshmi, N. Muthukumaran

Dr.R.PANNEERÜHASS,M.E.,Ph.D.,
PRINCIPAL
PRINCI

ISSN: 2231-2099Volume 11 Issue 1 Jan-March 2021 Pages 31-35

# Relative Time Synchronization of Distributed System Clock of Applications for Software-in- theloop SiL Simulation

R.Nanthini\*, V.Maha, S.Deevika, R.Bharathi,

Department of Computer Science And Engineering, A.R. Engineering College, Villupuram
E-mail: nandhini.cse@gmail.com

Abstract—As distributed systems such as automotive, medical, manufacturing automation become larger and more complex, it is difficult to test these systems. Also, the synchronization of distributed applications make the testing more difficult. In the Software-in-the-Loop (SiL) simulation, a synchronization method among clock of applications is provided for virtual hardware devices and environment. A typical synchronization technique is that a single global clock synchronizes local clocks of other sites but may make high accuracy but low performance in SiL simulation because synchronization occurs in all nodes when the global clock ticks. Also there are some issues of which node should be selected, how much time the global clock drifts when adding new sites, etc. In the paper, we propose a method of clock synchronization based on relative time to enhance the simulation performance.

Keywords—Synchronization: Relative: Distributed; Simulation; Software-in-the-loop;

#### I INTRODUCTION

Recently, as the IT convergence industry has been enlarged and more wider, the scale of embedded system become more bigger in the form of distributed system such as automotive. medical, manufacturing automation, etc. [1-3]. Thus, it is necessary to test applications of these distributed embedded systems but it is difficult to test these applications since the testing environment of distributed applications should provide both the execution environment and synchronization mechanism among distributed sites [3-5]. The process of testing embedded testing is shown Fig. 1. Generally, testing of embedded system is performed with MiL(Model-in-the-Loop), SiL(Software-in-the-Loop) and HiL (Hardware-in-the-Loop) in order. In this paper, we consider only level of SiL [6] which is testing without hardware. In SiL simulation of distributed applications, however, time synchronization is essential. In wireless sensor network, for example, time synchronization is a major topic because of high accuracy [7]

In distributed applications there are two issue of time synchronization. One is synchronization between the clock in an application and the clock in real world, which is absolute synchronization. The other is synchronization among clock of applications, which is relative synchronization [5]. In SiL simulation relative synchronization is important more than absolute synchronization because environment and hardware is not real but virtual. Thus, in this paper, we consider only relative synchronization. A typical synchronization technique is using global clock [8]. This technique is that only global clock synchronizes clocks of the others but may make high accuracy low performance in SIL simulation because synchronization occurs in all nodes when global clock ticks. Also there are some issues that which node should be selected, that new node be required, that how much time global clock drift, etc.

So for high performance of SiL simulation including in synchronization and above issues, we propose a method of relative time synchronization. This paper is organized as follows: Section II introduces synchronization of related works; Section III presents the main idea of relative time synchronization: Section IV shows case study; Section V shows evaluation of our method; Section VI provides conclusion.

### II. REALATED WORKS

IEEE 1588 standard [9-11] defines PTP(precision time protocol) which enables precise synchronization of clocks in distributed system. Because each system has its clock which is




Fig. 1. Process of testing embedded system

R.Nanthini\*, V.Maha, S.Deevika, R.Bharathi



Dr.R.PANNEERDHASS, M.E., Ph.D.,
PRINCIPAL
POST,
VADAKUCHIPALAYAM,
VILLUPURAMIBOS, 6841.
VILLUPURAMIBOS, 6841.